

Heat Shrinkable Tubing 3:1 on a Reel

• HIS-A - with adhesive liner

HIS-A forms a seal against moisture and protect against corrosion and mechanical abrasion.

Features and Benefits

- Adhesive lined heat shrink tubing
- Inner wall melts when heated and is forced into gaps
- Adhesive forms seal against moisture as tubing cools
- Protects components
- Available in black and transparent
- 6 sizes for wide range of applications



HIS-A - with adhesive liner

MATERIAL	Polyolefin, cross-linked (PO-X)		
Shrink Ratio	3:1		
Operating Temperature	-55 °C to +125 °C		
Minimum Shrink Temperature	+100 °C		
Longitudinal change after shrinkage	-10% max.		
Softening Point Adhesive	+85 °C		
Dielectric Strength	15 kV/mm according to IEC 60684 P2		
Flammability	UL224 VW-1 (except clear)		
Insulation Class	A (VDE 0530)		
Specifications	CSA, SAE - AMS - DTL-23053 / 4		



WT D Ч

Heat Shrinkable Tubing 3:1 with adhesive

ТҮРЕ	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Article-No.
HIS-A-3/1	3.0	1.0	1.00	10 m	Black (BK)	308-10300
	3.0	1.0	1.00	10 m	Transparent (CL)	308-10303
HIS-A-6/2	6.0	2.0	1.00	5 m	Black (BK)	308-10600
	6.0	2.0	1.00	5 m	Transparent (CL)	308-10603
HIS-A-9/3	9.0	3.0	1.40	5 m	Black (BK)	308-10900
	9.0	3.0	1.40	5 m	Transparent (CL)	308-10903
HIS-A-12/4	12.0	4.0	1.80	5 m	Black (BK)	308-11200
	12.0	4.0	1.80	5 m	Transparent (CL)	308-11203
HIS-A-18/6	18.0	6.0	2.25	4 m	Black (BK)	308-11800
	18.0	6.0	2.25	4 m	Transparent (CL)	308-11803
HIS-A-24/8	24.0	8.0	2.50	3 m	Black (BK)	308-12400
	24.0	8.0	2.50	3 m	Transparent (CL)	308-12403

All dimensions in mm. Subject to technical changes. Minimum Order Quantity (MOQ) may differ from package content.



Please note! Not all products listed on this page may have this approval. For product specific approvals please refer to the Appendix.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Shrink Tubing and Sleeves category:

Click to view products by Hellermann manufacturer:

Other Similar products are found below :

770-006S102
5685710001
CR6145-000
CR8248-000
CR9960-000
603312-4
607381P039
617867N001
6500750004
D-306-38
770-003S106W2

770-007A303
770-010Y106W1
770-010Y706W1
7771210001
MFP-1/4"-Clear
MFP-3/64"-Clear
MFT-MT2000-NO.14-0-SP
MFT-MT2000-NO.65-X-SP

NO.65-X-SP
MHHT-4-15K2-G-104
MIL-LT-1-1/2-4-SP
MIL-LT-1-1/2-9-STK
MIL-LT-1/2-2-STK
MIL-LT-3/0-SP
MIL-LT-3/32-0-SP
MIL-LT-3/3