

# HSMW-C230

## White Color Side-Mount ChipLED

---

### Description

The Broadcom<sup>®</sup> HSMW-C230 is a side-emitting surface-mount chipLED. This chipLED comes in small package footprint of 1.0 mm × 0.55 mm. Its small form factor allows flexible board design, and the LED can be closely mounted, thus offering maximum miniaturization benefits to the user.

The low package height of 0.3 mm makes it an ideal solution for an application that has limited head room, such as wearables and small portable handheld devices.

By using efficient and high brightness InGaN LED materials, this product is capable of delivering high light output. It is compatible with industry-standard automatic machine placement and reflow soldering.

### Features


- LEDs with InGaN die
- Surface-mount device with 0.30-mm height
- Compatible with reflow soldering
- Tape in 8-mm carrier tape on a 7-in. diameter reel

### Applications

- Backlighting
- Indicator

**CAUTION!** LEDs are class 1A ESD sensitive per ANSI/ESDA/JEDEC JS-001. Please observe appropriate precautions during handling and processing. Refer to Application Note AN-1142 for additional details.

Figure 1: Package Dimensions

**NOTE:**

1. All dimensions are in millimeters.
2. Tolerance  $\pm 0.1$  mm unless otherwise specified.
3. Encapsulant: clear epoxy

**Absolute Maximum Value at  $T_J = 25^\circ\text{C}$** 

| Parameter                         | Rating     | Units            |
|-----------------------------------|------------|------------------|
| DC Forward Current <sup>a</sup>   | 10         | mA               |
| Peak Forward Current <sup>b</sup> | 40         | mA               |
| Power Dissipation                 | 31         | mW               |
| LED Junction Temperature          | 95         | $^\circ\text{C}$ |
| Operating Temperature             | -40 to +85 | $^\circ\text{C}$ |
| Storage Temperature               | -40 to +85 | $^\circ\text{C}$ |

a. Derate as shown in [Figure 11](#).

b. Duty factor = 10%, frequency = 1 kHz.

## Optical/Electrical Characteristics at $T_J = 25^\circ\text{C}$ , $I_F = 5\text{ mA}$

| Parameter   | Min. | Typ. | Max. | Units              |
|---|------|------|------|--------------------|
| Luminous Intensity, $I_v^a$                                 | 45.0 | —    | —    | mcd                |
| Viewing Angle, $2\theta_{1/2}^b$                            | —    | 175  | —    | degree             |
| Forward Voltage, $V_F$                                      | 2.55 | —    | 3.15 | V                  |
| Reverse Current, $I_R$ (at $V_R = 5\text{V}$ ) <sup>c</sup> | —    | —    | 100  | $\mu\text{A}$      |
| Thermal Resistance, $R\theta_{J-S}$                         | —    | 320  | —    | $^\circ\text{C/W}$ |

- The luminous intensity is measured at the mechanical axis of the LED package. The actual peak of the spatial radiation pattern may not be aligned with the axis.
- Viewing angle is the off-axis angle where the luminous intensity is  $\frac{1}{2}$  the peak intensity.
- Indicates the product final test condition. Long-term reverse bias is not recommended.

# Bin Information

## Intensity Bins (CAT)

| Bin ID | Luminous Intensity (mcd) |        |
|--------|--------------------------|--------|
|        | Min.                     | Max.   |
| P      | 45.0                     | 71.5   |
| Q      | 71.5                     | 112.5  |
| R      | 112.5                    | 180.0  |
| S      | 180.0                    | 285.0  |
| T      | 285.0                    | 450.0  |
| U      | 450.0                    | 715.0  |
| V      | 715.0                    | 1125.0 |
| W      | 1125.0                   | 1800.0 |
| X      | 1800.0                   | 2850.0 |
| Y      | 2850.0                   | 4500.0 |

Tolerance  $\pm 15\%$ .

## Forward Voltage Bins

| Bin ID | Forward Voltage (V) |      |
|--------|---------------------|------|
|        | Min.                | Max. |
| 1      | 2.55                | 2.75 |
| 2      | 2.75                | 2.95 |
| 3      | 2.95                | 3.15 |


Tolerance  $\pm 0.1V$ .

## Color Bins (BIN)

| Bin ID | Chromaticity Coordinates |        |
|--------|--------------------------|--------|
|        | x                        | y      |
| C1     | 0.2500                   | 0.2050 |
|        | 0.2500                   | 0.2500 |
|        | 0.2700                   | 0.2775 |
|        | 0.2700                   | 0.2325 |
| D1     | 0.2900                   | 0.2600 |
|        | 0.2900                   | 0.3025 |
|        | 0.3100                   | 0.3325 |
|        | 0.3100                   | 0.2875 |
| C2     | 0.2700                   | 0.2325 |
|        | 0.2700                   | 0.2775 |
|        | 0.2900                   | 0.3050 |
|        | 0.2900                   | 0.2600 |
| D2     | 0.3100                   | 0.2875 |
|        | 0.3100                   | 0.3325 |
|        | 0.3300                   | 0.3600 |
|        | 0.3300                   | 0.3150 |

Tolerance  $\pm 0.001$ .

**Figure 2: Chromaticity Coordinates Diagram**



Example of bin information on reel and packaging label:

CAT: P  $\rightarrow$  White = lv bin P

BIN: C1  $\rightarrow$  White = color bin C1

Figure 3: Intensity vs. Wavelength




Figure 4: Forward Current vs. Forward Voltage




Figure 5: Intensity vs. Forward Current




Figure 6: Intensity vs. Angle




Figure 7: Wavelength vs. Forward Current




Figure 8: Intensity vs. Temperature




Figure 9: Wavelength vs. Temperature




Figure 10: Forward Voltage vs. Temperature




Figure 11: Forward Current vs. Temperature





Figure 12: Recommended Solder Pad (Units: mm)








## Soldering

Figure 15: Recommended Reflow Soldering Conditions



- Reflow soldering must not be done more than twice. Observe necessary precautions of handling moisture sensitive device as stated in the following section.
- Do not apply any pressure or force on the LED during reflow and after reflow when the LED is still hot.
- Use reflow soldering to solder the LED. If unavoidable (such as rework), use manual hand soldering strictly controlled to the following conditions:
  - Soldering iron tip temperature = 310°C maximum
  - Soldering duration = 2 seconds maximum
  - Number of cycles = 1 only
  - Power of soldering iron = 50W maximum
- Do not touch the LED package body with the soldering iron except for the soldering terminals because it might cause damage to the LED.
- Confirm beforehand whether the functionality and performance of the LED is affected by hand soldering.

## Precautionary Notes

### Handling of a Moisture-Sensitive Device

This product has a Moisture Sensitive Level 2a rating per JEDEC J-STD-020. Refer to Broadcom Application Note AN5305, *Handling of Moisture Sensitive Surface Mount Devices*, for additional details and a review of proper handling procedures.

#### ■ Before use

- An unopened moisture barrier bag (MBB) can be stored at < 40°C/90% RH for 12 months. If the actual shelf life has exceeded 12 months and the humidity indicator card (HIC) indicates that baking is not required, it is safe to reflow the LEDs per the original MSL rating.
- Do not open the MBB prior to assembly (for example, for IQC).

#### ■ Control after opening the MBB

- Read the HIC immediately upon opening the MBB.
- Keep the LEDs at < 30°C/60% RH at all times, and all high-temperature-related processes, including soldering, curing, or rework, must be completed within 672 hours.

#### ■ Control for unfinished reel

Store unused LEDs in a sealed MBB with desiccant or desiccator at < 5% RH.

#### ■ Control of assembled boards

If the PCB soldered with the LEDs is to be subjected to other high-temperature processes, store the PCB in a sealed MBB with desiccant or desiccator at < 5% RH to ensure that all LEDs have not exceeded their floor life of 672 hours.

#### ■ Baking is required if the following conditions exist:

- The HIC indicator indicates a change in color for 10% and 5% as stated on the HIC.
- The LEDs are exposed to conditions of > 30°C/60% RH at any time.
- The LEDs' floor life exceeded 672 hours.

The recommended baking condition is: 60°C ±5°C for 20 hours.

Baking should only be done once.

## Application Precautions

- The drive current of the LED must not exceed the maximum allowable limit across temperature as stated in the data sheet. Constant current driving is recommended to ensure consistent performance.
- LEDs exhibit slightly different characteristics at different drive currents that might result in larger performance variations (that is, intensity, wavelength, and forward voltage). Set the application current as close as possible to the test current to minimize these variations.
- The LED is not intended for reverse bias. Use other appropriate components for such purposes. When driving the LED in matrix form, ensure that the reverse bias voltage does not exceed the allowable limit of the LED.
- Avoid rapid change in ambient temperature, especially in high humidity environments, because this will cause condensation on the LED.
- If the LED is intended to be used in harsh environments, protect the LED against damages caused by rain water, dust, oil, corrosive gases, external mechanical stress, and so on.

## Disclaimer

Broadcom's products are not specifically designed, manufactured, or authorized for sale as parts, components, or assemblies for the planning, construction, maintenance, or direct operation of a nuclear facility or for use in medical devices or applications. The customer is solely responsible, and waives all rights to make claims against Broadcom or its suppliers, for all loss, damage, expense, or liability in connection with such use.

Broadcom, the pulse logo, Connecting everything, Avago Technologies, Avago, and the A logo are among the trademarks of Broadcom and/or its affiliates in the United States, certain other countries and/or the EU.

Copyright © 2017 by Broadcom. All Rights Reserved.

The term "Broadcom" refers to Broadcom Limited and/or its subsidiaries. For more information, please visit [www.broadcom.com](http://www.broadcom.com).

Broadcom reserves the right to make changes without further notice to any products or data herein to improve reliability, function, or design. Information furnished by Broadcom is believed to be accurate and reliable. However, Broadcom does not assume any liability arising out of the application or use of this information, nor the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Standard LEDs - SMD category](#):*

*Click to view products by [Broadcom manufacturer](#):*

Other Similar products are found below :

[LTST-N683GBEW](#) [597-3006-607F](#) [LTW-170ZDC](#) [597-3403-607F](#) [LTW-K140SZR40](#) [LTW-M140ZVS](#) [598-8110-100F](#) [598-8170-100F](#)  
[598-8610-202F](#) [7012X7](#) [AAAF5060QBFSEEZGS](#) [APT1608QGW](#) [ASMT-YTC7-0AA02](#) [EASV1803BA0](#) [HT-F104TW-5860](#) [KA-3528YT](#)  
[SML310BATT86](#) [SML-512VWT86A](#) [SML-LX0606SISUGC/A](#) [SML-LXL1307SRC-TR](#) [SML-LXR851SIUPGUBC](#) [LT1ED53A](#) [17-21/G6C-](#)  
[FM1N2B/3T](#) [FAT801-S](#) [AM27ZGC03](#) [APB3025SGNC](#) [APFA3010SURKCGKQBDC](#) [APHK1608VGCA](#) [APT2012QGW](#) [CLMVC-FKA-](#)  
[CA1E1L81BB7C3C3](#) [CLX6D-FKB-CN1R1H1BB7D3D3](#) [CLYBA-FKA-CFHHL9BBB7A363](#) [CMD11504UR](#) [LTST-C250KGKT](#) [LTW-](#)  
[010DCG](#) [LTW-21TS5](#) [LTW-220DS5](#) [LTW-K140SZR30](#) [ASMB-BTE1-0B332](#) [ASMT-CW00](#) [MP-1616-2103-50-80](#) [BR1102W-TR-LF](#)  
[HSMY-C177](#) [HT-121UYG-4739](#) [JANTXM19500/521-02](#) [UYGT801-S](#) [KVH1C100MF6R](#) [42-21SYGC/S530-E1/TR8](#) [YGFR411-H](#) [597-](#)  
[2311-402F](#)