

Accessories - IC-DFR 12 - 1852121

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Accessories, Number of positions: 12, Pitch: 5.08 mm, Color: green, This assembly frame can only be used in combination with IC 2,5/...-STGF-5,08

Why buy this product

- Feed-through assembly frame for inverted COMBICON plug IC 2,5/-STGF-5,08
- Vibration-resistant screw connection for both plugs provided by screw flanges
- Fitting the MSTB 2,5/...-STF-5,08 plug from outside
- Frame in plate cutout can be used and screwed on.
- Snap-locking of the IC plug into the frame
- Up to a panel thickness of 1.5 mm, the frame can be screwed before the IC plug is mounted



Key Commercial Data

Packing unit	50 pc
Minimum order quantity	50 pc
GTIN	4 017918 109004
Weight per Piece (excluding packing)	2.9 g
Custom tariff number	39269097
Country of origin	Poland

Technical data

Dimensions

Pitch	5.08 mm
Dimension a	55.88 mm

General

Range of articles	IC-DFR
Insulating material group	I
Nominal cross section	2.5 mm ²
Insulating material	PA

Accessories - IC-DFR 12 - 1852121

Technical data

General

Flammability rating according to UL 94	V0
Number of positions	12

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440210

ETIM

ETIM 3.0	EC000879
ETIM 4.0	EC000879
ETIM 5.0	EC002310

UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Accessories

Accessories

Mounting material

Screw set - DFK-MSTB-SS - 0708263



Screw set, for securing the header to the device wall, consists of an M3 x 10 screw, with a spring washer and a nut

PCB plug

Accessories - IC-DFR 12 - 1852121

Accessories


Printed-circuit board connector - IC 2,5/12-STGF-5,08 - 1825608

Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 12, Pitch: 5.08 mm, Connection method: Screw connection with tension sleeve, Color: green, Contact surface: Tin




Drawings

Drilling diagram



Dimensional drawing



Dimension b: 10.84 mm + (no. of pos. x 5.08 mm)

Dimension c: Dim. b + 5.83 mm

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminal Blocks - Unspecified](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[RST-20P](#) [NUSC4-WH](#) [TB200-15L1L2QC7](#) [11368](#) [TB100-08BSL10J4](#) [5606874](#) [LZW-B4.2 A12-4160](#) [LZW-B4.6 A12-4660](#) [FCR7900](#)
[FCR79001](#) [88486403](#) [ESKW 1/5 ST E3](#) [88486708](#) [ESKW 1/5 KU](#) [88545276](#) [ESKL 0E PA ST TRA](#) [88838208](#) [ESKW 1/2 KU](#) [88838304](#)
[ESKW 1/2 ST](#) [264-373](#) [LZW-B4.3 A12-4260](#) [294-4013](#) [HDFK 4 0707086](#) [HDFKV 50 0708522](#) [E.4203](#) [TSCB4-02P-15-01AH](#) [TSCB4-01P-](#)
[15-01AH](#) [TSCB4-03P-15-01AH](#) [294-4002](#) [E.4204](#) [5604707](#) [SLK3/2/D1-D2](#) [88167524](#) [231-127](#) [262-142](#) [264-112](#) [294-4003](#) [FCR7901](#)
[FCR79011](#) [CMDB4/4/BG](#) [HH-REC](#) [ETBF60020H2FLZ](#) [GP+WP A12-6302](#) [4721-P4](#) [4721-P8](#) [2727608](#) [SLK3/3/N-E-L](#) [88167527](#)