

International Rectifier

IRF6612PbF IRF661TRPbF

- RoHs Compliant ①
- Lead-Free (Qualified up to 260°C Reflow)
- Application Specific MOSFETs
- Ideal for CPU Core DC-DC Converters
- Low Conduction Losses
- High CdV/dt Immunity
- Low Profile (<0.7mm)
- Dual Sided Cooling Compatible ①
- Compatible with existing Surface Mount Techniques ①

Applicable DirectFET Package/Layout Pad (see p.8,9 for details)

| SQ | SX | ST | MQ | MX | MT | | | |
|----|----|----|----|----|----|--|--|--|
|----|----|----|----|----|----|--|--|--|

Description

The IRF6612PbF combines the latest HEXFET® Power MOSFET Silicon technology with the advanced DirectFET™ packaging to achieve the lowest on-state resistance in a package that has the footprint of a SO-8 and only 0.7 mm profile. The DirectFET package is compatible with existing layout geometries used in power applications, PCB assembly equipment and vapor phase, infra-red or convection soldering techniques. Application note AN-1035 is followed regarding the manufacturing methods and processes. The DirectFET package allows dual sided cooling to maximize thermal transfer in power systems, improving previous best thermal resistance by 80%.

The IRF6612PbF balances industry leading on-state resistance while minimizing gate charge along with ultra low package inductance to reduce both conduction and switching losses. The reduced losses make this product ideal for high frequency/high efficiency DC-DC converters that power high current loads such as the latest generation of microprocessors. The IRF6612PbF has been optimized for parameters that are critical in synchronous buck converter's SyncFET sockets.

Absolute Maximum Ratings

| | Parameter | Max. | Units |
|--------------------------------|---|----------|-------|
| V_{DS} | Drain-to-Source Voltage | 30 | V |
| V_{GS} | Gate-to-Source Voltage | ± 20 | |
| $I_D @ T_C = 25^\circ\text{C}$ | Continuous Drain Current, $V_{GS} @ 10\text{V}$ ③ | 136 | |
| $I_D @ T_A = 25^\circ\text{C}$ | Continuous Drain Current, $V_{GS} @ 10\text{V}$ ③ | 24 | A |
| $I_D @ T_A = 70^\circ\text{C}$ | Continuous Drain Current, $V_{GS} @ 10\text{V}$ ④ | 19 | |
| I_{DM} | Pulsed Drain Current ⑤ | 190 | |
| E_{AS} | Single Pulse Avalanche Energy ⑥ | 37 | mJ |
| I_{AR} | Avalanche Current ⑤ | 19 | A |




Fig 1. Typical On-Resistance vs. Gate-to-Source Voltage

Notes:


- ① Click on this section to link to the appropriate technical paper.
- ② Click on this section to link to the DirectFET Website.
- ③ Surface mounted on 1 in. square Cu board, steady state.

www.irf.com

IRF6612PbF
IRF661TRPbF
DirectFET™ Power MOSFET ②

Typical values (unless otherwise specified)

| V_{DSS} | V_{GS} | $R_{DS(on)}$ | $R_{DS(on)}$ |
|-----------|----------------------|--------------|--------------|
| 30V max | $\pm 20\text{V}$ max | 2.5mΩ@ 10V | 3.4mΩ@ 4.5V |
| Q_g tot | Q_{gd} | Q_{gs2} | Q_{rr} |
| 30nC | 10nC | 2.9nC | 8.1nC |



DirectFET™ ISOMETRIC





Fig 2. Total Gate Charge vs. Gate-to-Source Voltage

- ④ T_C measured with thermocouple mounted to top (Drain) of part.
- ⑤ Repetitive rating; pulse width limited by max. junction temperature.
- ⑥ Starting $T_J = 25^\circ\text{C}$, $L = 0.20\text{mH}$, $R_G = 25\Omega$, $I_{AS} = 19\text{A}$.

Static @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

| | Parameter | Min. | Typ. | Max. | Units | Conditions |
|--|--|------|------|------|----------------------|--|
| BV_{DSS} | Drain-to-Source Breakdown Voltage | 30 | — | — | V | $\text{V}_{\text{GS}} = 0\text{V}, \text{I}_D = 250\mu\text{A}$ |
| $\Delta \text{BV}_{\text{DSS}}/\Delta T_J$ | Breakdown Voltage Temp. Coefficient | — | 24 | — | mV/ $^\circ\text{C}$ | Reference to $25^\circ\text{C}, \text{I}_D = 1\text{mA}$ |
| $\text{R}_{\text{DS(on)}}$ | Static Drain-to-Source On-Resistance | — | 2.5 | 3.3 | m Ω | $\text{V}_{\text{GS}} = 10\text{V}, \text{I}_D = 24\text{A}$ ⑦ |
| | | — | 3.4 | 4.4 | | $\text{V}_{\text{GS}} = 4.5\text{V}, \text{I}_D = 19\text{A}$ ⑦ |
| $\text{V}_{\text{GS(th)}}$ | Gate Threshold Voltage | 1.35 | 1.8 | 2.25 | V | $\text{V}_{\text{DS}} = \text{V}_{\text{GS}}, \text{I}_D = 250\mu\text{A}$ |
| $\Delta \text{V}_{\text{GS(th)}}/\Delta T_J$ | Gate Threshold Voltage Coefficient | — | -5.6 | — | mV/ $^\circ\text{C}$ | |
| I_{DSS} | Drain-to-Source Leakage Current | — | — | 1.0 | μA | $\text{V}_{\text{DS}} = 24\text{V}, \text{V}_{\text{GS}} = 0\text{V}$ |
| | | — | — | 100 | | $\text{V}_{\text{DS}} = 24\text{V}, \text{V}_{\text{GS}} = 0\text{V}, T_J = 125^\circ\text{C}$ |
| I_{GSS} | Gate-to-Source Forward Leakage | — | — | 100 | nA | $\text{V}_{\text{GS}} = 20\text{V}$ |
| | Gate-to-Source Reverse Leakage | — | — | -100 | | $\text{V}_{\text{GS}} = -20\text{V}$ |
| g_{fs} | Forward Transconductance | 96 | — | — | S | $\text{V}_{\text{DS}} = 15\text{V}, \text{I}_D = 19\text{A}$ |
| Q_{g} | Total Gate Charge | — | 30 | 45 | nC | |
| Q_{gs1} | Pre-V _{th} Gate-to-Source Charge | — | 8.5 | — | | $\text{V}_{\text{DS}} = 15\text{V}$ |
| Q_{gs2} | Post-V _{th} Gate-to-Source Charge | — | 2.9 | — | | $\text{V}_{\text{GS}} = 4.5\text{V}$ |
| Q_{gd} | Gate-to-Drain Charge | — | 10 | — | | $\text{I}_D = 19\text{A}$ |
| Q_{godr} | Gate Charge Overdrive | — | 8.6 | — | | See Fig. 14 |
| Q_{sw} | Switch Charge ($\text{Q}_{\text{gs2}} + \text{Q}_{\text{gd}}$) | — | 13 | — | nC | |
| Q_{oss} | Output Charge | — | 18 | — | | $\text{V}_{\text{DS}} = 16\text{V}, \text{V}_{\text{GS}} = 0\text{V}$ |
| $t_{\text{d(on)}}$ | Turn-On Delay Time | — | 15 | — | | $\text{V}_{\text{DD}} = 16\text{V}, \text{V}_{\text{GS}} = 4.5\text{V}$ ③ |
| t_r | Rise Time | — | 52 | — | | $\text{I}_D = 19\text{A}$ |
| $t_{\text{d(off)}}$ | Turn-Off Delay Time | — | 21 | — | ns | Clamped Inductive Load |
| t_f | Fall Time | — | 4.8 | — | | See Fig. 15 & 16 |
| C_{iss} | Input Capacitance | — | 3970 | — | pF | $\text{V}_{\text{GS}} = 0\text{V}$ |
| C_{oss} | Output Capacitance | — | 780 | — | | $\text{V}_{\text{DS}} = 15\text{V}$ |
| C_{rss} | Reverse Transfer Capacitance | — | 360 | — | | $f = 1.0\text{MHz}$ |

Diode Characteristics

| | Parameter | Min. | Typ. | Max. | Units | Conditions |
|------------------------|---|------|------|------|-------|---|
| I_S | Continuous Source Current (Body Diode) | — | — | 110 | A | MOSFET symbol showing the integral reverse p-n junction diode. |
| | Pulsed Source Current (Body Diode) ① | — | — | 190 | |  |
| V_{SD} | Diode Forward Voltage | — | — | 1.0 | V | $T_J = 25^\circ\text{C}, \text{I}_S = 19\text{A}, \text{V}_{\text{GS}} = 0\text{V}$ ⑦ |
| t_{rr} | Reverse Recovery Time | — | 19 | 29 | ns | $T_J = 25^\circ\text{C}, \text{I}_F = 19\text{A}$ |
| Q_{rr} | Reverse Recovery Charge | — | 8.1 | 12 | nC | $d\text{i}/dt = 100\text{A}/\mu\text{s}$ ⑦ See Fig. 17 |

Notes:

⑤ Repetitive rating; pulse width limited by max. junction temperature.

⑦ Pulse width $\leq 400\mu\text{s}$; duty cycle $\leq 2\%$.

Absolute Maximum Ratings

| | | | |
|--------------------------------|----------------------------|-------------|------------------|
| $P_D @ T_A = 25^\circ\text{C}$ | Power Dissipation ③ | 2.8 | W |
| $P_D @ T_A = 70^\circ\text{C}$ | Power Dissipation ③ | 1.8 | |
| $P_D @ T_C = 25^\circ\text{C}$ | Power Dissipation ④ | 89 | |
| T_P | Peak Soldering Temperature | 270 | $^\circ\text{C}$ |
| T_J | Operating Junction and | -40 to +150 | |
| T_{STG} | Storage Temperature Range | | |

Thermal Resistance

| | Parameter | Typ. | Max. | Units |
|--------------|--------------------------|-------|------|---------------------|
| R_{0JA} | Junction-to-Ambient ③ ① | — | 45 | $^\circ\text{C/W}$ |
| R_{0JA} | Junction-to-Ambient ⑨ ① | 12.5 | — | |
| R_{0JA} | Junction-to-Ambient ⑩ ① | 20 | — | |
| R_{0JC} | Junction-to-Case ④ ① | — | 1.4 | |
| R_{0J-PCB} | Junction-to-PCB Mounted | 1.0 | — | |
| | Linear Derating Factor ③ | 0.022 | | W/C |





Fig 3. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

Notes:


③ Used double sided cooling , mounting pad.

① R_θ is measured at T_J of approximately 90°C .


⑩ Mounted on minimum footprint full size board with metalized back and with small clip heatsink.



③ Surface mounted on 1 in. square Cu (still air).



⑨ Mounted to a PCB with small clip heatsink (still air)



⑩ Mounted on minimum footprint full size board with metalized back and with small clip heatsink (still air)

IRF6612PbF

International
Rectifier




Fig 4. Typical Output Characteristics




Fig 5. Typical Output Characteristics




Fig 6. Typical Transfer Characteristics




Fig 7. Normalized On-Resistance vs. Temperature




Fig 8. Typical Capacitance vs.Drain-to-Source Voltage




Fig 9. Typical Source-Drain Diode Forward Voltage




Fig 10. Maximum Safe Operating Area




Fig 11. Maximum Drain Current vs. Case Temperature




Fig 12. Threshold Voltage vs. Temperature




Fig 13. Maximum Avalanche Energy vs. Drain Current

IRF6612PbF

International
IR Rectifier




Fig 14a. Gate Charge Test Circuit




Fig 14b. Gate Charge Waveform




Fig 15a. Unclamped Inductive Test Circuit




Fig 15b. Unclamped Inductive Waveforms




Fig 16a. Switching Time Test Circuit




Fig 16b. Switching Time Waveforms





Fig 17. Diode Reverse Recovery Test Circuit for N-Channel HEXFET® Power MOSFETs

DirectFET™ Substrate and PCB Layout, MX Outline ③ (Medium Size Can, X-Designation).

Please see DirectFET application note AN-1035 for all details regarding the assembly of DirectFET.

This includes all recommendations for stencil and substrate designs.




IRF6612PbF

International
IR Rectifier


DirectFET™ Outline Dimension, MX Outline (Medium Size Can, X-Designation).

Please see DirectFET application note AN-1035 for all details regarding the assembly of DirectFET.


This includes all recommendations for stencil and substrate designs.



DirectFET™ Part Marking




DirectFET™ Tape & Reel Dimension (Showing component orientation).



NOTE: Controlling dimensions in mm
Std reel quantity is 4800 parts. (ordered as IRF6612TRPBF). For 1000 parts on 7"
reel, order IRF6612TR1PBF

| REEL DIMENSIONS | | | | | | | | |
|-----------------|----------------------------|------|--------|----------|-----------------------|-------|-------|----------|
| CODE | STANDARD OPTION (QTY 4800) | | | | TR1 OPTION (QTY 1000) | | | |
| | METRIC | MIN | MAX | IMPERIAL | METRIC | MIN | MAX | IMPERIAL |
| A | 330.0 | N.C. | 12.992 | N.C. | 177.77 | N.C. | 6.9 | N.C. |
| B | 20.2 | N.C. | 0.795 | N.C. | 19.06 | N.C. | 0.75 | N.C. |
| C | 12.8 | 13.2 | 0.504 | 0.520 | 13.5 | 12.8 | 0.53 | 0.50 |
| D | 1.5 | N.C. | 0.059 | N.C. | 1.5 | N.C. | 0.059 | N.C. |
| E | 100.0 | N.C. | 3.937 | N.C. | 58.72 | N.C. | 2.31 | N.C. |
| F | N.C. | 18.4 | N.C. | 0.724 | N.C. | 13.50 | N.C. | 0.53 |
| G | 12.4 | 14.4 | 0.488 | 0.567 | 11.9 | 12.01 | 0.47 | N.C. |
| H | 11.9 | 15.4 | 0.469 | 0.606 | 11.9 | 12.01 | 0.47 | N.C. |

LOADED TAPE FEED DIRECTION



| DIMENSIONS | | | | | | | |
|------------|--------|-------|----------|-------|-----|-----|--|
| CODE | METRIC | | IMPERIAL | | MIN | MAX | |
| | MIN | MAX | MIN | MAX | | | |
| A | 7.90 | 8.10 | 0.311 | 0.319 | | | |
| B | 3.90 | 4.10 | 0.154 | 0.161 | | | |
| C | 11.90 | 12.30 | 0.469 | 0.484 | | | |
| D | 5.45 | 5.55 | 0.215 | 0.219 | | | |
| E | 5.10 | 5.30 | 0.201 | 0.209 | | | |
| F | 6.50 | 6.70 | 0.256 | 0.264 | | | |
| G | 1.50 | N.C. | 0.059 | N.C. | | | |
| H | 1.50 | 1.60 | 0.059 | 0.063 | | | |

Data and specifications subject to change without notice.
This product has been designed and qualified for the Consumer market.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903

Visit us at www.irf.com for sales contact information.05/06

Note: For the most current drawings please refer to the IR website at:
<http://www.irf.com/package/>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for MOSFET category:

Click to view products by Infineon manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [D2003UK](#) [705463DB](#) [MCH6422-TL-E](#) [FW231A-TL-E](#) [APT5010JFLL](#) [NTNS3A92PZT5G](#) [IRF100S201](#) [JANTX2N5237](#)
[2SK2464-TL-E](#) [2SK3818-DL-E](#) [FCA20N60_F109](#) [FDZ595PZ](#) [STD6600NT4G](#) [FQD4P40TM_AM002](#) [FSS804-TL-E](#) [FW217A-TL-2W](#)
[APT10050JVFR](#) [2SJ277-DL-E](#) [2SK1691-DL-E](#) [2SK2545\(Q,T\)](#) [D1014UK](#) [D2294UK](#) [405094E](#) [423220D](#) [MCH6646-TL-E](#) [TPCC8103,L1Q\(CM](#)
[IRF3710](#) [367-8430-0972-503](#) [VN1206L](#) [424134F](#) [026935X](#) [051075F](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [751625C](#) [873612G](#)
[IPS70R2K0CEAKMA1](#) [APT8015JVFR](#) [APT50M85JVR](#) [APT5010JVFR](#) [APT12031JFLL](#) [APT12040JVR](#) [NTE6400](#) [NVC3S5A51PLZT1G](#)
[JANTX2N6796U](#) [JANTX2N6784U](#)