

**Display Elektronik GmbH**

**DATA SHEET**

**LCD MODULE**

**DEM 800480D TMH-PW-N**

**5,0" TFT**

**Product Specification**

**Ver.: 2**

**04.03.2011**



## Contents

|   |    |
|---|----|
| 1. General Description and Features     | 4  |
| 1.1 Features                            | 4  |
| 1.2 LCD Module                          | 4  |
| 2. Mechanical Information               | 4  |
| 3. Electrical Specifications            | 5  |
| 3.1 Absolute Max. Ratings               | 5  |
| 3.2 AC Timing Characteristic of The LCD | 8  |
| 3.3 Back-Light Unit                     | 10 |
| 4. Optical Characteristics              | 11 |
| 4.1 Optical characteristic of the LCD   | 11 |
| 5. I/O Terminal                         | 13 |
| 5.1 Pin Assignment                      | 13 |
| 5.2 Block Diagram                       | 14 |
| 6. Displayed Color and Input Data       | 15 |
| 7. Reliability Condition                | 16 |
| 8. Dimensional Outlines                 | 17 |

## 1. General Description and Features

DEM 800480D TMH-PW-N is a transmissive type color active matrix TFT (Thin Film Transistor) liquid crystal display (LCD) that uses amorphous silicon TFT as a switching device. This model is composed of a TFT-LCD module, a driver circuit and a back-light unit. Graphics and texts can be displayed on a WVGA 800 (W) x 3 x 480 (H) dots (15:9 aspect ratio) with 16.7M colors by supplying 24 bits data signal (8 bits/each color). The following table described the features of DEM 800480D TMH-PW-N.

### 1.1 Features

- Transmissive and back-light with 14 LEDs are available.
- TN (Twisted Nematic) mode.
- Digital RGB (8 bits/color) data transfer.
- Data enable mode.
- ROHS Compliance

### 1.2 LCD Module

| Item               | Specification                            | Unit     |
|--------------------|--|----------|
| Screen Size        | 5.0 inches                               | Diagonal |
| Display Resolution | 800 (H) x 480 (V)                        | Pixel    |
| Active Area        | 108 (H) x 64.8 (V)                       | mm       |
| Outline Dimension  | 118.5 (H) x 77.55 (V) x 3.4 (T)          | mm       |
| Display Mode       | Normally white mode/ Transmissive        | --       |
| Pixel Arrangement  | R,G,B Vertical Stripe                    | --       |
| Pixel Size         | 135 x 135                                | um       |
| Display Color      | 16.7 M                                   | --       |
| Viewing Direction  | 6 o'clock                                | --       |
| Input Interface    | Digital RGB (8 bits/color) Data Transfer | --       |

## 2. Mechanical Information

| Item        | Min.           | Typ.   | Max.  | Unit   | Note |     |
|-------------|----------------|--------|-------|--------|------|-----|
| Module Size | Horizontal (H) | 118.35 | 118.5 | 118.65 | mm   |     |
|             | Vertical (V)   | 77.4   | 77.55 | 77.70  | mm   |     |
|             | Thickness (T)  | 3.1    | 3.4   | 3.7    | mm   | (1) |
| Weight      | --             | (62)   | --    | g      | --   |     |

Note (1) Not Include Component . Refer to the Outline Dimension Drawing as attached.

**3. Electrical Specifications****3.1 Absolute Max. Ratings**

## 3.1.1 Absolute Ratings of Environment

If the operating condition exceeds the following absolute maximum ratings, the TFT LCD module may be damaged permanently.

( $T_a=25\pm 2^\circ\text{C}$ ,  $V_{SS}=\text{GND}=0$ )

| Item                  | Symbol    | Min. | Max. | Unit | Note    |
|-----------------------|-----------|------|------|------|---------|
| Storage temperature   | $T_{STG}$ | -30  | 80   | °C   | (1)     |
| Operating temperature | $T_{OPR}$ | -20  | 70   | °C   | (1,2,3) |

Note (1) 95 % RH Max. (  $40^\circ\text{C} \geq T_a$  ). Maximum wet-bulb temperature at  $39^\circ\text{C}$  or less. ( $T_a > 40^\circ\text{C}$ ) No condensation.

Note (2) In case of below  $0^\circ$ , the response time of liquid crystal (LC) becomes slower and the color of panel becomes darker than normal one. Level of retardation depends on temperature, because of LC's character


Note (3) Only operation is guaranteed at operating temperature. Contrast, response time, another display quality are evaluated at  $+25^\circ\text{C}$ .

3.1.2 Electrical Absolute Maximum Ratings

(V<sub>SS</sub>=GND=0)

| Parameter                       | Symbol                              | Min. | Max.                 | Unit  | Remark                 |
|---------------------------------|-------------------------------------|------|----------------------|-------|------------------------|
| Power supply voltage            | V <sub>DD</sub>                     | -0.5 | 5.0                  | V     |                        |
| Signal input voltage            | R0-R7,G0-G7,<br>B0-B7,DCLK,DE,HS,VS | -0.3 | V <sub>DD</sub> +0.3 | V     | --                     |
| Permissive input ripple voltage | V <sub>RF</sub>                     | --   | 100                  | mVp-p | V <sub>DD</sub> =+3.3V |

Display On/Off Sequence :



**Note :**


- (1) The supply voltage of the external system for the module input should be the same as the definition of V<sub>DD</sub>.
- (2) Apply the lamp voltage within the LCD operation range. When the back-light turns on before the LCD operation or the LCD turns off before the back-light turns off, the display may momentarily become white.
- (3) In case of V<sub>DD</sub> = off level, please keep the level of input signal on the low or keep a high impedance.
- (4) TP4 should be measured after the module has been fully discharged between power off and on period.
- (5) Interface signal shall not be kept at high impedance when the power is on.

3.1.3 DC Electrical Characteristics of the TFT LCD

(Ta=25±2°C, V<sub>SS</sub>=GND=0)

| Item                    | Symbol  | Min.    | Typ. | Max.    | Unit | Remark |
|-------------------------|---------|---------|------|---------|------|--------|
| Power supply            | VDD     | 3.0     | 3.3  | 3.6     | V    |        |
| Input Voltage for logic | H Level | 0.7xVDD | -    | VDD     | V    |        |
|                         | L Level | 0       | -    | 0.3xVDD | V    |        |
| Power Supply current    | IDD     | -       | -    | (220)   | mA   | Note 1 |

Note1: f<sub>v</sub> =60Hz , Ta=25°C , Display pattern : Gray pattern



## 3.2 AC Timing Characteristic of The LCD


## 3.2.1 Timing Condition (DE only mode)

| Signal     | Parameter               | Symbol    | Min. | Typ. | Max. | Unit. | Remark |
|------------|-------------------------|-----------|------|------|------|-------|--------|
| DCLK       | DCLK cycle time         | $T_{cph}$ | 25   | -    | -    | ns    |        |
|            | DCLK Frequency          | $f_{clk}$ | -    | 30   | 40   | MHz   |        |
|            | DCLK High plus width    | $T_{cwh}$ | 40   | 50   | 60   | %     |        |
| Horizontal | HSD setup time          | $T_{hst}$ | 8    | -    | -    | ns    |        |
|            | HSD hold time           | $T_{hhd}$ | 8    | -    | -    | ns    |        |
|            | Horizontal display area | $t_{hd}$  | -    | 800  | -    | Tcph  |        |
|            | HSD period time         | $t_h$     | -    | 928  | -    | Tcph  |        |
|            | HSD pulse width         | $t_{hpw}$ | 1    | 48   | -    | Tcph  |        |
|            | HSD back porch          | $t_{hb}$  | -    | 40   | -    | Tcph  |        |
|            | HSD front porch         | $t_{hfp}$ | -    | 40   | -    | Tcph  |        |
| Vertical   | VSD setup time          | $T_{vst}$ | 8    | -    | -    | ns    |        |
|            | VSD hold time           | $T_{vhd}$ | 8    | -    | -    | ns    |        |
|            | Vertical display area   | $t_{vd}$  | -    | 480  | -    | th    |        |
|            | VSD period time         | $t_v$     | -    | 525  | -    | th    |        |
|            | VSD pulse width         | $t_{vpw}$ | -    | 3    | -    | th    |        |
|            | VSD back porch          | $t_{vb}$  | -    | 29   | -    | th    |        |
|            | VSD front porch         | $t_{vfp}$ | -    | 13   | -    | th    |        |
| DE         | DE setup time           | $T_{esu}$ | 8    | -    | -    | ns    |        |
|            | DE hold time            | $T_{ehd}$ | 8    | -    | -    | ns    |        |
| DATA       | Data setup time         | $T_{dsu}$ | 8    | -    | -    | ns    |        |
|            | Data hold time          | $T_{dhd}$ | 8    | -    | -    | ns    |        |




3.2.2 Timing Characteristic

3.2.2.1 DE and RGB Input Timing



Horizontal display timing range



**3.3 Back-Light Unit**

The Back-light system is an edge-lighting type with 14 white LED (Light Emitting Diode)s. The characteristics of 14 white LEDs are shown in the following tables.

(Ta= Room Temp)

| Characteristics   | Symbol          | Min.    | Typ.   | Max.   | Unit | Note |
|-------------------|-----------------|---------|--------|--------|------|------|
| Forward Voltage   | V <sub>f</sub>  | (21)    | (23.1) | (23.8) | V    |      |
| Forward Current   | I <sub>f</sub>  | -       | 40     | (50)   | mA   | (1)  |
| Power Consumption | P <sub>BL</sub> | -       | 924    | (1190) | mW   | (2)  |
| LED Life time     | -               | (20000) | -      | -      | hr   | (3)  |

Note (1) LEDs in 7 series x 2 parallel type.

(2) Where I<sub>f</sub> = 40mA, V<sub>f</sub> = 23.1, P<sub>BL</sub> = V<sub>f</sub> × I<sub>f</sub>

(3) The environmental conducted under ambient air flow ,at Ta=25±2°C, 60%RH±5%

4. Optical Characteristics

4.1 Optical characteristic of the LCD

The following items are measured under stable conditions. The optical characteristics should be measured in a dark room or equivalent state with the methods.

Measuring equipment: BM-7A


| Item                          | Symbol         | Condition                  | Min                          | Type    | Max     | Unit              | Note   |       |
|-------------------------------|----------------|----------------------------|------------------------------|---------|---------|-------------------|--------|-------|
| Brightness                    | B              |                            | (200)                        | (250)   | --      | cd/m <sup>2</sup> |        |       |
| Response time                 | T <sub>r</sub> | θ=0°                       | -                            | 3       | 6       | ms                | .      |       |
|                               | T <sub>f</sub> |                            | --                           | 7       | 14      | ms                |        |       |
| Contrast ratio                | CR             | At optimized viewing angle | (480)                        | (600)   | --      | --                |        |       |
| Luminance Uniformity          | ΔL             |                            | 70                           | 80      |         | %                 |        |       |
| Color Chromaticity (CIE 1931) | White          | W <sub>x</sub>             | θ=0°<br>Normal Viewing Angle | (0.277) | (0.307) | (0.337)           | --     | BM-7A |
|                               |                | W <sub>y</sub>             |                              | (0.318) | (0.348) | (0.378)           |        |       |
| Viewing Angle (6H)            | Hor.           | θ <sub>R</sub>             | CR≥10                        | 65      | 75      | --                | Degree |       |
|                               |                | θ <sub>L</sub>             |                              | 65      | 75      | --                |        |       |
|                               | Ver.           | θ <sub>U</sub>             |                              | 50      | 60      | --                |        |       |
|                               |                | θ <sub>D</sub>             |                              | 60      | 70      | --                |        |       |

a. Test equipment setup

After stabilizing and leaving the panel alone shall be warmed up for the stable operation of LCM, the measurement should be executed. Measurement should be executed in a stable, windless, and dark room. Optical specifications are measured by Topcon BM-7(fast) with a viewing angle of 2° at a distance of 50cm and normal direction.

b. Definition of response time: Tr and Tf

The response time is defined as the following figure and shall be measured by switching the input signal for "black" and "white".



c. Definition of contrast ratio:


Brightness measured when LCD is at "white state"

$$\text{Contrast Ratio (CR)} = \frac{\text{Brightness measured when LCD is at "white state"}}{\text{Brightness measured when LCD is at "black state"}}$$

Brightness measured when LCD is at "black state"

d. Measured at the center area of the panel when all the input terminals of LCD panel are electrically opened.

e. View Angle



f. Definition of Luminance of White: Luminance of white at the center points

|                                 |          |
|---------------------------------|----------|
| Light Source of Back-Light Unit | LED Type |
|---------------------------------|----------|


g. Definition of White Uniformity

$$\text{White Uniformity} = \frac{\text{Min. luminance of white among 9-points}}{\text{Max. luminance of white among 9-points}} \times 100\%$$

h. The definition of Color Gamut -Color Chromaticity CIE 1931

Color coordinate of white & red, green, blue at center point.

Color Gamut : NTSC(%) = ( RGB Triangle Area / NTSC Triangle Area ) x 100



## 5. I/O Terminal


## 5.1 Pin Assignment

| Pin No. | Symbol | I/O | Function                        | Remark |
|---------|--------|-----|---------------------------------|--------|
| 1       | VLED-  | P   | Power for LED backlight cathode |        |
| 2       | VLED+  | P   | Power for LED backlight anode   |        |
| 3       | GND    | P   | Power Ground                    |        |
| 4       | VDD    | P   | Power Supply                    |        |
| 5       | R0     | I   | Red data signal (LSB)           |        |
| 6       | R1     | I   | Red data signal                 |        |
| 7       | R2     | I   | Red data signal                 |        |
| 8       | R3     | I   | Red data signal                 |        |
| 9       | R4     | I   | Red data signal                 |        |
| 10      | R5     | I   | Red data signal                 |        |
| 11      | R6     | I   | Red data signal                 |        |
| 12      | R7     | I   | Red data signal (MSB)           |        |
| 13      | G0     | I   | Green data signal (LSB)         |        |
| 14      | G1     | I   | Green data signal               |        |
| 15      | G2     | I   | Green data signal               |        |
| 16      | G3     | I   | Green data signal               |        |
| 17      | G4     | I   | Green data signal               |        |
| 18      | G5     | I   | Green data signal               |        |
| 19      | G6     | I   | Green data signal               |        |
| 20      | G7     | I   | Green data signal (MSB)         |        |
| 21      | B0     | I   | Blue data signal (LSB)          |        |
| 22      | B1     | I   | Blue data signal                |        |
| 23      | B2     | I   | Blue data signal                |        |
| 24      | B3     | I   | Blue data signal                |        |
| 25      | B4     | I   | Blue data signal                |        |
| 26      | B5     | I   | Blue data signal                |        |
| 27      | B6     | I   | Blue data signal                |        |
| 28      | B7     | I   | Blue data signal (MSB)          |        |
| 29      | DGND   | P   | Digital ground                  |        |
| 30      | DCLK   | I   | Pixel clock                     |        |
| 31      | DISP   | I   | Display on/ off                 |        |
| 32      | HSYNC  | I   | Horizontal sync signal          |        |
| 33      | VSYNC  | I   | Vertical sync signal            |        |
| 34      | DE     | I   | Data Enable signal              |        |
| 35      | NC     | I   | No Connect                      |        |
| 36      | GND    | P   | Power Ground                    |        |
| 37      | NC     | -   | No Connect                      |        |
| 38      | NC     | -   | No Connect                      |        |
| 39      | NC     | -   | No Connect                      |        |
| 40      | NC     | -   | No Connect                      |        |

I: Input, O: Output, P: Power

Notes: NC Pin must be retained; this pin can't contact GND or other signal. GND Pin must ground contact, can not be floating. Connector Part No: FH12A-40S-0.5SH(55) or equivalent.

5.2 Block Diagram



6. Displayed Color and Input Data

|             | Color & Gray Scale | Data Signal |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |
|-------------|--------------------|-------------|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
|             |                    | R7          | R6 | R5 | R4 | R3 | R2 | R1 | R0 | G7 | G6 | G5 | G4 | G3 | G2 | G1 | G0 | B7 | B6 | B5 | B4 | B3 | B2 | B1 | B0 |
| Basic Color | Black              | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |    |
|             | Red                | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |    |
|             | Green              | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |    |
|             | Blue               | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  | 1  |    |
|             | Cyan               | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  |    |
|             | Magenta            | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  | 1  |    |
|             | Yellow             | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |    |
|             | White              | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  |    |
| Red         | Black              | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |    |    |
|             | Red(1)             | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |    |    |
|             | Red(2)             | 0           | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |    |    |
|             | :                  | :           | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  |    |    |
|             | Red(127)           | 0           | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |    |    |
|             | :                  | :           | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  |    |    |
|             | Red(254)           | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |    |    |
|             | Red(255)           | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |    |    |
| Green       | Black              | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |    |    |
|             | Green(1)           | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0  | 0  | 0  | 0  | 0  |    |    |
|             | Green(2)           | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |    |    |
|             | :                  | :           | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  |    |    |
|             | Green(127)         | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  |    |    |
|             | :                  | :           | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  |    |    |
|             | Green(254)         | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |    |    |
|             | Green(255)         | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  |    |    |
| Blue        | Black              | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |    |    |
|             | Blue(1)            | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  |    |    |
|             | Blue(2)            | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  |    |    |
|             | :                  | :           | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  |    |    |
|             | Blue(127)          | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  |    |    |
|             | :                  | :           | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  | :  |    |    |
|             | Blue(254)          | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  | 0  |    |    |
|             | Blue(255)          | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  | 1  |    |    |

0 : Low level voltage, 1 :High level voltage

Each basic color can be displayed in 256 gray scales from 8 bit data signals. With the combination of total 24 bit data signals, the 16.7M color display can be achieved on the screen.

7. Reliability Condition


No change on display and in operation under the following test condition.

Condition: Unless otherwise specified, tests will be conducted under the following condition.

Temperature: 20±5°C.

Humidity: 65±5%RH.

Tests will be not conducted under functioning state.

| No. | Parameter   | Condition  | Notes |
|-----|---|--|-------|
| 1   | High Temperature Operating                        | 70°C±2°C, 240hrs (Operation state).  |       |
| 2   | Low Temperature Operating                         | -20°C±2°C, 240hrs (Operation state).   | 1     |
| 3   | High Temperature Storage                          | 80°C±2°C, 240hrs.  | 2     |
| 4   | Low Temperature Storage                           | -30°C±2°C, 240hrs.   | 1,2   |
| 5   | High Temperature and High Humidity Operation Test | 60°C±2°C, 90%, 240hrs.   | 1,2   |
| 6   | Vibration Test                                    | Total fixed amplitude: 1.5mm.<br>Vibration Frequency: 10~55Hz.<br>One cycle 60 seconds to 3 direction of X, Y, Z each 15 minutes.  | 3     |
| 7.  | Drop Test   | To be measured after dropping from 60cm high on the concrete surface in packing state.<br><br><i>Dropping method corner dropping:</i><br><i>A corner: Once edge dropping.</i><br><i>B, C, D edge: Once face dropping.</i><br><i>E, F, G face: Once.</i> |       |

- Notes:
1. No dew condensation to be observed.
  2. The function test shall be conducted after 4 hours storage at the normal temperature and humidity after removed from the test chamber.
  3. Vibration test will be conducted to the product itself without putting I in a container.





## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [TFT Displays & Accessories](#) category:*

*Click to view products by [Display Elektronik](#) manufacturer:*

Other Similar products are found below :

[OAI-80038AA-2013-A](#) [HDA430T-3G1H](#) [EA CARREDIPTFT02](#) [NL6448BC20-21D](#) [NB7W-KBA04](#) [NB-ATT01](#) [NB5Q-ATT01](#) [NB5Q-KBA04](#) [NB-CN001](#) [NL12880BC20-05](#) [NL8060BC26-35C](#) [NL8060BC26-35F](#) [TCG104SVLQAPNN-AN20](#) [OAI-80038AA-2008-A](#) [315-U004B15300](#) [UMSH-8596MD-34T \(REV D\)](#) [98-0003-3490-8](#) [1044278](#) [1029309](#) [1060549](#) [DE 127-TU-30/7,5](#) [DE 128-TU-20/7,5](#) [EP-LK007TFTPCAP](#) [FR7.0A00](#) [RC2002A-TIG-CSX](#) [NL6448BC2021C](#) [TX17D01VM2EAB](#) [TX14D23VM5BAA](#)  
[TCG121WXLRXVNNANX35](#) [EIC-LCD-1080P](#) [T272480C07VR01](#) [1060632](#) [TCG070WVLPAAANN-AN50](#) [TCG035QVLPDANN-GN50](#)  
[1060630](#) [RFE430V-AIW-DNG](#) [T-55619GD065J-LW-ABN](#) [NHD-1.8-128160EF-SSXN-FT](#) [TCG104SVLPEANN-AN30](#) [NL6448BC33-70](#)  
[NL192108BC18-06F](#) [NLB150XG02L-01](#) [NL6448BC20-30D](#) [NL10276BC16-06](#) [NL192108AC10-01D](#) [NL6448AC18-08F](#) [NL6448BC20-30F](#)  
[NL12880BC20-05BD](#) [NL12880BC20-05D](#) [NL8060BC26-35BA](#)