

## special devices



Inductive proximity switches are contact-free sensors. They detect all conductive metals, regardless of whether they move or not. The achievable sensing range of the devices depends on the object material and its dimensions. The vibration-resistant sensors can be approached laterally or frontally. Inductive proximity switches are used for presence detection (e.g. goods carriers), positioning (e.g. dampers), counting (e.g. nuts /bolts), speed detection (e.g. for cog wheels), on conveyor systems (e.g. hose feedings) or distance measurements (e.g. press-in checking) of metallic objects.



## **TECHNICAL DATA**

Construction type housing	Cuboid
Degree of protection (IP)	IP20
Depth	110mm
Height	75mm
Material housing	Plastic
Width	22.5mm
Galvanic separation between input and output	NO
Galvanic separation between supply voltage and all other current circuits	NO
Inherently safe according to EN 60947-5-6 NAMUR	NO
Line monitoring	NO
Power consumption	0.4W
Rated supply voltage at DC (min/max)	10V / 35V
Reverse polarity protection	NO
Short-circuit-proof	NO
Suited for safety functions	NO
Switching frequency	3Hz
Type of electric connection	Screw connection
Type of power supply	Active
With LED indication	NO
With communication interface RS-232	NO
Operation temperature (min/max)	-25°C / 70°C

IV991196	inf
special devices	dechouic
CONNECTION	
DIMENSIONAL DRAWING	
ADDITIONAL INFORMATION	

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Proximity Sensors category:

Click to view products by IPF ELECTRONIC manufacturer:

Other Similar products are found below:

01.001.5653.1 70.340.1028.0 70.360.2428.0 70.364.4828.0 70.810.1053.0 72.360.1628.0 73.363.6428.0 980659-1 QT-12

E2ECQC2D1M1GJT03M E2EX10D1NN E2E-X14MD1-G E2E-X2D1-G E2EX2ME2N E2E-X3D1-N 10M E2E-X4MD1-G

E2FMX1R5D12M E2K-F10MC1 5M EC3016PPASL-1 EI1204TBOSL-6 EI5515NPAP BSA-08-25-08 IC08ANC15PO-K 25.161.3253.0 25.332.0653.1 25.352.0653.0 25.352.0753.0 25.523.3253.0 922FS1.5C-A4P-Z774 SC606ABV0S30 SM552A100 SM952A126100LE SM956A132600 A1220EUA-T F3S-A162-U CL18 QT-08L 34.110.0010.0 TL-C2MF1-M3-E4 IA08BLF15NOM5 IA08BSF15NOM5 IA12ASF04DOM1 IS2 IS31SE5000-UTLS2-TR 34.110.0021.0 34.110.0022.0 CA150-120VACDC VM18VA3000Q XS508BSCBL2 XS512BLNAM12