

ÖLFLEX® SPIRAL 540 P

Robust, halogen-free PUR spiral cable with high restoring forces

ÖLFLEX® SPIRAL 540 P - PUR spiral cable, robust and with high restoring forces, halogen free and oil-resistant power and control cable for machine construction

Info

High restoring forces

Halogen-free

Voltage class from 1.5 mm² 450/750 V



Oil-resistant



Mechanical resistance



Halogen-free



Good chemical resistance



Suitable for outdoor use



Cold-resistant

Last Update (17.01.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® SPIRAL 540 P

Benefits

Extension lengths of up to 3.5 times the unextended spiral length, high recoiling forces

The signal colour of the outer sheath increases safety and visual perception

Increased durability under harsh conditions thanks to robust PUR outer sheath

Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media

Wide temperature range for applications in harsh climatic environments

Application range

Harsh conditions

Mechanical engineering

Construction industry

Medical equipment

In damp interiors or outdoors

Product features

Halogen-free

Good resistance of the outer sheath to cutting and abrasion

High resistance to oil, low temperatures, microbes and hydrolysis

Flexible down to -30°C

Product Make-up

Strands of tinned-copper wires

Core insulation: TPE

Outer sheath made of special polyurethane

Length of straight ends: 1st end = 200 mm, 2nd end = 600 mm

Versions without the mandatory LAPP designation, but with other solid lengths, end lengths and end forms available on request

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000247 ETIM 5.0 Class-Description: Spiralized cable
Core identification code:	Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9 From 6 cores: black with white numbers
Conductor stranding:	Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5
Nominal voltage:	0.75 - 1 mm ² : U0/U: 300/500 Vac As from 1.5 mm ² : U0/U = 450/750 Vac
Test voltage:	3000 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Temperature range:	Flexible use: -30°C to +50°C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Photographs are not to scale and do not represent detailed images of the respective products.

* Prices are net prices without VAT and surcharges. Sale to business customers.

Versions without the mandatory LAPP designation, but with other solid lengths, end lengths and end forms available on request

Article number	Number of cores and mm ² per conductor	Spiral length, extended (mm)	Spiral length, unextended (mm)	Cable diameter (mm)
U ₀ /U: 300/500 V				
73220107	2 X 0.75	1000	300	6.6
73220108	2 X 0.75	2000	600	6.6
73220109	2 X 0.75	3500	1000	6.6
73220110	2 X 0.75	5000	1500	6.6
73220111	3 G 0.75	1000	300	7
73220112	3 G 0.75	2000	600	7
73220113	3 G 0.75	3500	1000	7
73220114	3 G 0.75	5000	1500	7
71220115	4 G 0.75	1000	300	7.6
71220116	4 G 0.75	2000	600	7.6
71220117	4 G 0.75	3500	1000	7.6
71220118	4 G 0.75	5000	1500	7.6
71220119	5 G 0.75	1000	300	8.5
71220120	5 G 0.75	2000	600	8.5
71220121	5 G 0.75	3500	1000	8.5
71220122	5 G 0.75	5000	1500	8.5
73220123	2 X 1	1000	300	7
73220124	2 X 1	2000	600	7
73220125	2 X 1	3500	1000	7
73220126	2 X 1	5000	1500	7
73220127	3 G 1	1000	300	7.4
73220128	3 G 1	2000	600	7.4
73220129	3 G 1	3500	1000	7.4
73220130	3 G 1	5000	1500	7.4
71220131	4 G 1	1000	300	8.2
71220132	4 G 1	2000	600	8.2
71220133	4 G 1	3500	1000	8.2
71220134	4 G 1	5000	1500	8.2
71220135	5 G 1	1000	300	9
71220136	5 G 1	2000	600	9
71220137	5 G 1	3500	1000	9
71220138	5 G 1	5000	1500	9
73220139	7 G 1	1000	350	10.9

Last Update (17.01.2017)
 ©2017 Lapp Group - Technical changes reserved
 Product Management www.lappkabel.de
 You can find the current technical data in the corresponding data sheet.
 PN 0456 / 02_03_16

Article number	Number of cores and mm ² per conductor	Spiral length, extended (mm)	Spiral length, unextended (mm)	Cable diameter (mm)
73220140	7 G 1	2000	700	10.9
73220141	7 G 1	3500	1200	10.9
73220142	7 G 1	5000	1700	10.9
U ₀ /U: 450/750 V				
73220143	2 X 1.5	1000	300	8.4
73220144	2 X 1.5	2000	600	8.4
73220145	2 X 1.5	3500	1000	8.4
73220146	2 X 1.5	5000	1500	8.4
73220147	3 G 1.5	1000	300	8.9
73220148	3 G 1.5	2000	600	8.9
73220149	3 G 1.5	3500	1000	8.9
73220150	3 G 1.5	5000	1500	8.9
71220151	5 G 1.5	1000	350	10.9
71220152	5 G 1.5	2000	700	10.9
71220153	5 G 1.5	3500	1200	10.9
71220154	5 G 1.5	5000	1700	10.9
73220155	7 G 1.5	1000	350	13.5
73220156	7 G 1.5	2000	700	13.5
73220157	7 G 1.5	3500	1200	13.5
73220158	7 G 1.5	5000	1700	13.5
73220159	3 G 2.5	1000	350	10.6
73220160	3 G 2.5	2000	700	10.6
73220161	3 G 2.5	3500	1200	10.6
73220162	3 G 2.5	5000	1700	10.6
71220163	5 G 2.5	1000	350	13.4
71220164	5 G 2.5	2000	700	13.4
71220165	5 G 2.5	3500	1200	13.4
71220166	5 G 2.5	5000	1700	13.4

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Specialised Cables category](#):

Click to view products by [Lapp Kabel manufacturer](#):

Other Similar products are found below :

[GP-IE515546DS-002](#) [96CB-L2020PIB2](#) [1200740161](#) [R7ACAB003S](#) [R88ACAKA0015SRE](#) [R88ACAWL005SDE](#) [R88ACRGB010C](#)
[R88ACRGD0R3C](#) [R88ACRGD0R3CBS](#) [R88ACRKA020CRE](#) [1300660201](#) [1971465-2](#) [22733-8](#) [2R7004A20F060](#) [SSL009PC2DC012N](#)
[FC2A-KC6C](#) [FZVS415M](#) [CCSFCBF2](#) [R7ACAB005S](#) [R88ACAGD003SRE](#) [R88ACAGE005BRE](#) [R88ACAKE003SRE](#) [R88ACAKE005SRE](#)
[R88ACAKE010SRE](#) [R88ACRKM010SRE](#) [R88AFIK222RE](#) [XS2WM12PUR4SA10M](#) [XS2WM12PVC4SA10M](#) [05AU05](#) [UCABLE](#)
[10114734-2010LF](#) [R88ACRKC015NRE](#) [XW2Z010H3](#) [XW2Z010H1](#) [5-1589827-8](#) [861084-1](#) [XW2Z200JB24](#) [CR4000A76M020](#)
[1300140039](#) [CR4000A76M005](#) [CR4006A76M005](#) [10077488-N0550FDLF](#) [XW2ZRY150C](#) [I4JPBJLUXX100](#) [I4JPBJLUXX50](#) [CM06W](#)
[CM08](#) [POE004](#) [0243 009 05](#) [0243 009 20](#)