


Small Signal Fast Switching Diodes


Features

- V_R 75V
- I_{FAV} 150mA

■ Limiting Values (Absolute Maximum Rating)

Item	Symbol	Unit	Conditions	Max
Repetitive peak reverse voltage	V_{RRM}	V		100
Reverse voltage	V_R	V		75
Peak forward surge current	I_{FSM}	A	$t_p=1\mu s$	2
Repetitive peak forward current	I_{FRM}	mA		500
Forward continuous current	I_F	mA		300
Average forward current	I_{FAV}	mA	$V_R=0$	150
Power dissipation	P_{tot}	mW		500 ¹⁾
Thermal resistance	R_{thJA}	°C/W	junction to ambient air	300 ¹⁾
Maximum junction temperature	T_j	°C		175
Storage temperature range	T_{stg}	°C		-65 to +175

Notes:

¹⁾ Valid provided that electrodes are kept at ambient temperature



■Electrical Characteristics (T_a=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Max
Forward voltage	V _F	mV	I _F =50mA	1000
Reverse current	I _R	nA	V _R =20V	25
	I _R	μA	V _R =20V, T _j =150 °C	50
	I _R	μA	V _R =75V	5
Breakdown voltage	V _(BR)	V	I _R =100μA, t _p /T=0.01, t _p =0.3ms	100(min)
Diode capacitance	C _D	pF	V _R =0, f =1MHz, V _{HF} =50mV	4
Reverse recovery time	t _{rr}	ns	I _F = I _R =10mA, i _R =1mA	8
	t _{rr}	ns	I _F = 10mA, V _R =6V, i _R =0.1×I _R , R _L =100Ω	4

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
LL4148	F1	Approximate 0.47	2500	150000	7" reel

■Characteristics(Typical)

FIG1: Forward Current vs. Forward Voltage




FIG2: Reverse Current vs. Reverse Voltage







FIG3:Diode Capacitance vs. Reverse Voltage



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Diodes - General Purpose, Power, Switching category](#):

Click to view products by [Yangjie manufacturer](#):

Other Similar products are found below :

[MCL4151-TR3](#) [MMBD3004S-13-F](#) [RD0306T-H](#) [RD0506LS-SB-1H](#) [RGP30G-E373](#) [DSE010-TR-E](#) [BAQ333-TR](#) [BAQ335-TR](#) [BAQ33-GS18](#) [BAS1602VH6327XT](#) [BAV17-TR](#) [BAV19-TR](#) [BAV301-TR](#) [BAW27-TAP](#) [HSC285TRF-E](#) [NSVBAV23CLT1G](#) [NTE525](#) [1SS181-TP](#) [1SS184-TP](#) [1SS193,LF](#) [1SS193-TP](#) [1SS400CST2RA](#) [SBAV99LT3G](#) [SDAA13](#) [LL4448-GS18](#) [SHN2D02FUTW1T1G](#) [LS4150GS18](#) [LS4151GS08](#) [SMMD7000LT3G](#) [FC903-TR-E](#) [1N4449](#) [1N4934-E3/73](#) [1SS226-TP](#) [APT100DL60HJ](#) [RFUH20TB3S](#) [RGP30G-E354](#) [RGP30M-E3/73](#) [D291S45T](#) [MCL4151-TR](#) [BAS 16-02V H6327](#) [BAS 21U E6327](#) [BAS 28 E6327](#) [BAS33-TAP](#) [BAS 70-02V H6327](#) [BAV300-TR](#) [BAV303-TR3](#) [BAW27-TR](#) [BAW56DWQ-7-F](#) [BAW56M3T5G](#) [BAW75-TAP](#)