

Vermason		Product Information No: PIS 058		
	Page 1 of 1	Issue No 4	Date: 19 Feb 2002	Approved by

FX AND HD VERMAFOAM CONDUCTIVE POLYURETHANE FOAM

Codes L21.. and L25.. - FEC Part No 1758847/175848/175849

Vermafoam FX and HD are carbon impregnated polyether polyurethane foams. They are available in a variety of thicknesses from 6mm to 40mm in sheets up to 1m x 1m. Both products can also be supplied cut to customer requirements.

175849 L21.. FX type is soft and flexible. It is used as cushion packaging.

175847 L25.. HD type has outstanding "pin insertion" properties. It is used to hold
175848 devices in place.

TECHNICAL DATA

Typical values of 6mm thick samples

TYPE	COLOUR	SURFACE RESISTIVITY Ω/square	VOLUME RESISTIVITY Ωm	pH of WATER EXTRACT	DENSITY Kg/m^3
FX	BLACK	5×10^3 to 5×10^4	30 - 40	7.8	30 - 40
HD	BLACK	10^4 to 10^5	50 - 60	7.6	45 - 55

For further information, please contact
Vermason Ltd, 1 Avenue One, Letchworth, Hertfordshire SG6 2HB
 Tel: +44(0)1462 672005 Fax: +44(0)1462 670440
 e-mail : sales@vermason.co.uk
www.vermason.co.uk

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Vermason](#) manufacturer:

Other Similar products are found below :

[072425B](#) [229765](#) [200535](#) [222547](#) [222562](#) [50424](#) [229625](#) [242296](#) [210320](#) [210300](#) [35268](#) [220522](#) [242140](#) [47200](#) [231250](#) [203065](#) [237670](#)
[231288](#) [242210](#) [242278](#) [242291](#) [239260](#) [222635](#) [237195](#) [203005](#) [241090](#) [229100](#) [242276](#) [230310](#) [J6609](#) [242271](#) [47201](#) [242274](#) [230480](#)
[238711](#) [200520](#) [35594](#) [35595](#) [230660](#) [230500](#) [237675](#) [211045](#) [231275](#) [229775](#) [237200](#) [229755](#) [203015](#) [229630](#) [230260](#) [200515](#)