



Technical Data Sheet
Edition 1
Date: 14/05/2004

Letratag Plastic tape

Letratag tape is a direct thermal tape available in six colors. Each cassette contains one tape of 12 mm width and 4 m length.

Property	Unit	Value	Test method
1. General			
- Thickness tape	Micron	145 ± 10 %	Micrometer
- Thickness liner	Micron	55 ± 10 %	
2. Adhesive properties		Dwell	
		20 min 24 hrs	
- to stainless steel	N/25mm	10 11	PSTC-1
- to glass		9 11	
- to PVC		11 14	
- to textured ABS		8 9	
- to powder coated steel		7 8	
- to wood		3 4	
- to polypropylene film glossy		8 11	
- to polyethylene		3 4	
- to tupperware		9 9	
- to steel computer casing		1 1	
3. Abrasion resistance of text printed in Letratag			Crockmeter, 900g weight/arm
- Pencil erasure	30x	No visible effect	
- Polystyrene pin	30x	No visible effect	
- Sandpaper	30x	No visible effect	
Chemical resistance of text printed in Letratag			
- Eurosuper	30x	No visible effect	
- Diesel	30x	No visible effect	
- Isopropylalcohol	30x	Printing gone	
- Ethanol	10x	Printing gone	

Dwell means the contact time between label and substrate

<ul style="list-style-type: none"> - Ethyl acetate - Skydrol (hydraulic engine oil) - Sabesto (brake fluid cleaner) - Exxsol 40 (cleaning solvent) - ULS (cleaning solvent) - Ether - Acetone - Toluene - Dreft - Water - Vim - General degreaser - Synthetic thinner - White spirit - Oil spots remover - Cellulose thinner - Calgonit - Sun brilliance - Instanet - Antikal - Nafta - Workspace degreaser 	<ul style="list-style-type: none"> 3x 30x 5x 30x 5x 15x 10 x 10 x 30 x 30 x 30 x 30x 30x 30 x 30 x 30 x 30x 30 x 30 x 30 x 30 x 5x 	<ul style="list-style-type: none"> Printing gone Printing gone Printing gone No visible effect Printing gone Printing gone Printing gone Printing gone No visible effect No visible effect No visible effect Severe print removal Printing gone No visible effect No visible effect Printing gone No visible effect No visible effect No visible effect No visible effect No visible effect No visible effect Printing gone 	
<p>4. Light stability of printed label</p> <ul style="list-style-type: none"> - 5 days in suntester with glass filter (corresponds with 2 months exposure behind window glass) - 5 days in suntester with UV- filter (corresponds with 2 months outdoor exposure) 		<p>No visible effect on text or background.</p> <p>Slight discoloration of background. No visible effect on text.</p>	
<p>5. Temperature stability</p> <ul style="list-style-type: none"> - Application temperature - Short term high service temperature - 10' at 60°C - 10' at 70°C - 10' at 80°C 	<p>°C</p>	<p>Room temperature</p> <p>No visible effect on text and background</p> <p>No visible effect on text and background</p> <p>No visible effect on text and background.</p>	

Dwell means the contact time between label and substrate

<p>-10' at 90°C</p> <p>- Long term low service Temperature</p> <p>- 30 days at -18°C</p>		<p>No visible effect on text and background.</p> <p>No visible effect on text and background.</p>	
<p>6. Humidity resistance of applied label</p> <p>- 30 days at 40°C, 95 % R.H. (on alu panel)</p>		<p>Slight discoloration of text. No visible effect on background.</p>	
<p>7. Shelf life of label roll</p>		<p>1 year at 5-25°C and 40-85% relative humidity when stored in its original packaging. We are confident that our product will perform well beyond this frame. However, it remains the responsibility of the user to assess the risk of using such product.</p>	

Scratch resistance : The printed labels are subjected to different scratching sources for a fixed number of cycles with a finger weight of 900g.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Dymo manufacturer](#):

Other Similar products are found below :

[1868771](#) [1868802](#) [1868713](#) [45016](#) [18758-R1](#) [45811](#) [S0895840](#) [S0946430](#) [45010](#) [S0721660](#) [1868740](#) [1868737](#) [1868756](#) [1868772](#) [1868707](#)
[1868714](#) [1868732](#) [1868736](#) [1868758](#) [1868773](#) [45012](#) [S0720610](#) [18762-R1](#) [M1011 KIT](#) [40917](#) [S0722440](#) [1805437](#) [1868775](#) [S0720870](#)
[1868752](#) [1868753](#) [11354](#) [18508-R1](#) [1868761](#) [18757-R1](#) [1868798](#) [99012](#) [45014](#) [S0955990 PROMO](#) [S0955960 PROMO](#) [1868774](#) [1868810](#)
[S0721530](#) [S0904980](#) [91332](#) [1868751](#) [1868755](#) [18487](#) [1868754](#) [43610](#)