MINIATURE LAMP (47) Details



47				
T3 1/4 M BAY 6.3V .15A .5CP				
T-3 1/4	Filament	C-2R	Base Style	Miniature Bayonet (BA9s)
0.39	\mathbf{MOL}^{\dagger} (in)	1.19	LCL ^{**} (in)	0.78
10	MOL (mm)	30.23	LCL (mm)	19.80
6.3	MSCP [‡]	0.52	Avg Life Hrs	3000
0.945	Amps	0.15	RoHS Compliant	
	0.39 10 6.3	0.39 MOL ⁺ (in) 10 MOL (mm) 6.3 MSCP *	T-3 1/4 Filament C-2R 0.39 MOL ⁺ (in) 1.19 10 MOL (mm) 30.23 6.3 MSCP ⁺ 0.52	T3 1/4 M BAY 6.3V .15A T-3 1/4 Filament C-2R Base Style 0.39 MOL ⁺ (in) 1.19 LCL ⁺⁺ (in) 10 MOL (mm) 30.23 LCL (mm) 6.3 MSCP ⁺ 0.52 Avg Life Hrs

+ MOL (Maximum Overall Length):

The overall length of a lamp, from the top of the shell to the bottom of the base.

‡ MSCP (Mean Spherical Candlepower):

Candlepower produced at design volts. Candlepower is increased rapidly with an increase of applied voltage and conversely is reduced rapidly with a reduction of applied voltage.

++ LCL (Light Center Length):

The distance from a reference point, usually the bottom of the lamp base, to the center of the light source.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for CEC manufacturer:

Other Similar products are found below :

<u>303</u> 243 50 81 28PSB L20120CS-W 120MB E85 85 47 657 120PSB 130MB 1815 46 1141 927 908 93 1866 44 1829 1820 H3-55W 1847 939 3175 51 1818 161 388 680 1156 1813 7371 H3-70W/24V 655 756 464 112 1835 1819 40 7219 757 222 N-F-24.000M-10-1015-3085-40 K-F-12.000M-16-2030-2070-100 755 K-F-16.000M-9-2020-2070-60