#### **MINIATURE LAMP (50) Details**



Part #	50				
Description	G3 1/2 M SCREW 7.5V.22A.1CP				
Bulb Shape	G-3 1/2	Filament	C-2R	Base Style	Miniature Screw (E10)
Glass Diameter (in)	0.46	MOL <sup>†</sup> (in)	0.94	LCL <sup>††</sup> (in)	0.72
Glass Diameter (mm)	11.7	MOL (mm)	23.88	LCL (mm)	18.29
Volts	7.5	MSCP <sup>‡</sup>	1	Avg Life Hrs	1000
Watts	1.65	Amps	0.22	RoHS Compliant	

## † MOL (Maximum Overall Length):

The overall length of a lamp, from the top of the shell to the bottom of the base.

## **‡ MSCP (Mean Spherical Candlepower):**

Candlepower produced at design volts. Candlepower is increased rapidly with an increase of applied voltage and conversely is reduced rapidly with a reduction of applied voltage.

#### **†† LCL (Light Center Length):**

The distance from a reference point, usually the bottom of the lamp base, to the center of the light source.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for CEC manufacturer:

Other Similar products are found below:

303 243 50 81 28PSB L20120CS-W 120MB E85 85 47 657 120PSB 130MB 1815 46 1141 927 908 93 1866 44 1829 1820 H3-55W 1847 939 3175 51 1818 161 388 680 1156 1813 7371 H3-70W/24V 655 756 464 112 1835 1819 40 7219 757 222 N-F-24.000M-10-1015-3085-40 K-F-12.000M-16-2030-2070-100 755 K-F-16.000M-9-2020-2070-60