



"EPA ground cords shall be used to make electrical connections between groundable points and the EPA ground facility.

Where a single resistor is used in the EPA ground cord, this shall be located near the groundable point. Where more than one resistor is used, a resistor of a minimum resistance value of one half the total resistance shall be located near the groundable point.

When accessible, the EPA ground cord and its groundable point connection shall be shrouded by insulating material." (EN 61340-5-1 section 5.3.4 ground cords)

Per Note 6 of Table 1 of EN 61340-5-1 for Working surfaces, storage racks, trolleys and carts "It is allowed, when approved by the ESD co-ordinator, to use surfaces which are 'hard ground' i.e. less than 1 X 10<sup>4</sup> ohms to EPA ground."

- 2.5mm polyurethane insulation
- Conductor is high strength 7-end duplex tinsel for strength and flexibility
- 1 megohm resistor built in each socket
- Colours: black and yellow
- Dielectric Strength: Cords withstand 1250 volts DC for at least one minute
- Standard cords are marked and date coded

Item #	Description
VER-26964	CORD,COILED,2M,10MMSOCKET/10MM SOCKET, BLACK
VER-26965	CORD,COILED,2M,10MMSOCKET/10MM SOCKET,YELLOW



Specifications and procedures subject to change without notice.



## Coiled Cords, 2M, 10mm Socket, 10mm Socket

VERMASON

UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH, HERTS, SG6 2TD UK

PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440 E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk Drawing Number VER-26964

DATE: September 2015

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Vermason manufacturer:

Other Similar products are found below:

 072425B
 229765
 200535
 222547
 222562
 50424
 229625
 242296
 210320
 210300
 35268
 220522
 242140
 47200
 231250
 203065
 237670

 231288
 242210
 242278
 242291
 239260
 222635
 237195
 203005
 241090
 229100
 242276
 230310
 J6609
 242271
 47201
 242274
 230480

 238711
 200520
 35594
 35595
 230660
 230500
 237675
 211045
 231275
 229775
 237200
 229755
 203015
 229630
 230260
 200515