



- Ground cord used to connect mats to (Earth Bonding Point) plugs
- 1 megohm (1x10<sup>6</sup> ohms) resistor in socket end ٠
- 2.5mm cord diameter ٠
- PVC insulation with 7 ends duplex tinsel copper conductor ٠
- Both cord ends terminated with 10mm snap socket ٠

Item #	Description
VER-26974	CORD,STRAIGHT,0.7M,10MMSOCKET/ 10MM SOCKET
VER-26970	CORD,STRAIGHT,1.5M,10MMSOCKET/ 10MM SOCKET

"EPA ground cords shall be used to make electrical connections between groundable points and the EPA ground facility.

Where a single resistor is used in the EPA ground cord, this shall be located near the groundable point. Where more than one resistor is used, a resistor of a minimum resistance value of one half the total resistance shall be located near the groundable point.

When accessible, the EPA ground cord and its groundable point connection shall be shrouded by insulating material." (EN 61340-5-1 section 5.3.4 EPA ground cords)

Unless otherwise noted, tolerance is ±10%



Specifications and procedures subject to change without notice.

## Straight Cord, 10mm Socket, 10mm Socket

VERMASON UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH, HERTS, SG6 2TD UK PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440 E-MAIL:Service@Vermason.co.uk, INTERNET: Vermason.co.uk

**Drawing Number** VER-26974

DATE: September 2015

Made in the

United Kingdom

© 2015 VERMASON.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Vermason manufacturer:

Other Similar products are found below :

<u>072425B</u> <u>229765</u> <u>200535</u> <u>222547</u> <u>222562</u> <u>50424</u> <u>229625</u> <u>242296</u> <u>210320</u> <u>210300</u> <u>35268</u> <u>220522</u> <u>242140</u> <u>47200</u> <u>231250</u> <u>203065</u> <u>237670</u> <u>231288</u> <u>242210</u> <u>242278</u> <u>242291</u> <u>239260</u> <u>222635</u> <u>237195</u> <u>203005</u> <u>241090</u> <u>229100</u> <u>242276</u> <u>230310</u> <u>J6609</u> <u>242271</u> <u>47201</u> <u>242274</u> <u>230480</u> 238711 200520 35594 35595 230660 230500 237675 211045 231275 229775 237200 229755 203015 229630 230260 200515