



# SFP Modules 100Base-FX LC



ETHERNET via fiber optic cables offers a multitude of advantages for industrial applications. High immunity to interference, electrical isolation, and long ranges are important parameters here.

Description		Item No.	Pack. Unit
<b>SFP Module 2: 1310nm, 100Base-FX Multi-mode LC, 2 km</b>	Connector Duplex LC, Wavelength 1310 nm, Fiber type Multi-mode 62.5/125 µm, 50/125 µm, Maximum length 2000 m, Operating temperature 0 °C ... +60 °C, Storage temperature -20 °C ... +80 °C, Dimensions (mm) W x H x D: 13.4 x 13.3 x 56.6; Laser Class 1 acc. to EN 60825-1	<b>852-201/107-002</b>	<b>1</b>
<b>SFP Module 30: 1310nm, 100Base-FX Single-mode LC, 30 km</b>	Connector Duplex LC, Wavelength 1310 nm, Fiber type Single-mode 9/125 µm, Maximum length 30000 m, Operating temperature 0 °C ... +60 °C, Storage temperature -20 °C ... +80 °C, Dimensions (mm) W x H x D: 13.4 x 13.3 x 56.6; Laser Class 1 acc. to EN 60825-1	<b>852-201/107-030</b>	<b>1</b>
<b>SFP Module 2 T: 1310nm, 100Base-FX, Multi-mode, LC, 2 km, (Extended temperature range: -40 °C ... +70 °C)</b>	Connector Duplex LC, Wavelength 1310 nm, Fiber type Multi-mode 62.5/125 µm, 50/125 µm, Maximum length 2000 m, Operating temperature -40 °C ... +70 °C, Storage temperature -40 °C ... +80 °C, Dimensions (mm) W x H x D: 13.4 x 13.3 x 56.6; Laser Class 1 acc. to EN 60825-1	<b>852-201/040-002</b>	<b>1</b>

### Characteristics:

- Duplex LC optical connector
- Industry standard small form pluggable (SFP) package
- Compliant with Fast ETHERNET standard;
- Differential LVPECL inputs and outputs;
- Single 3.3V power supply;
- TTL signal detect indicator;
- Hot pluggable capability

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wago manufacturer](#):*

Other Similar products are found below :

[750-460](#) [231-118/026-000](#) [231-303/026-000](#) [231-620/019-000](#) [257-403](#) [280-438](#) [280-831](#) [284-624](#) [284-681](#) [206-861](#) [210-111](#) [231-303/037-000](#) [231-446/001-000\\_NR](#) [231-833/001-000](#) [232-216/026-000](#) [234-510](#) [264-726](#) [280-339](#) [793-500 2](#) [51228988](#) [209-132](#) [830-800/000-305](#) [788-507](#) [750-512](#) [264-321](#) [279-101](#) [281-365](#) [713-1428/107-000](#) [731-138/048-000](#) [750-459](#) [750-517](#) [750-601](#) [793-3505](#) [231-535/001-000](#) [2624-1103](#) [787-712](#) [713-1407](#) [2000-5457](#) [221-525](#) [832-1206](#) [832-3604](#) [281-512/281-501](#) [286-336](#) [288-437](#) [750-421](#) [750-838](#) [753-559](#) [750-1505](#) [787-732](#) [753-437](#)