

# TECHNICAL DATA

Version 16

## AT8 PVC Floor Marking Tape

### General Description

A heavy duty plasticised PVC film coated with a white, High adhesion, high tack and aggressive pressure sensitive adhesive.

- Excellent conformability, particularly to uneven surfaces
- Specially formulated PVC prevents lifting
- Water resistant
- Good abrasion resistance
- UV resistant
- Very aggressive, non-corrosive adhesive
- Can be walked on immediately after application
- Suitable for indoor and outdoor use
- Can be applied by hand or machine
- Colours and widths in accordance with the Sports England Guidance Notes



### Technical Details

#### Typical Values

Tape Thickness	0.14mm
Breaking Load	26 N/cm
Elongation at Break	150%
Adhesion	
Steel	3.5 N/cm
Self	2.5 N/cm
Water Extract	
pH	6.0 to 8.0
Conductivity	Max 2.5 mS/m
RoHS Compliant	Yes
Service Temperature	0°C to +60°C
Application Temperature	+5°C to +40°C
Storage Temperature	+12°C to +25°C

#### NOTE

Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

#### STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.



#### AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.

#### Adding more to adhesive tape

Registered in England No. 929843  
Vat No. 115-6143-00

Advance Tapes International Limited  
Westmoreland Avenue  
Thurmaston  
Leicester LE4 8PH  
England

Tel. +44 (0)116 251 0191  
Fax. +44 (0)116 265 2046  
contact@advancetapes.com

www.advancetapes.com



Q05026

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Advance Tapes manufacturer](#):*

Other Similar products are found below :

[AT7 BLACK 33M X 25MM](#) [AT163 SILVER 50M X 50MM](#) [AT8 BLACK 33M X 50MM](#) [AT541 33M X 12MM](#) [AT2000 BLACK 18M X 50MM](#) [AT2000 BLACK/YELLOW 18M X 50MM](#) [AT525 COPPER 33M X 10MM](#) [AT7 BROWN 33M X 25MM](#) [AT10 BLACK 33M X 50MM](#) [AT200 WHITE 50M X 50MM](#) [AT8 BLUE 33M X 50MM](#) [AT8 GREEN 33M X 50MM](#) [AT159 BLUE 50M X 25MM](#) [AT202 WHITE 50M X 50MM](#) [AT2000 YELLOW 18M X 50MM](#) [AT2000 BLACK 18M X 100MM](#) [AT525 COPPER 33M X 50MM](#) [AT159 GREEN 50M X 50MM](#) [AT4002 WHITE 55M X 25MM](#) [AT9 SILVER 33M X 50MM](#) [AT160 BLUE 50M X 50MM](#) [AT3400 BLACK 20M X 19MM](#) [AT4001 WHITE 55M X 25MM](#) [AT30 BLACK 33M X 50MM](#) [AT132 WHITE 50M X 50MM](#) [AT4004 YELLOW 66M X 25MM](#) [AT159 BLACK 50M X 50MM](#) [AT160 WHITE 50M X 50MM](#) [AT8 RED 33M X 50MM](#) [AT85 BLACK 10M X 50MM](#) [AT42 ORANGE 33M X 50MM](#) [AT7 ASSORTED COLOURS 33M X 19M](#) [AT160 YELLOW 50M X 50MM](#) [AT8H RED / WHITE 33M X 50MM](#) [AT544 33M X 19MM](#) [AT544 33M X 25MM](#) [AT526 COPPER 33M X 19MM](#) [AT308 CREAM 25M X 50MM](#) [AT7 VIOLET 33M X 25MM](#) [AT202 BLACK 50M X 50MM](#) [AT30 CLEAR 33M X 50MM](#) [AT44 BLACK 33M X 100MM](#) [AT85 BLACK 10M X 19MM](#) [AT159 WHITE 50M X 25MM](#) [AT175 GREEN 50M X 50MM](#) [AT159 YELLOW 50M X 50MM](#) [AT79 BLACK 10M X 19MM](#) [AT7 GREEN 33M X 25MM](#) [AT7 RED 33M X 19MM](#) [AT27 TRANSPARENT 33M X 25MM](#)