

## This document was generated on 02/09/2017 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Status: Overview: Description:		<u>nd Receptacles</u> TPA Header, Dual Row, Vertical, with PCB Mounting Flange, 8 Nickel (Ni) Plating, without Drain Holes		
Documents: 3D Model Drawing (PDF) Product Specification PS	S-5556-003 (PDF)	Packaging Specification PK-30069-001-001 (PDF) RoHS Certificate of Compliance (PDF)		Para Bafamana antu
·	· · · ·		Series Ima	ge - Reference only
Agency Certification CSA		LR19980	EU ELV	
UL		E29179	Not Relevant	
UL		E29179		
General			EU RoHS	China RoHS
Product Family		PCB Headers	Compliant	
Series		30069	REACH SVHC	
Application		Power, Wire-to-Board	Not Contained Pe	
Comments		Current for wire-to-wire applications = 13.0A max. per	ED/21/2016 (20 Ju	une
Comments		circuit. Current for wire-to-board applications = 9.0A	2016)	
			Halogen-Free	
O		max. per circuit	Status	
Overview		Mini-Fit® TPA2 Plugs and Receptacles	Not Low-Haloger	
Product Name		Mini-Fit® TPA		nation on product
UPC		822350400848	environmental co	
Physical				- nlianaa @malay aam
Breakaway		No	Email <u>productcompliance@molex.com</u> Please visit the <u>Contact Us</u> section for ar	
Circuits (Loaded)		8		
Circuits (maximum)		8	non-product comp	liance questions.
Color - Resin		Black	China ROHS	Green Image
Durability (mating cycles max)		30	ELV	Not Relevant
First Mate / Last Break		No	RoHS Phthalates	
Flammability		94V-0	ROHS Phinalates	Not Contained
Glow-Wire Compliant		No		
Guide to Mating Part		No		
Keying to Mating Part		None	Search Parts in	this Series
Lock to Mating Part		Yes	30069 Series	
Material - Metal		Brass		
		Tin		
Material - Plating Mating Material - Plating Termination		Tin	Mates With	
Material - Plating Termination Material - Resin			<u>30007</u> WINI-FIT I	PA™ Receptacle Hou
Net Weight		Polyester		
Number of Rows		2.560/g		
		2 Vorticel		
Orientation		Vertical		
PCB Locator		Yes		
PCB Retention		Yes		
PCB Thickness - Recommended		1.80mm		
Packaging Type		Bag		
Pitch - Mating Interface		4.20mm		
Pitch - Termination Inter		4.20mm		
Polarized to Mating Par		Yes		
Polarized to PCB		Yes		
Shrouded		Partial		
Stackable		No		
Surface Mount Compati	ble (SMC)	No		
Temperature Range - Operating		-40°C to +105°C		

Termination Interface: Style	Through Hole				
<b>Electrical</b> Current - Maximum per Contact Voltage - Maximum	13.0A 600V				
Solder Process Data Duration at Max. Process Temperature (seconds) Lead-freeProcess Capability Max. Cycles at Max. Process Temperature Process Temperature max. C	005 WAVE 001 235				
Material Info					
<b>Reference - Drawing Numbers</b> Packaging Specification Product Specification Sales Drawing	PK-30069-001-001 PS-5556-003 SD-30069-001-000				

## This document was generated on 02/09/2017 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA 48050-002LF DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 891-007-9SS-BST1T 000-34000 0008550134 0009482033 0009507031 0009524054 57102-F02-18ULF 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 636-1427 638009-1 641938-9 641991-4 644168-1 644827-2 647662-1 65039-019ELF 65692-001LF 65781-018