



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE5437 & NTE5438 Silicon Controlled Rectifier (SCR) 8 Amp Sensitive Gate, TO220

Description:

The NTE5437 and NTE5438 are silicon controlled rectifiers (SCR) in a TO220 type package designed for general purpose high voltage applications where gate sensitivity is required.

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)


Repetitive Peak Off-State Voltage ($T_J = -40^\circ$ to $+125^\circ\text{C}$, $R_{GK} = 1\text{k}\Omega$), V_{DRM} , V_{RRM}		
NTE5437		400V
NTE5438		600V
On-State Current (All Conducting Angles, $T_C = +85^\circ\text{C}$), $I_{T(RMS)}$		8A
Average On-State Current (Half Cycle, $\ominus = 180^\circ$, $T_C = +85^\circ\text{C}$), $I_{T(AV)}$		5.1A
Non-Repetitive On-State Current, I_{TSM}		
Half Cycle, 60Hz		88A
Half Cycle, 50Hz		80A
Fusing Current ($t = 10\text{ms}$, Half Cycle), I^2t		32A ² s
Peak Reverse Gate Voltage ($I_{GR} = 50\mu\text{A}$), V_{GRM}		8V
Peak Gate Current (10 μs Max), I_{GM}		2A
Peak Gate Dissipation (10 μs Max), P_{GM}		5W
Gate Dissipation (20ms Max), $P_{G(AV)}$		0.5W
Operating Junction Temperature Range, T_J		-40° to $+125^\circ\text{C}$
Storage Temperature Range, T_{stg}		-40° to $+125^\circ\text{C}$
Lead Temperature (During Soldering, 1.6mm from case, 10sec Max), T_L		$+250^\circ\text{C}$
Thermal Resistance, Junction-to-Case, R_{thJC}		4K/W
Thermal Resistance, Junction-to-Ambient, R_{thJA}		60K/W

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Max	Unit	
Off-State Leakage Current	I_{DRM} , I_{RRM}	$V_{DRM} + V_{RRM} = \text{Rated Voltage}$, $R_{GK} = 1\text{k}\Omega$	$T_J = +125^\circ\text{C}$	-	0.5	mA
			$T_J = +25^\circ\text{C}$	-	5.0	μA

Electrical Characteristics (Cont'd): ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Max	Unit
On-State Voltage	V_T	$I_T = 16\text{A}, T_J = +25^\circ\text{C}$	-	1.95	V
On-State Threshold Voltage	$V_{T(TO)}$	$T_J = +125^\circ\text{C}$	-	1.05	V
On-State Slope Resistance	r_T	$T_J = +125^\circ\text{C}$	-	65	$\text{m}\Omega$
Gate Trigger Current	I_{GT}	$V_D = 7\text{V}$	-	200	μA
Gate Trigger Voltage	V_{GT}	$V_D = 7\text{V}$	-	2.0	V
Holding Current	I_H	$R_{GK} = 1\text{k}\Omega$	-	10	mA
Latching Current	I_L	$R_{GK} = 1\text{k}\Omega$	-	20	mA
Critical Rate of Voltage Rise	dv/dt	$V_D = .67 \times V_{DRM}, R_{GK} = 1\text{k}\Omega, T_J = +125^\circ\text{C}$	5	-	$\text{V}/\mu\text{s}$
Critical Rate of Current Rise	di/dt	$I_G = 10\text{mA}, di_G/dt = 0.1\text{A}/\mu\text{s}, T_J = +125^\circ\text{C}$	100	-	$\text{A}/\mu\text{s}$
Gate Controlled Delay Time	t_{gd}	$I_G = 10\text{mA}, di_G/dt = 0.1\text{A}/\mu\text{s}$	-	500	ns
Commutated Turn-Off Time	t_q	$T_C = +85^\circ\text{C}, V_D = .67 \times V_{DRM}, V_R = 35\text{V}, I_T = 5.1\text{A}$	-	100	μs



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [SCRs](#) category:

Click to view products by [NTE](#) manufacturer:

Other Similar products are found below :

[NTE5428](#) [NTE5448](#) [NTE5457](#) [NTE5511](#) [T1500N16TOF VT](#) [T720N18TOF](#) [T880N14TOF](#) [T880N16TOF](#) [TN1205H-6G](#) [TN1215-800B-TR](#)
[TS110-7UF](#) [TT104N12KOF-A](#) [TT104N12KOF-K](#) [TT162N16KOF-A](#) [TT162N16KOF-K](#) [TT330N16AOF](#) [VS-111RKI120PBF](#) [VS-16RIA100](#)
[VS-22RIA20](#) [VS-2N5206](#) [VS-2N685](#) [VS-40TPS08A-M3](#) [VS-50RIA10](#) [057219R](#) [T1190N16TOF VT](#) [T1220N22TOF VT](#) [T201N70TOH](#)
[T830N14TOF](#) [T830N18TOF](#) [TD92N16KOF-A](#) [TT250N12KOF-K](#) [VS-ST180S12P0V](#) [VS-25RIA40](#) [VS-16RIA120](#) [VS-30TPS08PBF](#)
[TN1215-800G-TR](#) [NTE5427](#) [NTE5442](#) [X0405NF 1AA2](#) [VS-ST300S20P0PBF](#) [T2160N28TOF VT](#) [TT251N16KOF-K](#) [VS-22RIA100](#) [VS-](#)
[16RIA40](#) [CR02AM-8#F00](#) [VS-ST110S12P0VPBF](#) [TD250N16KOF-A](#) [GA301A](#) [VS-ST110S16P0](#) [VS-10RIA10](#)