



What can we help you find?

📴 Share

Quick Links

Search for Tooling

🚞 Print

Check Pricing & Availability

Contact Us About This Product

Product Feature Selector




Email

Products Industries About TE Innovation Support Center Resources My Account

Home > Products > Product Feature Selector > Product Details

# 1326032-4 Product Details



1326032-4

TE Internal Number: 1326032-4 🥒 Active

#### Timer Contacts



#### Product Highlights:

- Timer Products Product Line
- 2.5 mm System Series, USCAR Series
- Wire-to-Wire
- Applies To Wire/Cable
- Contact

View all Features









#### Additional Information: Product Line Information

#### Related Products:

Tooling

# Documentation & Additional Information

#### Product Drawings:

2.8mm RECEPTACLE, SEALED (PDF, English)

#### Catalog Pages/Data Sheets:

None Available

#### Product Specifications:

None Available

#### Application Specifications:

2.8-mm Terminal System (Sealed and Unsealed) (PDF, English)

#### Instruction Sheets:

None Available

#### CAD Files:

None Available

#### Product Features (Please use the Product Drawing for all design activity)

## Product Type Features:

- Product Line = Timer Products
- Series = 2.5 mm System, USCAR
- Product Type = Contact
- Termination Method to Wire/Cable = Crimp
- Wire/Cable Type = Discrete Wire
- Insulation Support = With

## Termination Features:

- Wire/Cable Size (AWG) = 16
- Wire/Cable Size (mm²) = 1.25 1.4

## Dimensions:

• Mating Area Interface Dimensions (mm [in]) = 2.79 x 0.79 [.110 x

# **Body Features:**

Single Wire Sealing System = Yes

## Contact Features:

- Contact Type = Socket
- Contact Base Material = Copper Alloy
- Contact Plating, Mating Area, Material = Bright Tin
- Contact Plating, Mating Area, Thickness (μm [μin]) = 0.8 [31.49]

## Configuration Features:

GET 0.64 Connector System = No

## Industry Standards:

List all Documents

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

## **Environmental:**

Operating Temperature (°C [°F]) = 125 [257]

## Conditions for Usage:

- Applies To = Wire/Cable
- Accepts Wire Insulation Diameter, Range (mm [in]) = 1.88 2.34 [0.074 - 0.092]

## Operation/Application:

Application Use = Wire-to-Wire

## Packaging Features:

- Packaging Method = Standard Reeling
- Packaging Quantity = 2,500

- Brand = TE Connectivity
- Comment = Refer to the application and product specification for additional information.

Corporate Information

About TE Investors News Room Supplier Portal Careers

Quick Links

Check Distributor Inventory Cross Reference Products Find Documents & Drawings Product Compliance Support Center Customer Support

Email or Chat With Us Find a Phone Number Search Knowledge Base Manage Your Account

# Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address













Terms & Conditions Privacy Policy

Site Map

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for te connectivity manufacturer:

Other Similar products are found below:

570416-000 CLTEQ-M81CE-SSRELAY-4-20V 4-1633138-8 D38999/24FJ4AN 4-1195131-0 650069-000 SMD100-2 2EDL4CM
DTS20W19-11PD-3028 DTS20W19-11PD-3028-LC DTS20W19-32SD-3028-LC DTS20W19-32SD-3028 NC6-P104-06 TXR64AB903616AI DTS26F21-41HE DTS26F21-41AE DTS26F21-41PE-LC DTS26F21-11SE-3028-LC D38999/24WF32JE D38999/24WF32SE-LC
DTS24W19-32HE D38999/20JB35HA D38999/24WJ20PA 164-8033-08 D38999/24FF32JE D38999/24FF32SE-LC D38999/24WF32JB
D38999/24WG11HA D38999/24WG11HN MS27467T21F11H DJT16E21-11HA DTS24F19-32HE DTS20W19-32SA-3028-LC DTS24F1911SC-3028-LC DTS24F19-11SC-3028 DJT14E13-98HB D38999/20WC8BB 1-330599-5 DTS24F21-41HN-LC DTS24F21-41HN
DTS24F21-41AN DTS24F21-39HN DTS24F21-41PN-LC AFD50-10-6SN-1A-LC DJT10F17-26HC DTS24W19-32HB ACT20JE99HA
DJT10E17-26HC DJT10E17-26HN DJT10F17-26HA