PCI-1751

48-ch Digital I/O and 3-ch Counter PCI Card



Features

- 48 TTL digital I/O lines
- Emulates mode 0 of 8255 PPI
- Buffered circuits for higher driving capacity
- Interrupt handling capability
- Timer/Counter interrupt capability
- Supports both dry and wet contact
- Keeps the I/O port setting and DO state after system reset
- BoardID switch

FCC CE

Introduction

PCI-1751 is a 48-bit digital I/O card for the PCI bus. Its 48 bits are divided into six 8-bit I/O ports and users can configure each port as input or output via software. PCI-1751 also provides one event counter and two 16-bit timers, which can be cascaded to become a 32-bit timer.

Specifications

Digital Input

- Channels
- Compatibility
- Interrupt Inputs
- Input Voltage

Digital Output

- Channels
- Compatibility
- Output Voltage

Counter/Timer

- Channels
- Compatibility
- Resolution
- Base Clock
- Max. Input Frequency
- Clock Input
- Gate Input
- Counter Output

General

- I/O Connectors
- Dimensions (L x H)
- **Power Consumption**
- Temperature
- Relative Humidity

48 (shared with output) 5 V/TTL 2 (PC00,PC10) Logic 0: 0.8 V (max.) Logic 1: 2 V (min.)

- 48 (shared with input) 5 V/TTL Logic 0 : 0.8 V max. @+24 mA (sink)
- Logic 1 : 2 V min. @-15 mA (source) 3 channels are free for user applications 5 V/TTL
- 16-bit Channel 0 : Internal 10MHz External Clock (up to 10MHz) Takes input from output of Channel 0 External Clock (up to 10MHz) Channel 1 : Channel 2 : Internal 10MHz External Clock (up to 10MHz) 10 MHz
 - Logic 0 : 0.8 V (max.) Logic 1 : 2 V (min.) Logic 0 : 0.8 V (max.) Logic 1 : 2 V (min.)
- Logic 0 : 0.8 V max. @+24 mA (sink) Logic 1 : 2 V min. @-15 mA (source)
- 1 x 68-pin SCSI female connector 170 mm x 100 mm (6.9" x 3.9") +5V @ 850 mA (typical)
- +5V @ 1 A (max.)

CE/FCC

- Operating: 0 ~ 70°C (32 ~ 158°F) Storage: -20 ~ 80°C (-4 ~ 176°F) 5 ~ 95% RH, non-condensing (refer to IEC 60068-2-3)
- Certification

Ordering Information

- PCL-10168-1E
- PCL-10168-2E
- ADAM-3968
- ADAM-3968/20
- ADAM-3968/50
- PCLD-8751
- PCLD-8761
- PCLD-8762

1 2 3 4	35 36	PA10 PA11
2 3 4	36	PA11
3 4	27	
4	3/	PA12
	38	PA13
5	39	PA14
6	40	PA15
7	41	PA16
8	42	PA17
9	43	GND
10	44	PB10
11	45	PB11
12	46	PB12
13	47	PB13
14	48	PB14
15	49	PB15
16	50	PB16
17	51	PB17
18	52	GND
19	53	PC10
20	54	PC11
21	55	PC12
22	56	PC13
23	57	PC14
24	58	PC15
25	59	PC16
26	60	PC17
27	61	GND
28	62	CNTO_CLK
29	63	CNT0_G
30	64	CNT1_CLK
31	65	CNT1_G
32	66	CNT2_CLK
33	67	CNT2_G
34	68	VCC
	/	
	22 23 24 25 26 27 28 29 30 31 32 33 34	22 56 23 57 24 58 25 59 26 60 27 61 28 62 29 63 30 64 31 65 32 66 33 67 34 68

Pin Assignments

- PCI-1751
 - Accessories
- 68-pin SCSI Shielded Cable, 2 m 68-pin DIN-rail SCSI Wiring Board 68-pin SCSI to 3 20-pin Box Header Board 68-pin SCSI to 2 50-pin Box Header Board 48-ch Isolated Digital Input Board
 - 24-ch Replay/ Isolated Digital Input Board

48-ch Digital I/O and Counter PCI Card

68-pin SCSI Shielded Cable, 1 m

48-ch Relav Board

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Controllers category:

Click to view products by Advantech manufacturer:

Other Similar products are found below :

CS1WCN223 CS1WCN713 CS1WKS001E 61F-11NH 61FGPN8DAC120 61F-GP-NT AC110 61F-GPN-V50-AC110 70177-1011 F03-03 HAS B F03-03 HAS C F03-31 81513201 81513535 81550401 FT1A-C12RA-W 88981106 H2CAC24A R88A-CAGA005S R88A-CRGB003CR-E R88ARR080100S R88A-TK01K DCN1-1 DTB4896VRE DTB9696CVE DTB9696LVE MR-50LF+ E53-AZ01 E53E8C E5CWLQ1TCAC100240 B300LKL21 NE1ASCPU02EIPVER11 NE1SCPU01 NE1SDRM21U NSCXDC1V3 NSH5-232CW-3M NT20SST122BV1 NV3Q-SW41 NV4W-ATT01 NV-CN001 OAS-160-N K31S6 K33-L1B K3TX-AD31A L595020 SRS2-1 G32X-V2K 26546803 26546805 26546831 CJ1W-OD204