


Switched-Mode Power Supply, 1-Phase

EPSITRON® ECO Power



- Primary switch mode power supply unit
- Prepared for class I equipment
- Natural convection cooling when horizontally mounted
- Enclosed for use in switchgear cabinets
- Parallel operation, series connection possible
- Electrically isolated output voltage (SELV) acc. to EN 60950-1/UL 60950

Description	Item No.	Pack. Unit
Switched-Mode Power Supply, 24 VDC / 2.5 A	787-712	1

Technical Data	
Environmental requirements:	
Ambient operating temperature	-10 °C ... +70 °C
Storage temperature	-25 °C ... +85 °C
Rel. humidity	95 % (no condensation)
Derating	-3.3 % / K (> 55 °C at 230 VAC)
Degree of pollution	2 (acc. to EN 50178)
Climatic category	3K3 (acc. to EN 60721)
Safety and protection:	
Test voltage pri.-sec./ pri.-gr. / sec.-gr.	3 kV AC / 1.5 kV AC / 0.5 kV AC
Protection class	Prepared for class I equipment
Degree of protection	IP20 acc. to EN 60529
Overvoltage protection	via varistor at primary circuit
Short circuit protection	yes
No-load proof	yes
Feedback voltage	28 VDC
Parallel operation	yes
Series connection	yes
MTBF	480000 h (acc. IEC 61709)
Connection and type of mounting:	
Wire connection	CAGE CLAMP® (WAGO 745 Series)
Cross sections	0.08 ... 4 mm ² / AWG 28 ... 12 (THHN, THWN)
Strip lengths	8 ... 9 mm / 0.33 in
Type of mounting	DIN-rail mount (EN 60715)
Dimensions and weight:	
Dimensions (mm) W x H x L	50 x 92 x 136
	Height from upper-edge of DIN 35 rail
Weight	596 g
Standards and approvals:	
Standards/Specifications	EN 60950, EN 61000-6-2, EN 61000-6-3, UL 60950, UL 508, ANSI/ISA 12.12.01 (Class I Div.2), ATEX, IEC Ex

Technical Data	
Input:	
Nominal input voltage V_i nom	110 ... 240 VAC
Input voltage range	85 ... 264 VAC; 130 ... 373 VDC
Frequency	47 - 63 Hz
Input current I_i	0.7 A typ. at 230 VAC; 1.2 A at 115 VAC
Discharge current	< 1 mA
Inrush current	< 30 A
Mains failure hold-up time	> 20 ms at 230 VAC
Output:	
Nominal output voltage V_o nom	24 VDC (SELV)
Output voltage range	22 ... 28 VDC adjustable
Output current I_o	2.5 A at 24 V DC
Factory preset	24 VDC
Adjustment accuracy	1%
Residual ripple	< 100 mV (peak-to-peak) to 20 MHz
Overload behavior	Constant power (in overload range: 1.15 ... 1.4 x I_o); shutdown and automatic restart in the event of a short circuit
Operational indication	LED green (24 V DC o.k.), LED red (overload)
Efficiency / power losses:	
Efficiency	82 % typ.
Power loss P_V	8.3 W (at 230 VAC and 2.5 ADC)
Max. power loss P_V	11.5 W (at 110 VAC and 2.75 ADC)
Fuse protection:	
Internal fuse	F 2.5 A / 250 V
External fuse	Circuit breakers 10 A, 16 A, characteristic: B or C An external DC fuse is required for the DC input voltage

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wago manufacturer](#):

Other Similar products are found below :

[750-460](#) [231-118/026-000](#) [231-303/026-000](#) [231-620/019-000](#) [257-403](#) [280-438](#) [280-831](#) [284-624](#) [284-681](#) [206-861](#) [210-111](#) [231-303/037-000](#) [231-446/001-000_NR](#) [231-833/001-000](#) [232-216/026-000](#) [234-510](#) [264-726](#) [280-339](#) [793-500 2](#) [51228988](#) [209-132](#) [830-800/000-305](#) [788-507](#) [750-512](#) [264-321](#) [279-101](#) [281-365](#) [713-1428/107-000](#) [731-138/048-000](#) [750-459](#) [750-517](#) [750-601](#) [793-3505](#) [231-535/001-000](#) [2624-1103](#) [787-712](#) [713-1407](#) [2000-5457](#) [221-525](#) [832-1206](#) [832-3604](#) [281-512/281-501](#) [286-336](#) [288-437](#) [750-421](#) [750-838](#) [753-559](#) [750-1505](#) [787-732](#) [753-437](#)