

## **Features**

- PC Mountable
- Only 1.1 Cubic Inches
- Long Life
- Low Power Coil Types (L-suffix)



# SPDT, 1 Form "C"




DC OPERATED						
NTE Type No.	Nom. Volt.	Contact Arr.	Coil Res. Ohms (Typ)	Nom. Power	Max. Contact Cur. @ 28VDC or 120VAC	Diag No.
R48-5D5-6L	5/6VDC	SPDT	340	110mW	5A	D24
R48-5D5-12L	12VDC	SPDT	1350	100mW	5A	D24
R48-5D5-24L	24VDC	SPDT	5400	100mW	5A	D24
R48-5D10-6	5VDC	SPDT	100	110mW	10A	D24
R48-5D10-12	12VDC	SPDT	600	110mW	10A	D24
R48-5D10-24	24VDC	SPDT	2400	250mW	10A	D24

# **R48 Series**



# Miniature, General Purpose, 5 Amp & 10 Amp, DC, SPDT Relays for TV Remote Control, Burglar Alarms, Timers, Garage Door Openers.



# Recommended PC Board holes are .067 (1.7) Dia.

# **Electrical Specifications**

#### Contact

Rating: 5 Amp 120/240 VAC 10 Amp 28 VDC resistive load Material: Silver, gold plated

(R48-5D5-12L, R48-5D5-24L, R48-5D10-24)

Silver alloy

(R48-5D5-6L, R48-5D10-6, R48-5D10-12)

## Coil

Coil Voltages: See Chart

Pick-up Voltages: 80% of nominal Coil Vltg.

Drop-out Voltages: 10% of actual pick-up (min.)

Resistance: See Chart

Operational Characteristics
Timing Value ..... Operate Time: 25 mS

Release Time: 3 mS typ.

## **Insulation Characteristics**

**Dielectric Strength** 

Contact To Coil Voltages: 1500 VRMS Across Open Contacts: 500 VRMS Coil To Frame: 1500 VRMS Resistance: 1000 megohms min.

@ 500 VDC

## **Environmental Characteristics**

Operating: -55 C to +85 C Soldering: 270 C (518 F) max

Life

Mechanical: 10,000,000 operations

Weight

Std: 1.5 oz (42 grams) approx

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for NTE manufacturer:

Other Similar products are found below:

747 797 868 1724 NEH680M50FE NEHH1.0M450CB NTE526A 228A 231 954 2023 510 WH20-04-25 04-SLPE3750A 5615 591 69-36WW-WR-KIT 7056 7448 NEH.10M50AA NEH2.2M63AA NEH330M35DD NEH33M10AA NEV.22M100AA NEV470M50FF NTE133 NTE542 NTE74154 R02-11A10-120H 04-SCBW25L-BK 04-SCBW6C-BK 04-SCBW32L-BK 04-SCW10C-BK 04-SCBW19L-GR 04-SCW19L-WH 04-SCW19L-OR 04-SCW38L-WH 04-SCBW50L-OR 04-SCBW50L-GR 04-SCW10C-GR 04-SCW10C-OR 04-SCW10C-OR 04-SCBW32L-GR 04-SCBW32L-WH 04-SCBW32L-OR 04-SCBW6C-WH 04-SCBW6C-GR 04-SCBW6C-OR 04-SCBW25L-GR 04-SCBW25L