

MODEL NO.	LENGTH
CBL-USB2-2824-100	100 FEET
CBL-USB2-2824-500	500 FEET
CBL-USB2-2824-1000	1000 FEET

## USB BULK CABLE SPECIFICATION

CROSS-SECTIC	CROSS-SECTIONAL VIEW			COLOR CODE:	
Jacket Braided Shield Al/Mylar Shield		Twisted Pair Conductor Drain Wire	1. W 2. Liq 3. Bli 4. Re	ght Green ack	
		Twisted Pair		Conductors	
CONDUCTORS	CONDUCTOR SIZE, IN [MM]	28AWG 7X .005 [7X .127]		24AWG 7X .008 [7X .2]	
	MATERIAL	TINNED COPPER STRANDED		TINNED COPPER STRANDED	
	MATERIAL	POLYOLEFIN		SR-PVC	
INSULATION	DIAMETER, IN [MM]	.030 ± .003 [.76 ± .08]		.043 ±.003 [1.10±.08]	
JACKET	MATERIAL	PVC			
	DIAMETER, IN [MM]	.177 ± .006 [4.5 ± 0.15]			
	COLOR	BLACK			
	MATERIAL	ALUMINUM MYLAR			
FOIL SHIELD COVERAGE		125%			
	MATERIAL	TINNED COPPER			
BRAID COVERAGE		65%			
DRAIN WIRE	CONDUCTOR SIZE, IN [MM]	28AWG 7X .005 [7X .127]			
	MATERIAL	TINNED COPPER STRANDED			
MARKING	L-COM	AWM 2725 60°C 30V VW-1 USB CABLE REV. 2.0 28AWG/1P 24AWG/2C Exxxxx			
-	COLOR	WHITE			
		ELECTRICAL PROPERT	IES		
VOL	TAGE RATING		30\	/	
TEMPE	RATURE RATING	60 °C			
CONDUC	CTOR RESISTANCE			KM AT 20°C MAX KM AT 20°C MAX	
		CABLE TO BE RoHS COM	IPLIANT		

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for L-Com manufacturer:

Other Similar products are found below :

AVG2-KVM DVIHDMF TSP4088C5 CAUALB-3M CA-RSPNMA002 HG913Y-NF CSMNB15MF-15 CSMNB15MM-10 TRD815RA2BLK-5 TRD815RA2BL-5 WJ670300 CSM9MF-2.5 CA3A-90DA-1M CA3A-90LA-05M CA3A-90LMICB-03M CA3A-90RMICB-03M U3A00003-03M CTLF3VGAMM-20 HDCAMM-3 U3A00013-105M TSP8048C5S-10PK CSMT15MM-25 CSPL25MM-50 CSPL9MF-10 CSPL9MF-5 CSPL25MF-5 TRD855HFB-1M TRD855HFB-4M TRD855HFB-5M AL-IPEPS NB201611-10F-1 NB121005-10F TRD855SRA6DBL-1M TRD855SRA7DBL-10M U2A00016-3M U2A00017-03M PR175SCDLCQ24 U3A00089-2M TRA5261S-1F TRA6261-1F TRA6261-25F HG2415U-PRO-5PK USBBFT DGB25F CAUBLKAB-1M CASATAL-18 CIB24-6M CA3A-90LMICB-1M U2A00001-5M U3A00008-1M