

POWER ADAPTERS FOR LAPTOPS, ROUTERS AND MONITORS <a href="https://www.qoltec.com/product/power-adapters-for-laptops-routers-and-monitors/led-driver-led-driver-ip67-150w-12v-125a-waterproduct/power-adapters-for-laptops-routers-and-monitors/led-driver-led-driver-ip67-150w-12v-125a-waterproduct/power-adapters-for-laptops-routers-and-monitors/led-driver-led-driver-ip67-150w-12v-125a-waterproduct/power-adapters-for-laptops-routers-and-monitors/led-driver-ip67-150w-12v-125a-waterproduct/power-adapters-for-laptops-routers-and-monitors/led-driver-ip67-150w-12v-125a-waterproduct/power-adapters-for-laptops-routers-and-monitors/led-driver-ip67-150w-12v-125a-waterproduct/power-adapters-for-laptops-routers-and-monitors/led-driver-ip67-150w-12v-125a-waterproduct/power-adapters-for-laptops-routers-and-monitors/led-driver-ip67-150w-12v-125a-waterproduct/power-adapters-for-laptops-routers-and-monitors/led-driver-ip67-150w-12v-125a-waterproduct/power-adapters-for-laptops-routers-and-monitors/led-driver-ip67-150w-12v-125a-waterproduct/power-adapters-for-laptops-routers-and-monitors/led-driver-ip67-150w-12v-125a-waterproduct/power-adapters-for-laptops-routers-and-monitors/led-driver-ip67-150w-12v-125a-waterproduct/power-adapters-for-laptops-routers-and-monitors/led-driver-ip67-150w-12v-125a-waterproduct/power-adapters-for-laptops-routers-and-monitor-and-monitor-and-monitor-and-monitor-and-monitor-and-monitor-and-monitor-and-monitor-and-monitor-and-monitor-a



LED Driver IP67 150W | 12V | 12.5A | Waterproof

Product code: 50945

High-quality Qoltec Waterproof LED Power Supply destined to power led strips, modules, panels, led bulbs and other electronic devices powered by 12VDC. It can be used inside and outside buildings

Power: 150 W Output Voltage: 12 V Output current: 12.5 A

TECHNICAL DATA

INPUT VOLTAGE	230 V
USABLE POWER	150 W
OUTPUT VOLTAGE	12 V
OUTPUT CURRENT	12.5 A
ADDITIONAL INFORMATION	Plastic case Waterproof
WARRANTY	24 months
FREQUENCY RANGE	47-63Hz
WORKING TEMPERATURE	-20~ +60 C
OVERLOAD	Larger than 105% of capacity restoration after abnormity removed
EFFICIENCY	82%
VOLTAGE ADJUSTMENT	11.6-12.4V
VOLTAGE ACCURACY	3%
LINEAR ADJUSTMENT	0.5%
LOAD ADJUSTMENT	2%
START AND RISE TIME	1000ms,30ms/230VAC
HOLD TIME	50ms/230VAC
INPUT VOLTAGE RANGE	175-264VAC

WWW.QOLTEC.COM 1 / 2

AC CURRENT	088A/220V
SURGE CURRENT	Cold start: 65A/230VAC
OVERHEAT	Overheat protection starts when temperature in transistor over 140 C Automatic restoration when temperature is back normal
WORKING HUMIDITY	20~90%, whitout condense
STORAGE TEMPERATURE	-40~+80 C
VIBRATION PROFF	10~500Hz,5G 10min/cycle, X Y Z axes 60 min each
DIMENSIONS	190 x 37 x 62 mm
IP RATING	IP67
R&N	220mVp-p
EAN CODE	5901878509457

WWW.QOLTEC.COM 2 / 2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Power Supplies category:

Click to view products by **QOLTEC** manufacturer:

Other Similar products are found below:

ESS015W-1000-12 EUC-075S105DT PDA-WIFI PIFC-K250F PITB-K222A ALD-514012PJ134 LB240S24KH LMH020-SPLC-0000-0000001 LMD600-0100-C1A7-7030000 79534 79535 EUG-200S210DT ESS030W-1050-21 ESS030W-0900-32 BPOXL 4-12-035 SLM160W-3.9-40-ZA LE42S24VN ESS010W-0180-42 ESS010W-0350-24 ESS010W-0200-42 ESM060W-1400-42 PDA080B-1A0G ESS010W-0500-12 PDA150B-S1A5G ZPS-20 SLM140W-1.05-130-ZA ESS040W-1400-27 ESS015W-0700-18 ESS010E-0250-42 EVM120W-2700-42-ECN2 79278 MU060C105AQ_0-10V EUD-150S350DVA LSWC-040S105PS LWA320-C420-ARK-B 50304 HVG-320-36AB HVG-320-54AB ELEMENT 30/220-240/700 S OT FIT 38/220-240/900 CS S MINI ELEMENT 180/220-240/24 G2 PWM-40-36 PWM-60-36 LUD-060S150BSF RCD-48-1.00 ESS010W-0750-12 EUC-036S035DV EUC-036S045DV EUC-036S070SV EUC-042S105DS