



Uninterruptible power supply | 600VA | 360W | LCD

Product code: 53911

Qoltec offline UPS emergency power supply is a modern and economical device that ensures stable operation of connected electronic devices even in the event of a power failure. The duration of a power supply with a 100W load is 14 minutes. The UPS protects connected devices against loss and voltage drop in the network and excludes the possibility of damage in the event of overvoltages in the electricity network, also protects against overloads and short circuits. The Qoltec offline UPS will meet the requirements of anyone who wants to have control over the stable operation of their devices regardless of fluctuations in the mains supply. Thanks to the highest quality and wide range of operation, it is an ideal solution for powering desktops and other peripheral devices at home or in the enterprise, as well as in educational institutions and offices.

UPS

Qoltec emergency power system UPS offline is a modern and economical device, which provides emergency power to connected loads when the input power source or mains power fails. UPS protects connected devices from power disruption, voltage spike and eliminates possible damage in case of mains power overvoltage. It also protects connected loads from overloads and short circuit. A definite advantage of our UPS is LCD display, which provides information about status and measurements according to current operating mode. Thanks to that monitoring operation of a device will be easy, quick and reliable. Qoltec UPS offline meets everyone's requirements, who are looking for device, which protects connected loads from instability of the mains frequency. Thanks to high quality and wide operating range it is perfect solution for people who want to have ensured the continuity of operation of computers and other peripheral devices in home, enterprise, educational institutions and government offices. UPS offline is also indispensable to power central heating pump.

TECHNICAL DATA

RUNTIME (100W)	14 min
USABLE POWER	360 W
RATED CAPACITY	600 VA
POWER FACTORY	0.6
LOAD TYPE	Personal computer and other PC peripheral devices

AC VOLTAGE RANGE	140Vac ~ 290Vac / 5Vac
AC FREQUENCY	40Hz ~ 70Hz / 1Hz
OUTPUT RANGE (LINE)	220Vac - 230Vac / 10%
OUTPUT FREQUENCY (LINE)	40Hz ~ 70Hz / 1Hz
OUTPUT VOLTAGE (BATTERY)	220Vac - 230Vac / 5%
OUTPUT FREQUENCY (BATTERY)	50Hz - 60Hz / 1Hz
TRANSFER TIME	10ms
OUTPUT SOCKETS	1 x IEC 2 x SCHUKO
BACKUP TIME	> 6 min (half charge)
BUILT-IN BATTERY	1x12V / 7Ah
SCREEN	LCD
CHARGING TIME	8 hrs (to fully charged)
STORAGE TEMPERATURES	-15°C to 45°C
OPERATING TEMPERATURE	0°C to 40°C
RELATIVE HUMIDITY	0% - 90%
SAFETY	Surge protection Overload protection Short Circuit Protection Under/Overvoltage Protection
ADDITIONAL INFORMATION	LCD display Auto charging Charging in UPS OFF Mode Sound signal LEDs
PACKAGE CONTENTS	UPS with built-in power cable (1xSchuko) 1.2m User manual Warranty card
NOISE	35dB (1 meter from front panel)
NETWORK PROTECTION	RJ45 / 11 surge protector (Optional)
COMMUNICATION INTERFACE	Intelligent RS-232 / USB (Optional)
DIMENSIONS	340 x 102 x 155 mm
WEIGHT	4.8 kg
WARRANTY	24 months
EAN CODE	5901878539119
SHORT CIRCUIT	Auto protection. Output shuts off and the buzzer beeps continuously.
OVERLOAD	110% 120%, buzzer beeps. UPS switches off within 5 minutes; >120% buzzer beeps continuously, UPS immediately turns off

BATTERY PROTECTION

Auto protection. The UPS auto shutdown when battery voltage is low or high.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Fans](#) category:

Click to view products by [QOLTEC](#) manufacturer:

Other Similar products are found below :

[614R](#) [6424/2HP-210](#) [8312R](#) [DV4118/2NP-183](#) [AFB0948HH-S687](#) [PFB0824DHE-8B72](#) [G2E085-AA05-10](#) [RD20S-4/210660](#) [4318/12T](#)
[4418HH](#) [AUB0912H-F00](#) [3412N/2ME](#) [K2E225-RA92-09](#) [4184N/2XR](#) [5214N2HH](#) [614J2HHPR-010](#) [8412NGL-12](#) [4114N/12HHR-297](#)
[4656](#) [ZWR-903](#) [4112N12GL-175](#) [KD2406PKB2.\(2\).GN](#) [AFB1248HHE](#) [AFB1212LE-F00](#) [FAN-SCH-1](#) [MF60151V1-1000U-G99](#)
[PF80252V1-1000U-G99](#) [PF92252V1-1000U-G99](#) [4112N/2H6P](#) [4114N/17-251](#) [6212NH](#) [622/2N](#) [712F-011](#) [8218J/2NP-181](#) [W1G180-AB47-](#)
[15](#) [FAA1-12038NBKW31-A](#) [6318N/2TDP](#) [6318N/2H3PU](#) [6318HU](#) [424JMU](#) [PMD1206PTVX-A.U.GN](#) [PF80251B2-000U-F99](#)
[EF40101BX-1000U-G99](#) [AD1224LB-A71GL](#) [9GA0924L4021](#) [9GA0924M4021](#) [9GA0924M4011](#) [9GA0824B20011](#) [9GA0812A2D0011](#)
[9GA0912M4D011](#) [9GA0924W4D01](#)