

# R13 PUSH SWITCH

### D42 E64A

### R13-564A








<u>∞</u> 0.7~3.5 mm max


#### **FEATURES**

- \* MATERIAL: Frame is sn plated brass. Plunger are nylon(UL flame: 94V-2). Terminals are au plated brass.
- \* Mounted by screws.



\* ( ) = momentary **R13-565** 






### **FEATURES**

\* MATERIAL: Hosing is nylon (UL flame: 94V-2). Bottom are PBT. Lens are PC.

R13-565

- \* Mounted by screws.
- \* LED indepéndent.



**10 mm max** 7~10 mm max

				.,
UNCTION	KNOB	FRAME & ACTUATOR	LED VOLTAGE (independent)	,
SPDT ON-(ON)	1	MATERIAL		
'		1 Bass with Ni plated	1 12V DC	
SPDT ON-ON			2 24V DC	
PDT ON-(ON)			a LFD Independent	
	TERMINAL	LENS COLOR	(regular rating)	
OPDT ON-ON	1 5 T.110" SQ (2.8°0.5t)	LED COLOR	( 0 0/	
OPDT ON-ON OPDT ON-ON	TERMINAL  1 5 3.110" SQ (2.8°0.51)	5 SUS 304 LENS COLOR		



All the specifications are subject to change without notice.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by SCI manufacturer:

Other Similar products are found below:

LW1L-M1C10V-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M7E-HRN2 67021K512 67081K512X 701PB580 MDPSSGLFS

810K2M1ZQJ8122 810KSV30B 82PB19-H58 FLT 2U EE 01A MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2

8442K2 8646AB6X718UL 8646ABUL FSDWH 9001KXRK 9001T8BK 9533CD4+U574+U4922 1203MRA A22EM01S

A22NZRNMNBA A3AT-90A1-00L A595 1202A6 12037A2ULCSA 1203A2UL ABD122N-B 1211390004 ABN111-Y ABN400-R

1211500044 1211580012 1212MRA 1232A6NF 1241.1183.7047 1241.2511 1241.3428 1223A2ULCSA 1223MRA 1232AX2119

1241.1183.8000 1241.1183.8029 1241.2506 1241.2606