
Features

- **Current or Voltage Input Types**
- **SCR Output**
- **Zero Crossing Switching**
- Standard 16-Lead DIP Type Package with 4 Pins




RS4 Series



Printed Circuit Board Mountable Solid State Relay, 1 Amp.

D63



Input Specifications

RS4-1D1-A (Current Input Type)

Control Current Range: 10-35mA Must Turn-On Current: 10mA Must Turn-Off Current: 1mA

RS4-1D1-B (Voltage Input Type)

Control Voltage Range: 3.5-10VDC Nom. Input Impedance: 270Ω Typ. Input Current (@ 5VDC): 15mA Must Turn-On Voltage: 3.5VDC Must Turn-Off Voltage: 1.0VDC

utput Specifications

Operating Voltage Range: 20-280V (RMS) Load Current Range: 0.01-1.0A (RMS) Transient Over-Voltage: 600V (Peak) Max. Surge Current (16.6ms): 30A (Peak)
Min. Off-State dv/dt: 500V/μs at max. rated voltage

Max. Off-State Leakage Current: 0.01mA (RMS) at rated voltage Max. On-State Voltage Drop: 1.2V (Peak) at rated current

Max. Turn-On Time: 1/2 cycle Max. Turn-Off Time: 1/2 cycle

Power Factor (Min.) with Max. Load: 0.5


ctrical Specifications

Dielectric Strength (Input-Output Isolation): 3750V (RMS)

Min. Insulation Resistance (@ 500VDC): $10^9 \Omega$ Max. Capacitance (Input-Output): 2.0pF **Environmental Characteristics**

Operating: -30°C to +80°C Storage: -30°C to +125°C

Pin Connection Diagram



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for NTE manufacturer:

Other Similar products are found below:

747 797 868 1724 NEH680M50FE NEHH1.0M450CB NTE526A 228A 231 954 2023 510 WH20-04-25 04-SLPE3750A 5615 591 69-36WW-WR-KIT 7056 7448 NEH.10M50AA NEH2.2M63AA NEH330M35DD NEH33M10AA NEV.22M100AA NEV470M50FF NTE133 NTE542 NTE74154 R02-11A10-120H 04-SCBW25L-BK 04-SCBW6C-BK 04-SCBW32L-BK 04-SCW10C-BK 04-SCBW19L-GR 04-SCW19L-WH 04-SCW19L-OR 04-SCW38L-WH 04-SCBW50L-OR 04-SCBW50L-GR 04-SCW10C-GR 04-SCW10C-OR 04-SCW10C-OR 04-SCBW32L-GR 04-SCBW32L-WH 04-SCBW32L-OR 04-SCBW6C-WH 04-SCBW6C-GR 04-SCBW6C-OR 04-SCBW25L-GR 04-SCBW25L