

Description:	Reliseal V56 is a universal connecting and branch joint, which can be used for connections as well as individual branches of plastic cables and wires made from PVC, PE, EPR and VPE. irrespective of the type of terminal in question. Das Relicon® gel in the shell insulates and seals the connection. The moulding shells have a strain relief and are made from impact- proof PP and are bound with a film hinge.
Area of application:	Indoors, outdoors, underground, underwater, in installation channels
Properties:	Fulfil IP68, 10 meters perfect strain relief Good insulating properties through the use of Relicon® gel Non-toxic gel No mixing necessary Reopenable Easy to assemble UV- resistant Resistant to ageing Weather- resistant Temperature resistant from -20°C to 90°C incl. connector block
Storage:	Unlimited storage life
Included:	Gel shell filled with Relicon® gel Screwing for the strain relief Assembly instructions Connector 3 x 2,5mm ² to 5x6 mm ² Adapter seal for different cable diameters
Construction site- ready:	Tried and tested Construction site- ready Relicon® system incl. Terminal for connections up to 5x6mm ² in size; ready for assembly as a complete set
Tests:	Certified according to DIN EN 50393 (corresponds DIN VDE 0278-393) DIN EN 60695-2-11 (corresponds VDE 0471-2-11) test on the flammability of end products using a filament DIN EN 60529 (corresponds VDE 0470-1) protection class by boxes

Article-No.	Typ	Cable diameter	Conductor cross-section mm ²		Socket dimensions
		mm (from-to)	from	to	mm (LxWxH)
435-01660	Reliseal V56 PP GY	Main cable: 12-18	3 x 2,5	5 x 6	190 x 60 x 47



HellermannTyton

HellermannTyton GmbH
Grosser Moorweg 45
D-25436 Tornesch

Telefon: +49 (0) 4122/701-1
Telefax: +49 (0) 4122/701-400

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Cable Glands, Strain Reliefs & Cord Grips](#) category:

Click to view products by [Hellermann](#) manufacturer:

Other Similar products are found below :

[120-116-1-1-20BP](#) [120-116-1-1-32BE](#) [120-117-40](#) [120-123-14](#) [120-123-16](#) [120-125-16](#) [120-125-16R](#) [120-125-16Y](#) [120-125-24Y](#) [120-125-28](#) [120-125-28R](#) [120-125-32](#) [120-125-32R](#) [120-125-40](#) [120-125-56](#) [120-126-14](#) [120-126-16](#) [120-126-20](#) [120-126-20BL](#) [120-126-20R](#) [120-126-24](#) [120-126-28](#) [120-126-32](#) [120-126-40BL](#) [120-116-1-1-06BP-509](#) [120-116-1-1-06CP](#) [120-116-1-1-16BE](#) [120-116-1-1-28BP](#) [120-123-20](#) [120-123-24](#) [120-123-32](#) [120-125-20](#) [120-125-20Y](#) [120-125-24](#) [120-125-24R](#) [120-125-28Y](#) [120-126-14BL](#) [120-126-16R](#) [120-126-16Y](#) [120-126-24BL](#) [120-126-28BL](#) [120-126-32BL](#) [120-126-40](#) [120-126-48](#) [120-126-48BL](#) [1300980012](#) [1300980105](#) [DBZM-6828](#) [1498](#) [15190-103 R2](#)