

Product information RSC 30 - RSC 50 - RSC 50/11

Industrial Connecting Solutions: Circular Connectors: 7/8", M23 Connectors: 7/8" Connectors: Field Attachable 7/8" Connectors: Connectors: RSC 30 - RSC 50

 $http://e-catalog.hirschmann.com/link/57078-24228-256281-256289-256290-276563-276565-248841/en/RSC_05-11/uistate$

240 V

250 V

> 1 GΩ

UL

1.5 kV eff./60 s

RoHS 2002/95/EG

| Name | RSC 30 - RSC 50 |
|---------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | |
| | Field attachable connector, 7/8" male connector, straight version, with threaded joint, assembling with screw terminals, 5 poles, screwed cable gland with PG |
| Delivery informations | 11 thread. |
| Delivery informations | - Danish Is |
| Availability Product description | available |
| · | RSC 50/11 |
| Type Order No. | 11592 |
| | |
| Description | Field attachable connector, 7/8" male connector, straight version, with threaded joint, assembling with screw terminals, 5 poles, screwed cable gland with PG 11 thread. |
| Number of contacts | 11 ulread. |
| | black |
| Color of housing Product characteristics | |
| Mechanical data | Oil resistance |
| Type of plug-in contact | Male connector |
| | ***** |
| Design of housing | straight 7/8" |
| Thread | |
| Design of electrical connection | screw connection |
| LED display present | X |
| Screw joint for cable for external cable diameter | 8.0 mm 10.0 mm |
| Screwed cable gland, connecting thread | Pg11 |
| Environmental conditions | |
| Environmental temperature | -40 °C 90 °C |
| Degree of protection (IP), mounted | IP67 |
| Pollution degree | 3 |
| Materials | |
| Housing material / Molded body | PA |
| Contact bearer material | TPU, self-extinguishing |
| Contact material | CuZn |
| Contact material - Surface refinement | silver-plated and gold-plated |
| Knurled screw / nut material | Al anodized |
| Sealing material | NBR |
| Electrical data | |
| Contact resistance | $\leq 5 \text{ m}\Omega$ |
| Rated current In | 9 A at 40°C, UL and notice derating |
| | |



Nominal voltage Rated voltage

Insulation resistance

RoHS 2002/95/EG compliant

Test voltage


Approvals Approvals



Industrial Connecting Solutions: Circular Connectors: 7/8", M23 Connectors: 7/8" Connectors: Field Attachable 7/8" Connectors: Connectors: RSC 30 - RSC 50 http://e-catalog.hirschmann.com/link/57078-24228-256281-256289-256290-276563-276565-248841/en/RSC_05-11/uistate

Picture

Drawing



- *a O-Ring O-ring *b Stift oder Schraubendreher als Montagehilfe pin or screwdriver as assembly tool
- *

 Kontakt 1,5 voreilend contact 1.5 leading

Belden Deutschland GmbH

Im Gewerbepark 2 58579 Schalksmühle Germany

Phone: +49 7127/14-1806 E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Standard Circular Connector category:

Click to view products by Lumberg manufacturer:

Other Similar products are found below:

C015 10F006 001 1 5M2530B10P 600247N007 600259N006 6280-2PG-519 6280-3PG-311 6280-3SG-311 6280-7SG-3DC 6280-7SG-522 6282-2SG-321 6282-5PG-311 6282-6PG-519 6283-11 6283-15 6290 6293 6382-2PG-311 6382-2SG-321 6382-2SG-3DC 6382-4SG-516 67-03E20-37P 680-SMG 681-PMG CXS3102A14S2P CXS3102A181S D38999/20FC8SA L/C MB12P-1 MB12R-6 7251-2PG-300 7251-2SG-300 7251-4PG-300 7251-4SG-300 7251-5PG-300 7251-5SG-300 7251-6SG-300 7251-7PG-300 7251-8PG-300 7271-6SG-300 7282-3PG-300-CH3 7282-8PG-3ES 73000005663 75-190216-08S 75-190218-10P 75-190614-07S 75-214636-52P 75-474118-10P 75-474211-03P 75-474218-19S 75-474618-01S 75-474620-07P