

MINIATURE LAMP (PR13) Details



Part #	PR13				
Description	PR BULB 4.75V .50A 2.0CP				
Bulb Shape	B-3 1/2	Filament	C-2R	Base Style	S.C. Miniature Flanged
Glass Diameter (in)	0.43	MOL [†] (in)	1.25	LCL ^{††} (in)	0.25
Glass Diameter (mm)	11	MOL (mm)	31.75	LCL (mm)	6.35
Volts	4.75	MSCP [‡]	2	Avg Life Hrs	15
Watts	2.375	Amps	0.50	RoHS Compliant	

† MOL (Maximum Overall Length):

The overall length of a lamp, from the top of the shell to the bottom of the base.

‡ MSCP (Mean Spherical Candlepower):

Candlepower produced at design volts. Candlepower is increased rapidly with an increase of applied voltage and conversely is reduced rapidly with a reduction of applied voltage.

†† LCL (Light Center Length):

The distance from a reference point, usually the bottom of the lamp base, to the center of the light source.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [CEC manufacturer:](#)

Other Similar products are found below :

[303](#) [243](#) [50](#) [81](#) [28PSB](#) [L20120CS-W](#) [120MB](#) [E85](#) [85](#) [47](#) [657](#) [120PSB](#) [130MB](#) [1815](#) [46](#) [1141](#) [927](#) [908](#) [93](#) [1866](#) [44](#) [1829](#) [1820](#) [H3-55W](#) [1847](#)
[939](#) [3175](#) [51](#) [1818](#) [161](#) [388](#) [680](#) [1156](#) [1813](#) [7371](#) [H3-70W/24V](#) [655](#) [756](#) [464](#) [112](#) [1835](#) [1819](#) [40](#) [7219](#) [757](#) [222](#) [N-F-24.000M-10-1015-3085-40](#)
[K-F-12.000M-16-2030-2070-100](#) [755](#) [K-F-16.000M-9-2020-2070-60](#)