



▶ AIRTOOLS

SILENT YET POWERFUL, POWERFUL YET LIGHTWEIGHT, LIGHTWEIGHT YET DURABLE

Generations of proud professionals have developed their skills together with Bahco tools since 1886 and already in the middle of last century Bahco has been synonymous with high quality air tools.

We are proud to present a strong comeback in the air tools business with a range of unique products. A range that incorporates Bahco's spirit of innovation and unrelenting quality. A range of silent yet powerful, powerful yet lightweight, lightweight yet durable tools, designed for high demands, from the toughest job to the most accurate precision job, from the smallest car to the largest truck.

In other words a complete range of professional air tools for everyday use!



BAHCO - THE CHOICE OF TRUE PROFESSIONALS

► AIR TOOL ICONS

PRODUCT CODE	PACKAGING DIMENSIONS	DRIVE	MAXIMUM TORQUE IN REVERSE MODE	TORQUE RANGE	SPEED - REVOLUTIONS PER MINUTE / STROKES PER MINUTE	SOUND PRESSURE	AIR CONSUMPTION	ENGINE OUTPUT
AIR INLET	HOSE DIAMETER / RECOMMENDED MIN. HOSE DIAMETER	TOOL WEIGHT	CHUCK / COLLET SIZE	DISC/BELT DIAMETER	EXCENTRIC	VIBRATION LEVEL	LENGTH	PACKAGED QTY

▶ BAHCO AIR TOOLS SPECIAL FEATURES

FAST AND EASY!



▶ TRUE ONE HAND DIRECTION AND POWER CONTROL KNOB

- Easy to change direction with one hand
- Easy to change power output with one hand

	BPM916	Impact wrench 3/8"		BPM914	Mini impact wrench 1/2"		BPM915	Impact wrench 1/2"
--	--------	--------------------	--	--------	-------------------------	--	--------	--------------------

DURABLE AND LIGHTWEIGHT!



▶ ONE PIECE MAGNESIUM HOUSING

Atomic number 12 (Magnesium) is prized for its lightness and strength. Its ions are essential to all living cells and the 11th most abundant element in the earth's crust

- Significantly lower weight
- Significantly increased durability

	BPM916	Impact wrench 3/8"		BPM914	Mini impact wrench 1/2"		BPM915	Impact wrench 1/2"
--	--------	--------------------	--	--------	-------------------------	--	--------	--------------------

SILENT AND LIGHTWEIGHT!



▶ COMPOSITE HOUSING AND HEXAGONAL RUBBER SLEEVE

- Significantly lower weight
- Significantly lower sound pressure
- Significantly lower vibration levels
- Great insulation against cold air
- User friendly grip

	BP816	Impact wrench 3/8"		BP824	Reciprocating saw		BP825	Reversible drill 13 mm
	BP815	Impact wrench 1/2"		BP601	Random orbital sander 5 mm		BP820	Ratchet 3/8"
	BP817	Impact wrench 3/4"		BP610	Random orbital sander 2,5 mm		BP821	Ratchet 1/2"
	BP823	5" Disc grinder		BP826	Reversible screwdriver 1.800 RPM		BP822	Mini grinder
	BP110	Cut-off tool		BP827	Reversible screwdriver 800 RPM		BP115	Angle grinder
	BP814	Impact wrench 1/2"		BP117	Low Revolution Grinder		BP822E	Extended die grinder

POWERFUL DURABILITY!




▶ TWIN HAMMER MECHANISM

- Reliable system for continuous torque increase with two hammers
- Resilient to air pressure fluctuations
- Consisting of surprisingly few parts
- Easy lubrication from the outside without dismantling the housing

	BP814	Impact wrench 1/2"		BPM916	Impact wrench 3/8"		BPM914	Mini impact wrench 1/2"
	BP816	Impact wrench 3/8"		BP817	Impact wrench 3/4"		BP900L	Long anvil impact wrench 1"
	BP815	Impact wrench 1/2"		BP900	Impact wrench 1"		BP915	Impact wrench 1/2"

THE CHOICE IS YOURS! EXTRA POWERFUL & SILENT or EXTRA SILENT & POWERFUL!



▶ EXCHANGEABLE MUFFLER SYSTEM

- Adapt the performance of the tool after your demands!
- Attach either one or two of the included optional mufflers and decrease the sound level remarkably with just a nominal power loss

	BP921	Ratchet 1/2"		BPM914	Mini impact wrench 1/2"		BPM915	Impact wrench 1/2"
	BPM916	Impact wrench 3/8"						

SMOOTH OPERATION!



▶ SWIVEL CONNECTION

- Allows the air hose to follow the tool naturally
- Higher comfort when operating

	BP816	Impact wrench 3/8"		BP820	Ratchet 3/8"		BP115	Angle grinder
	BP815	Impact wrench 1/2"		BP822	Mini grinder		BP824	Reciprocating saw
	BP814	Impact wrench 1/2"		BP110	Cut-off tool		BP822E	Extended die grinder
	BP821	Ratchet 1/2"						

A FAMILY WITH ATTITUDE!

EXTREME POWER!
The 8 VANES TWIN HAMMER mechanism delivers maximum power at minimum air consumption in no time



MAINTENANCE FREE!

We know you DON'T have time to lubricate your gun. Now you DON'T have to feel guilty about it because you DON'T NEED TO DO IT!

The exceptional OIL BATH lubrication system with high grade synthetic racing oil ensures a MAINTENANCE FREE TOOL and LONG LIFETIME

SMART DESIGN

Flat rubber covered top ensures a stable grip. Supplied with a black vinyl protection boot

CLUMSY?

No worries! The well balanced ONE PIECE MAGNESIUM HOUSING ensures extreme durability



**CONFUSED?
FORWARD? REVERSE?
MAX? MIN?**
Change DIRECTION and POWER output in 1 SECOND with ONE HAND! No need to WASTE TIME by USING TWO HANDS any more



**EXTRA SILENT & POWERFUL or
EXTRA POWERFUL & SILENT?**

The system with optional mufflers gives YOU the CHOICE to quickly adapt the tool to YOUR DEMANDS and needs! Use 0, 1 or 2 of the included mufflers! With no muffler the power is maximized, with 2 mufflers the sound is minimized

[mag-NEE-zee-əm]

IMPACT WRENCH 1/2"



THE CHOICE IS YOURS!

Muffler	MAX Nm	% Nm	dBa	%
0	1098 Nm		102.5 dBA	
1	1015 Nm	-7,6%	92.5 dBA	-316 %
2	935 Nm	-14,8%	86.6 dBA	-623 %

BPM915	100x250x250	1/2	1098	813	9.800	≤102,5	5,1	178	1/4	10	2,20
--------	-------------	-----	------	-----	-------	--------	-----	-----	-----	----	------

[mag-NEE-zee-əm]

MINI IMPACT WRENCH 1/2"



THE CHOICE IS YOURS!

Muffler	MAX Nm	% Nm	dBa	%
0	440 Nm		96.6 dBA	
1	414 Nm	-6%	90.3 dBA	-275 %

BPM914	100x250x200	1/2	440	300	10.700	≤96,6	4,54	68	1/4	10	1,30
--------	-------------	-----	-----	-----	--------	-------	------	----	-----	----	------

[mag-NEE-zee-əm]

IMPACT WRENCH 3/8"



THE CHOICE IS YOURS!

Muffler	MAX Nm	% Nm	dBa	%
0	440 Nm		99.1 dBA	
1	414 Nm	-6%	90.3 dBA	-275 %

BPM916	100x250x200	3/8	440	300	10.700	≤99,1	4,5	68	1/4	10	1,30
--------	-------------	-----	-----	-----	--------	-------	-----	----	-----	----	------

All technical specifications are stated at the recommended working pressure of 6.2 bar

POWERFUL YET LIGHTWEIGHT!



BP814 merely 1.2 kg and striking a maximum torque of 410 Nm in reverse

▶ MINI IMPACT WRENCH 1/2"



- Composite housing
- Twin hammer mechanism
- Air exhaust in handle
- Swivel connection

BP814	60x187x195	1/2	410	220-360	10.000	88	6,53	85	1/4	10	1,20

▶ IMPACT WRENCH 3/8"



- Composite housing
- Twin hammer mechanism
- Air exhaust in handle
- Swivel connection

BP816	60x187x195	3/8	410	220-360	10.000	88	6,53	85	1/4	10	1,20

▶ 3/8" IMPACT WRENCH SET



- Includes:
- One BP816
 - Eleven impact sockets
 - One 1/4" threaded male coupler
 - Supplied in robust plastic case with foam inlay (compatible with Bahco tool trolley modular system, T12)

BP816K1	108x371x321	10-24	2,20

All technical specifications are stated at the recommended working pressure of 6.2 bar

▶ IMPACT WRENCH 1/2"



- Composite housing
- Twin hammer mechanism
- Air exhaust in handle
- Swivel connection

BP815	78x215x210	1/2	825	320-620	7.000	84	5,00	130	1/4	10	1,95

▶ 1/2" IMPACT WRENCH SET



Includes:

- One BP815
- Eleven impact sockets
- One 1/4" threaded male coupler
- Supplied in robust plastic case with foam inlay (compatible with Bahco tool trolley modular system, T12)

BP815K1	108x371x321	10-24	3,20

▶ IMPACT WRENCH 3/4"



- Composite housing
- Twin hammer mechanism
- Air exhaust in handle

BP817	100x290x250	3/4	1.800	340-950	4.500	88	4,30	190	3/8	10	3,95

FOR THE LARGE ONES!



BP900L impressive 2.800 Nm!



All technical specifications are stated at the recommended working pressure of 6.2 bar

▶ EXTRA POWERFUL IMPACT WRENCH 1"



- Extremely powerful
- Air exhaust in handle
- Pin clutch mechanism

BP405	115x335x280	1	3.796	813-1.898	4.000	92	5,10	235	1/2	13	11,80

▶ IMPACT WRENCH 1"



- Heavy duty model
- Twin hammer mechanism
- 2" anvil
- Air exhaust in handle
- Power control in both directions

BP900	260x720x360	1	2.800	1.200-2.700	3.900	99	11,60	1.840	1/2	13	12,0

▶ LONG ANVIL IMPACT WRENCH 1"



- Heavy duty model
- Twin hammer mechanism
- 6" anvil for great accessibility
- Air exhaust in handle
- Power control in both directions

BP900L	260x720x360	1	2.800	1.200-2.700	3.900	99	11,60	1.840	1/2	13	12,50

▶ RATCHET 1/4"



- Speed control system for accurate operation
- Extra compact

BP700	45x210x75	1/4	164	0-30	300	94	3,60	65	1/4	10	0,50

▶ RATCHET 3/8"



- Speed control system for accurate operation
- Hexagonal rubber sleeve
- Air exhaust control system
- Swivel connection

BP820	60x235x60	3/8	201	0-67	270	80	2,6	120	1/4	10	1,20

▶ RATCHET 1/2"



- Speed control system for accurate operation
- Hexagonal rubber sleeve
- Air exhaust control system
- Swivel connection

BP821	56x280x65	1/2	260	0-67	150	80	2,60	120	1/4	10	1,20

All technical specifications are stated at the recommended working pressure of 6.2 bar

THE LONG & STRONG!

EASY TO HANDLE!
Balanced lightweight house for superior control and comfortable usage

COMFORTABLE TO HANDLE!
Soft grip handle with increased comfort, reduced vibration, and increased insulation against cold

HEAVY WORK LOAD?
No worries! The "stop lock" pins prevent ratchet pawl lock up and assures increased tool life

EXTRA SILENT & POWERFUL or EXTRA POWERFUL & SILENT?
The muffler bypass system gives YOU the choice to quickly adapt the tool to YOUR DEMANDS and needs!

Quiet Mode		Quiet Mode									
Icon	mm	mm	Nm	min ⁻¹	dBa	m/sec	l/min	inch	mm	kg	
BP921	70x330x90	308	1/2	7-95	200	≤94,9	≤5,2	127	1/4	10	1,35

MUFFLER BYPASS SYSTEM					
Muffler	MAX Nm	% Nm	dBa	% dBA	
	95 Nm		94.9 dBA		
	67 Nm	-30%	87.9 dBA	-224%	

▶ MINI RATCHET 1/4"



- Soft grip handle
- Hard coated motor plates
- Large lightweight selector knob
- All ball bearing construction and high strength alloy steel gear system
- Supplied with a black protection boot

Quiet Mode		Quiet Mode									
Icon	mm	mm	Nm	min ⁻¹	dBa	m/sec	l/min	inch	mm	kg	
BP919	50x280x100	198	1/4	0-47	235	84	2,5	40	1/4	10	0,59


▶ MINI RATCHET 3/8"



- Balanced lightweight housing
- Soft grip handle
- Hard coated motor plates
- Large lightweight selector knob
- All ball bearing construction and high strength alloy steel gear system
- Supplied with a black protection boot

Quiet Mode		Quiet Mode									
Icon	mm	mm	Nm	min ⁻¹	dBa	m/sec	l/min	inch	mm	kg	
BP920	50x280x100	198	3/8	0-47	235	84	2,5	40	3/8	10	0,59

WHEN ACCESSIBILITY & POWER IS CRUCIAL



The long & strong! 308mm long, 95Nm strong!

All technical specifications are stated at the recommended working pressure of 6.2 bar

THE PRECISE!

ALSO A PERFECTIONIST?
Precise 0,0635 mm CHUCK RUNOUT for precision drilling yielding a high quality job, ALWAYS!

IN A HURRY?
The 0,45 HP motor with 5 vanes provides MAXIMUM DRILLING POWER to get the job done faster

NEED FOR CONTROL?
REVERSIBLE VARIABLE SPEED TRIGGER for increased control of drilling speed

EASY TO HANDLE
Top mounted forward / reverse switch allowing one hand operation for easy usage

CLEVER DESIGN
User friendly design with forefinger support increases the precision in all drilling

COMFORTABLE TO HANDLE
Soft grip handle ensures a great working day

▶ HIGH PRECISION DRILL 13 mm



▶ HIGH PRECISION DRILL 10 mm



- Top mounted forward / reverse switch
- Internal ball bearing construction
- Supplied with integrated support handle and drill container

BP926	229	13	336	450	0-34	80	<2,50	108	1/4	10	1,30

- Top mounted forward / reverse switch
- Internal ball bearing construction

BP925	178	10	336	2.500	0-6,0	80	<2,50	108	1/4	10	1,0

▶ REVERSIBLE DRILL 13 mm



- Composite housing
- Removable and adjustable handle
- Forward / reverse lever ensures quick and easy change of direction
- Air exhaust in the handle for pleasant operation
- Quick chuck
- Rubber grip handle

BP825	220x155x45	450	88	<2,50	105	1/4	10	1,35



All technical specifications are stated at the recommended working pressure of 6.2 bar

▶ BELT SANDER 10 mm



Belts 25 pcs 80 grits - Suitable for BP212



BPN21201



- Adjustable arm
- Including three belts 80, 100 and 120 grits

BP212	65x280x85	10x330	246	16.000	83	<2,50	390	1/4	10	0,80
-------	-----------	--------	-----	--------	----	-------	-----	-----	----	------

▶ BELT SANDER 20 mm



Belts 25 pcs 100 grits - Suitable for BP222



BPN22201



- Adjustable arm
- Including two belts 100 and 120 grits

BP222	65x280x85	20x520	328	16.000	85,5	3,20	390	1/4	10	1,10
-------	-----------	--------	-----	--------	------	------	-----	-----	----	------

▶ ORBITAL SANDER 5 mm



- For central vacuum systems
- Composite housing

BP601	105x210x145	5	11.000	224	152	80	<2,50	255	1/4	10	0,80
-------	-------------	---	--------	-----	-----	----	-------	-----	-----	----	------

▶ ORBITAL SANDER 2,5 mm



- For central vacuum systems
- Composite housing

BP610	105x210x145	2,5	11.000	224	152	80	<2,50	255	1/4	10	0,80
-------	-------------	-----	--------	-----	-----	----	-------	-----	-----	----	------

Pad - Suitable for BP601 and BP610



BP51137



▶ PISTOL GRIP SANDER



- Top mounted speed change switch

BP204	120x570x238	168	3	25.000	85	4,53	170	0,50
-------	-------------	-----	---	--------	----	------	-----	------

Accessories suitable for BP204



Description

BP2044PAD 3" Velcro pad

BP20425180 25 pcs, 180 grit

BP20425220 25 pcs, 220 grit

BP20410320 10 pcs, 320 grit

BP20410800 10 pcs, 800 grit



BP2044PAD



BP20425180



BP20425220



BP20410320



BP20410800

▶ PISTOL GRIP SANDER SET



Including:

- BP204
- 1 x 3" Velcro pad
- 10 x 180 grits, 3" pads
- 10 x 220 grits, 3" pads
- 10 x 320 grits, 3" pads
- 10 x 800 grits, 3" pads



BP204K



108x371x321

All technical specifications are stated at the recommended working pressure of 6.2 bar

▶ REVERSIBLE SCREWDRIVER
1.800 RPM



- Composite motor housing
- Two speed trigger
- External adjustable clutch design
 - Forward: Adjustable torque
 - Reverse: Full torque
- Reversible bar on both sides for easy change of direction

BP826	50x245x170	1/4	373	1-10	1.800	83	<2,50	113	1/4	10	1,20

▶ REVERSIBLE SCREWDRIVER
800 RPM



- Composite motor housing
- Two speed trigger
- External adjustable clutch design
 - Forward: Adjustable torque
 - Reverse: Full torque
- Reversible bar on both sides for easy change of direction

BP827	50x245x170	1/4	373	1-12	800	83	<2,50	113	1/4	10	1,40

WHEN TOTAL CONTROL IS A MUST!



The unique clutch design of BP826 and BP827 ensures a total torque control!

All technical specifications are stated at the recommended working pressure of 6.2 bar

WHEN REAL POWER IS A MUST!



With its speed of 10.000 revolutions per minute the BP823 gets the job done in no time

▶ LOW REVOLUTION GRINDER



- Speed control system
- Hexagonal rubber sleeve
- Safety trigger

Exhaust hose for die grinder

BP117EH



BP117	50x243x172	373	2.500	85	4,53	170	1/4	10	1,0

▶ AIR RIVETER



- Rivet capacity;
3,2 mm
4,0 mm
4,8 mm
6,4 mm

BP125	349x543x397	19	1330	1/4	2,0

▶ DISC GRINDER



- Composite housing
- Safety trigger

BP823	108x285x147	125	559	10.000	83	<2,50	340	1/4	10	1,80

▶ CUT OFF TOOL



- Speed control system
- Rubber sleeve
- Safety trigger
- Swivel connection

BP110	81x190x86	75	373	18.000	98	<2,50	113	1/4	10	0,90

All technical specifications are stated at the recommended working pressure of 6.2 bar

▶ MINI DIE GRINDER



- 3 and 6 mm collet for improved flexibility
- Hexagonal rubber sleeve
- Safety trigger
- Air exhaust control system for pleasant operation
- Swivel connection

BP822	55x200x98	3 & 6	201	25.000	85	4,53	170	1/4	10	0,50

▶ RECIPROCATING SAW




- Composite housing
- Safety trigger mechanism
- Directional exhaust system
- Swivel connection
- Three car body saw blades included

BP824	50x340x90	10.000	85	3,70	160	1/4	10	0,50

Car body saw blades - Suitable for BP824

	mm-teeth
3845-18-10P	90-18
3845-24-10P	90-24
3845-32-10P	90-32



▶ NEEDLE SCALER



- Heavy duty
- Low vibration

BP127	70x370x190	3.700	97	8,70	159	1/4	10	2,60

▶ ANGLE GRINDER



- Hexagonal rubber sleeve
- Safety trigger
- Air exhaust control system
- Swivel connection

BP115	36x145x75	6	201	20.000	79	<2.50	113	1/4	10	0,59

▶ EXTENDED DIE GRINDER



- 3 and 6 mm collet for improved flexibility
- Hexagonal rubber sleeve
- Safety trigger
- Air exhaust control system for pleasant operation
- Swivel connection
- 95 mm long neck for increased accessibility

BP822E	55x243x172	3 & 6	201	25.000	89	4,53	113	1/4	10	0,80

Abbrasive wheels - Suitable for BP822, BP115 and BP822E

	mm	mm		mm	mm		
	BP420M	25	67		BP430M	12	55
	BP421M	14	53		BP431M	13	48
	BP422M	26	46		BP432M	15	44
	BP423M	25	53		BP433M	14	43
	BP424M	19	57		BP434M	13	42

For Bahco's extensive range of rotary burrs suitable for BP822, BP822E and BP115 please see the Bahco catalogue, www.bahco.com

▶ CARTRIDGE APPLICATOR



- Enables fast and efficient application of European standard cartridges

BP215	92x310x175	80	1/4	10	1,0	

All technical specifications are stated at the recommended working pressure of 6.2 bar

THE SLUGGER! AIR HAMMER SET

THE FASTEST

The unique quick chuck makes chisel change a piece of cake



HARD HITTING!

The 76 MM LONG STROKE of the EXTRA HEAVY HARD STEEL PISTON ensures striking power as you have never experienced before

DURABLE & SMART

Built of only the most heavy duty materials, solid HIGH GRADE STEEL BARREL, KEVLAR reinforced flutter disc, INBUILT AIR FILTER. All to ensure MAXIMUM TOOL LIFE



SO SMOOTH...

Even if the power is tremendous, the vibration is nominal. ONLY 1.5m/s² thanks to the dual elastomer cushions that absorb almost all vibration

COMPLETE

Supplied in robust plastic case including FIVE CHISELS for a wide area of applications

EASY HANDLING

Built in four position air regulator and direct multi-port frontal exhaust ensures comfortable usage

BP909K	108x371x321	10	229	2.500	94	1,5	60	1/4	10, 2,1

Accessory chisels - Suitable for BP909K

	Type	Shank	Included in BP909K
BP909TF	Turning, flat	Round 10.2mm	Yes
BP909TWF	Turning, wide flat	Round 10.2mm	Yes
BP909TTP	Turning, tapered punch	Round 10.2mm	Yes
BP909TE	Turning, edge claw	Round 10.2mm	Yes
BP909TH	Turning, hammer	Round 10.2mm	
BP909TSP	Turning, straight punch	Round 10.2mm	Yes
BP909NF	Non - turning, flat	Round 10.2mm	
BP909NE	Non - turning edge claw	Round 10.2mm	

▶ PAINT GUN SET

- High volume at low pressure
- High precision provides high quality painting
- Spare nozzle sets covering five diameters
- No seal component design for much longer operation life
- Precise air cap keeps the outlet less than 10PSI
- One piece aluminum housing



		BAR	Cup size (ml)			°C	kg
BPHVLP01	155x225x200	2-2.8	600	250	1/4	5-40	0,70

Accessories available loose and included with the BPHVLP01

	Description
BPHVLP0110	Nozzle set 1.0 mm
BPHVLP0112	Nozzle set 1.2 mm
BPHVLP0114	Nozzle set 1.4 mm
BPHVLP0117	Nozzle set 1.7 mm
BPHVLP0120	Nozzle set 2.0 mm

▶ BLOW GUN

- Steel nozzle
- Meets O.S.H.A requirements
- Brass inlet



		BAR			kg
BP218	19x200x85	≤ 11	158	1/4	0,15

All technical specifications are stated at the recommended working pressure of 6.2 bar

WHEN FLEXIBILITY IS A MUST!



Thanks to the double collets included in the BP822, it can drive both 3 and 6 mm inserts

▶ FEMALE MULTI-PROFILE COUPLER 1/4"



Suitable male profiles

- ISO6150B
- ARO210
- European (German)
- Italian

- Works with four standard male connector profiles
- Security lock enabling the operator to turn on and off the air flow, providing a safer and more simplified operation
 - The tool cannot be disconnected unless the air flow is turned off
 - Simplified operation - ease the connection of the male profile since the air flow can be cut
- Steel construction with composite coating, making it extremely durable
- Air flow: 1,600 l/min at 6.0 bar
- Maximum pressure: 14 bar
- Plug diameter: 6 mm

BPQC14	30x70x30	10	0,09

▶ PNEUMATIC WINDSCREEN REMOVER



- Robust design
- Pipe away exhaust
- Low vibration, <math><2.5\text{ m/s}^2</math>
- Noise reducing hose

BP233	43x275x75	80,5	<math><2,5</math>	260	1/4	10	1,20

Blades - Suitable for BP233

	Description	
BPBK30	Offset comma shaped blades pair in blister	
BPBG5725	Offset 13mm shaped blades pair in blister	
BPBG9057	Offset 13mm shaped blades pair in blister	
BPBU18	U shaped blades pair in blister	
BPBU24	U shaped blades pair in blister	
BPBU36	U shaped blades pair in blister	
BPBU60	U shaped blades pair in blister	
BPBU90	U shaped blades pair in blister	
BPBG3515	Straight blades pair in blister	
BPBG3525A	Straight blades pair in blister	
BPBG3525B	Straight blades pair in blister	
BPBSC156	Scraper pair in blister	

▶ MAGNETIC HOLDER



- Equipped with extra strong magnets that easily holds a 3/4" impact wrench, four impact sockets and one torque tool
- Painted with special and durable paint to avoid damage of the stored tools

BP500	125x390x135	1,03

▶ SPIRAL HOSES



- Polyurethane hose with fixed male threaded connector at both ends

BPH1010	90x530x90	10-13	10	1/4-1/4	0,86
BPH1310	90x530x90	13-18	10	1/2-1/2	1,0

All technical specifications are stated at the recommended working pressure of 6.2 bar

▶ PNEUMATIC MARKER



- For fast and secure marking
- Low vibration
- Low air consumption

BP799	17x200x17	13.000	78	<2,00	28	1/4	10	0,22

Spare tip - Suitable for BP799



BP79912

▶ AIR FILTER - REGULATOR



- Filters the air to avoid damage caused by dust
- Regulates desired pressure between 1 and 8,5 bar

		Adjustable pressure range (bar)	Maximum service pressure (MPa)	°C		Bowl capacity (ml)		
BP254	80x290x80	1-8,5	1,5	-5/+60	≤ 3.800	200	1/2	0,80

▶ AIR FILTER - REGULATOR - LUBRICATOR



- Filters the air to avoid damages caused by dust
- Regulates desired pressure between 1 and 8,5 bar
- Automatically lubricates the air to ensure correct operation and longer lifetime of the air tools

		Adjustable pressure range (bar)	Maximum service pressure (MPa)	°C		Bowl capacity (ml)		
BP255	115x235x115	1-8,5	1,5	-5/+60	≤ 3.800	200	1/2	1,35

▶ STEEL AIR HOSE REEL



- Corrosion resistant
- Adjustable double guide arm
- Ball bearing swivel
- Strengthened frame
- 110° swivel base
- Positive latching system which automatically locks the hose at desired length for increased functionality and comfort

BPHRS1315	519x614x264	13/20	15	1/2-1/2	24

▶ AIR HOSE REELS



- 180° swivel bracket
- Detachable pin swivel
- Durable corrosion and rough environment resistant polypropylene housing
- Positive latching system which automatically locks the hose at desired length for increased functionality and comfort

BPHR1315	509x539x239	13/16	15	1/2-1/2	9,70
BPHR1020	509x539x239	10/14,5	20	3/8-3/8	9,70

▶ IN LINE MINI LUBRICATOR



- Lubricates the air to ensure correct operation and longer lifetime of the air tools

BPN251	33x60x33	1/4	0,01

All technical specifications are stated at the recommended working pressure of 6.2 bar

THE PERFECT COMPANIONS TO BAHCO AIR TOOLS!

▶ IMPACT SOCKETS AND ACCESSORIES

Always use impact sockets with power tools. For the complete range of Bahco's robust impact sockets from 1/4" to 1 1/2", please see the Bahco catalogue, www.bahco.com

IMPACT SOCKETS AND ACCESSORIES 3/8"

3/8" Impact sockets metric



Part Number	Size (mm)
K7401M-7	7
K7401M-8	8
K7401M-9	9
K7401M-10	10
K7401M-11	11
K7401M-12	12
K7401M-13	13
K7401M-14	14
K7401M-15	15
K7401M-16	16
K7401M-17	17
K7401M-18	18
K7401M-19	19
K7401M-20	20
K7401M-21	21
K7401M-22	22
K7401M-24	24

3/8" Impact adaptor, universal holder



Part Number	Size	Size
K172	1/4"	3/8"

3/8" Impact adaptors, bit holder



Part Number	Size	Size
7407H	1/4"	3/8"
7408H	5/16"	3/8"



7409H	11 mm	3/8"
-------	-------	------

3/8" Clamping springs



Part Number	Size	Size	Size
K560F-2	3/8"	7-12	E5-E14
K560F-3	3/8"	13-19	

3/8" Impact sockets metric deep



Part Number	Size (mm)
K7406M-10	10
K7406M-13	13
K7406M-17	17

IMPACT SOCKETS AND ACCESSORIES 1/2"

1/2" Impact sockets metric

3/8" Impact extensions



Part Number	Length (mm)	Size	Size
K7760C-1	75	3/8"	3/8"
K7760C-2	150	3/8"	3/8"



Part Number	Size (mm)
K7801M-8	8
K7801M-9	9
K7801M-10	10
K7801M-11	11
K7801M-12	12
K7801M-13	13
K7801M-14	14
K7801M-15	15
K7801M-16	16
K7801M-17	17
K7801M-18	18
K7801M-19	19
K7801M-20	20
K7801M-21	21
K7801M-22	22
K7801M-23	23
K7801M-24	24
K7801M-25	25
K7801M-26	26
K7801M-27	27
K7801M-30	30
K7801M-32	32
K7801M-34	34
K7801M-36	36

3/8" Impact ball joint



Part Number	Size	Size
K7767S	3/8"	3/8"

3/8" Impact adaptors



Part Number	Size	Size
K6964C	1/4"	3/8"
K8164C	1/2"	3/8"

1/2" Impact sockets metric



Part Number	Size (mm)
K7801VM-17	17
K7801VM-19	19
K7801VM-22	22
K7801VM-24	24

1/2" Impact socket set metric



	K7801VM/S4		17-24
--	------------	--	-------

1/2" Impact socket sets imperial, 10 pcs



	K7801Z/10		7/16-1
--	-----------	--	--------

1/2" Impact sockets metric deep



K7806M-10	10
K7806M-11	11
K7806M-12	12
K7806M-13	13
K7806M-14	14
K7806M-16	16
K7806M-17	17
K7806M-18	18
K7806M-19	19
K7806M-21	21
K7806M-22	22
K7806M-23	23
K7806M-24	24
K7806M-27	27
K7806M-30	30

1/2" Impact socket sets imperial, 10 pcs



	K7806Z/10		7/16-1
--	-----------	--	--------

1/2" Impact socket set metric deep



	K7806M/S4		17-24
--	-----------	--	-------

1/2" Impact socket sets metric

D/S10	280x160x70	10-19
D/S14	280x160x70	10-27



D/S10



D/S14

1/2" Impact sockets imperial



K7801Z-3/8	3/8
K7801Z-7/16	7/16
K7801Z-1/2	1/2
K7801Z-9/16	9/16
K7801Z-5/8	5/8
K7801Z-11/16	11/16
K7801Z-3/4	3/4
K7801Z-13/16	13/16
K7801Z-7/8	7/8
K7801Z-15/16	15/16
K7801Z-1	1
K7801Z-1.1/16	1.1/16
K7801Z-1.1/8	1.1/8
K7801Z-1.1/4	1.1/4

1/2" Impact socket sets metric deep

DD/S10	280x160x70	10-19
DD/S14	375x215x100	10-27



DD/S10



DD/S14

1/2" Impact sockets imperial deep



K7806Z-3/8	3/8
K7806Z-7/16	7/16
K7806Z-1/2	1/2
K7801Z-9/16	9/16
K7801Z-5/8	5/8
K7801Z-11/16	11/16
K7801Z-3/4	3/4
K7801Z-13/16	13/16
K7801Z-7/8	7/8
K7801Z-15/16	15/16
K7801Z-1	1
K7801Z-1.1/16	1.1/16
K7801Z-1.1/8	1.1/8
K7801Z-1.1/4	1.1/4
K7801Z-1.5/16	1.5/16
K7801Z-1.3/8	1.3/8
K7801Z-1.7/16	1.7/16
K7801Z-1.1/2	1.1/2

1/2" Impact socket set + metric deep

D-DD/S20	375x215x100	10-19



D-DD/S20

1/2" Impact sockets TORX®



K7801TORX-E10	E10
K7801TORX-E12	E12
K7801TORX-E14	E14
K7801TORX-E16	E16
K7801TORX-E18	E18
K7801TORX-E20	E20
K7801TORX-E24	E24

1/2" Impact extensions



	mm	□	○
K8160D-1	75	1/2	1/2
K8160D-2	125	1/2	1/2
K8160D-3	250	1/2	1/2

1/2" Impact ball joint



	□	○
K8167S	1/2	1/2

1/2" Impact adaptors



	□	○
K7764D	3/8	1/2
K8964D	3/4	1/2

1/2" Impact adaptors, bit holder



	○	□
7807H	1/4	1/2
7808H	5/16	1/2
7809H	11.2 mm	1/2

1/2" Clamping springs



	□	○	☆
K560F-4	1/2	10-14	E10-E20
K560F-5	1/2	15-32	E-24

IMPACT SOCKETS AND ACCESSORIES 3/4"

3/4" Impact sockets metric



	○
K8901M-17	17
K8901M-18	18
K8901M-19	19
K8901M-21	21
K8901M-22	22
K8901M-23	23
K8901M-24	24
K8901M-27	27
K8901M-28	28
K8901M-29	29
K8901M-30	30
K8901M-32	32
K8901M-33	33
K8901M-34	34
K8901M-36	36
K8901M-38	38
K8901M-41	41
K8901M-46	46
K8901M-50	50
K8901M-55	55
K8901M-60	60

3/4" Impact sockets imperial



	○
K8901Z-11/16"	11/16
K8901Z-3/4"	3/4
K8901Z-13/16	13/16
K8901Z-7/8	7/8
K8901Z-15/16	15/16
K8901Z-1	1
K8901Z-1.1/16	1.1/16
K8901Z-1.1/8	1.1/8
K8901Z-1.3/16	1.3/16
K8901Z-1.1/4	1.1/4
K8901Z-1.5/16	1.5/16
K8901Z-1.3/8	1.3/8
K8901Z-1.7/16	1.7/16
K8901Z-1.1/2	1.1/2
K8901Z-1.9/16	1.9/16
K8901Z-1.5/8	1.5/8
K8901Z-1.11/16	1.11/16
K8901Z-1.3/4	1.3/4
K8901Z-1.13/16	1.13/16
K8901Z-1.7/8	1.7/8
K8901Z-1.15/16	1.15/16
K8901Z-2	2
K8901Z-2.1/16	2.1/16
K8901Z-2.3/16	2.3/16
K8901Z-2.1/4	2.1/4
K8901Z-2.3/8	2.3/8

3/4" Impact sockets imperial



	○
K8901Z-3/4	3/4
K8901Z-13/16	13/16
K8901Z-7/8	7/8
K8901Z-15/16	15/16
K8901Z-1	1
K8901Z-1.1/16	1.1/16
K8901Z-1.1/8	1.1/8
K8901Z-1.1/4	1.1/4
K8901Z-1.5/16	1.5/16
K8901Z-1.3/8	1.3/8
K8901Z-1.7/16	1.7/16
K8901Z-1.1/2	1.1/2
K8901Z-1.5/8	1.5/8
K8901Z-1.3/4	1.3/4

3/4" Impact sockets metric deep



	○
K8906M-17	17
K8906M-19	19
K8906M-21	21
K8906M-22	22
K8906M-24	24
K8906M-27	27
K8906M-30	30
K8906M-32	32
K8906M-33	33
K8906M-34	34
K8906M-36	36
K8906M-41	41

3/4" Impact sockets imperial deep



	○
K8906Z-3/4	3/4
K8906Z-13/16	13/16
K8906Z-7/8	7/8
K8906Z-15/16	15/16
K8906Z-1	1
K8906Z-1.1/16	1.1/16
K8906Z-1.1/8	1.1/8
K8906Z-1.1/4	1.1/4
K8906Z-1.5/16	1.5/16
K8906Z-1.3/8	1.3/8
K8906Z-1.7/16	1.7/16
K8906Z-1.1/2	1.1/2
K8906Z-1.5/8	1.5/8
K8906Z-1.3/4	1.3/4
K8906Z-2	2

3/4" Impact extensions



	mm	□	○
K8960F-2	175	3/4"	3/4"
K8960F-3	250	3/4"	3/4"

3/4" Impact ball joint



	□	○
K8967S	3/4	3/4

3/4" Impact adaptors



	□	○
K8164F	1/2	3/4
K9564F	1	3/4

3/4" Impact adaptor, bit holder



	○	□
K8909H-5	22 mm	3/4

3/4" Clamping springs



	□	○
K560F-6	3/4	17-46

IMPACT SOCKETS AND ACCESSORIES 1"

1" Impact sockets metric



Part Number	Size
K9501M-22	22
K9501M-24	24
K9501M-27	27
K9501M-30	30
K9501M-32	32
K9501M-33	33
K9501M-34	34
K9501M-36	36
K9501M-38	38
K9501M-41	41
K9501M-42	42
K9501M-46	46
K9501M-50	50
K9501M-55	55
K9501M-60	60
K9501M-65	65
K9501M-70	70
K9501M-75	75
K9501M-80	80

1" Impact sockets imperial



Part Number	Size
K9501Z-1	1
K9501Z-1.1/16	1.1/16
K9501Z-1.1/8	1.1/8
K9501Z-1.3/16	1.3/16
K9501Z-1.1/4	1.1/4
K9501Z-1.5/16	1.5/16
K9501Z-1.3/8	1.3/8
K9501Z-1.7/16	1.7/16
K9501Z-1.1/2	1.1/2
K9501Z-1.9/16	1.9/16
K9501Z-1.5/8	1.5/8
K9501Z-1.11/16	1.11/16
K9501Z-1.3/4	1.3/4
K9501Z-1.13/16	1.13/16
K9501Z-1.7/8	1.7/8
K9501Z-1.15/16	1.15/16
K9501Z-2	2
K9501Z-2.1/8	2.1/8
K9501Z-2.3/16	2.3/16
K9501Z-2.1/4	2.1/4
K9501Z-2.5/16	2.5/16
K9501Z-2.9/16	2.9/16
K9501Z-2.3/4	2.3/4

1" Impact sockets metric deep



Part Number	Size
K9506M-22	22
K9506M-24	24
K9506M-27	27
K9506M-30	30
K9506M-32	32
K9506M-33	33
K9506M-34	34
K9506M-36	36
K9506M-38	38
K9506M-41	41
K9506M-46	46
K9506M-50	50
K9506M-55	55
K9506M-60	60

1" Impact sockets imperial deep



Part Number	Size
K9506Z-1	1
K9506Z-1.1/16	1.1/16
K9506Z-1.3/16	1.3/16
K9506Z-1.1/4	1.1/4
K9506Z-1.7/16	1.7/16
K9506Z-1.1/2	1.1/2
K9506Z-1.5/8	1.5/8
K9506Z-1.13/16	1.13/16
K9506Z-1.7/8	1.7/8

1" Impact extensions



Part Number	Length (mm)	Size	Quantity
K9560G-1	125	1	1
K9560G-2	175	1	1
K9560G-3	325	1	1

1" Impact ball joint



Part Number	Size	Quantity
K9567S	1	1

1" Impact adaptor



Part Number	Size	Quantity
K8964G	3/4	1

1" Impact adaptor, bit holder



Part Number	Size	Quantity
K9509H5	22 mm	1

1" Screwdriver bits for hexagon metric socket head screws




Part Number	Size
K8909ML-12	12
K8909ML-14	14
K8909ML-17	17
K9509ML-19	19
K9509ML-22	22
K9509ML-24	24

1" Clamping springs



Part Number	Size	Quantity
K560F-7	1	19-70
K560F-8	1 & 1.1/2	75-80 & 46-90

Impact sockets Scania



Part Number	Description	Quantity
BHVIS0895	SCANIA F WHEEL-8F X 95MM-3/4	3/4
BHVIS08100	SCANIA R WHEEL-8F X 100MM-3/4	3/4

- Special impact sockets to use for Scania truck wheels
- Output:
- HVIS0895: 8 flutes x 95 mm for front wheels
- HVIS08100: 8 flutes x 100 mm for rear wheels

Impact socket Volvo



Part Number	Description	Quantity
BHVIS08115	VOLVO WHEEL-8F X 115MM-3/4	3/4

- Special impact sockets to use for Volvo truck wheels
- Output: 8 flutes x 115 mm

Impact sockets BPW



	mm	
BHVIS111BPW12	111	1
BHVIS120BPW16	120	1
BHVIS109BPW12	109	1

- Special impact sockets to use on the axles made by one of the most well-known axle makers, BPW
- Output: Special shape with different sizes per axle type

Axle nut remover BPW



	mm	
BHVIS80BPW12	80	3/4"


1" Torsion bars



	MAX Nm		kg
BWTB0132450	450	32	1,54
BWTB0132600	600	32	1,58
BWTB0133600	600	33	1,61

- Special torsion bars for controlling the torque applied to wheels and other parts

Wheel socket sets



	mm		kg
BWSS12P3	45x150x130	17, 19, 21	0,80
BWSS12P5	50x240x175	17, 19, 21, 22, 24	1,47

- Plastic protection on socket walls to ensure protection of the rims
- Plastic protection inside the socket to ensure protection of wheel nuts

Torsion bar set, 10 pcs



		kg
BWTB12P10	1/2	3,50

Color	MAX Nm
Red	75
Yellow	90
Green	110
Pink	120
Light blue	135
Navy blue	150
White	160
Black	190
Gray	205
Orange	240

- Torsion bars of special steel that limits the torque! When the maximum torque is reached the bar twists automatically
- (Always use a torque wrench after usage of torsion bars)

Safety wear

Always use appropriate safety equipment when operating power tools; safety glasses, ear protectors, gloves and protective clothing



	Description
3870-SAFETYGLASSES	Safety glasses



	Description
5428	Ear protectors



	Description	Size
GL008-8	PU Gloves	8
GL008-10	PU Gloves	10

- PU gloves with knuckle protector, reflective piping and soft cotton brow wipe on the thumb
- The orange material is a Spandex for comfort and fit. Elastic cuff with Velcro fastening for secure fitting



	Description	Size
GL010-8	Textured PU Gloves	8
GL010-10	Textured PU Gloves	10

- Textured PU gloves with additional padded cells to give protection whilst using power tools
- They also have the knuckle protector, reflective piping, cotton brow wipe, Spandex back and Elastic cuff



AUT-0846-INT



www.bahco.com

SNA Europe

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Hand Tools](#) category:

Click to view products by [Bahco](#) manufacturer:

Other Similar products are found below :

[568681-1](#) [576785-2](#) [576786-2](#) [58061-1](#) [58176-1](#) [58177-1](#) [58177-2](#) [58284-1](#) [59085](#) [0031](#) [59737-5](#) [015-0339-000](#) [015-8755-001](#) [600-146-06](#)
[M15570-25](#) [62200-5709](#) [6-304052-1](#) [63443-1002](#) [63443-3513](#) [63443-4025](#) [63443-7114](#) [6-354778-5](#) [6-354779-2](#) [63600-2995](#) [63810-0105](#)
[M8196914-08](#) [M819698-07](#) [662508-1](#) [662908-1](#) [679837-1](#) [679994-2](#) [68764-0001](#) [69001-0105](#) [69002-5525](#) [690124-7](#) [690191-1](#) [690191-4](#) [690672-](#)
[2](#) [690696-1](#) [691409-4](#) [691667-1](#) [692006-2](#) [692655-7](#) [692776-1](#) [692776-4](#) [693077-3](#) [693077-4](#) [693597-1](#) [ESR-17x17](#) [ET-LY10](#)