



Dissolved Oxygen Meter/Datalogger

Records data on an SD card in Excel® format

For easy transfer to a PC for analysis

Features:

- Dual backlit display of Oxygen Concentration and Temperature
- Measures dissolved oxygen from 0 to 20.0mg/L and 0 to 100.0% oxygen plus temperature from 32 to 122°F (0 to 50°C)
- Automatic Temperature Compensation from 0 to 50°C via temperature probe sensor built into polarographic type oxygen probe
- Offset adjustment used for zero function to make relative measurements
- Stores 99 readings manually and 20M readings via 2G SD card
- · Records readings with real date and time stamp
- User programmable sampling rate: 1 second to 8hrs:59min:59sec
- Min/Max and Data Hold functions
- · Auto power off with disable function
- · Built-in PC interface
- Complete with 6 x AA batteries, SD card, probe, two spare replacement membranes, electrolyte, and hard carrying case





Specifications	Dissolved Oxygen	Oxygen	Temperature
Range	0 to 20.0 mg/L	0 to 100.0%	32 to 122°F
			(0 to 50°C)
Accuracy	±0.4 mg/L	±0.7%	±0.8°C/1.5°F
Probe Compensation			
& Adjustmen	Salt: 0 to 50%	Altitude: 0 to 8910m	Temp: 0 to 50°C
Dimensions/Weight	7.2 x 2.9 x 1.9" (182 x 73 x 47.5mm) / 25.6oz(725g) (meter only) Probe: 28mm(1.1")D x 190mm(7.5")L		

Ordering Information:



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160