



ALL DIMENSIONS ARE APPROXIMATE, FOR REFERENCE ONLY.

NOTES:

- (1). TERMINAL: HIGH CONDUCTIVITY COPPER.
- (2). FINISH: ELECTRO TIN PLATE.
- (3). INSULATOR: NYLON, TRANSLUCENT.
- (4). CERTIFIED FOR 600V, 1000V IN SIGNS & FIXTURES
- (5). RATED FOR 105° MAX. TEMPERATURE

FOR CUSTUM CONNECTORS:

PLATING:  
 NP-NICKLE PLATED, SP-SILVER PLATED, LP-LEAD PLATED, PF-PLAIN FINISH  
 BENT TONGUES:  
 UF-45 DEGREE and UB-90 DEGREES  
 BOLT HOLES :  
 02-#8, 03-#10, 04-1/4", 05-5/16", 06-3/8", 08-1/2", 10-5/8"  
 BOLT HOLE SPACING:  
 08-1/2", 09-9/16", 10-5/8", 11-11/16" etc up to 28-1-3/4"  
 STACKING:  
 T-TOP and B-BOTTOM  
 INSPECTION HOLE:  
 PH-PEEP HOLE or BE-BLIND END  
 TONGUE WIDTH  
 NT - NARROW TONGUE

<b>GENERAL NOTES</b>		<b>Thomas &amp; Betts</b> <small>www.tnb.com</small>			
1. ALL DIMENSIONS ARE FOR REFERENCE ONLY. 2. DIMENSIONS IN BRACKETS [ ] ARE IN METRIC UNITS.					
<b>REVISIONS</b>		<b>ORIGINAL PROJECT NO / ( ERN NO )</b>		<b>SHEET NO:</b>	
1. SEE ERN (2012575 ) FOR APPROVAL SIGNATURES & RELEASE DATE. 03/16/11 PROJECT NO: CD55874		<b>CD55874 / ( 2010390 )</b>		<b>1 OF 3</b>	
		<b>REV. NO:</b>		<b>DRAWING NO:</b>	
		<b>1</b>		<b>WSD-000451</b>	

Cat No.	Bolt	A	B	C	D	E	TBM6S or 25000 Tool	Hydraulic 13642M
541041	#10	1.49	.50	.39	.08	.34	11821-CK	21707M-CK
541051	1/4	1.58	.53	.44	.07	.42	11822-CK	21708M-CK
541061	1/4	1.80	.60	.55	.09	.51	11823-CK	21709M-CK
541081	1/4	2.06	.65	.68	.11	.58	11824-CK	21710M-CK
541091	3/8	2.37	.93	.75	.13	.62	11825-CK	21711M-CK
541101	3/8	2.43	.93	.83	.13	.67	11826-CK	21712M-CK
541111	3/8	2.55	.93	.92	.13	.76	11827-CK	21713M-CK
541121	3/8	2.76	.93	1.03	.14	.78	11828-CK	21714M-CK
541131	1/2	3.20	1.25	1.13	.14	.86	11829-CK	21715M-CK

**Thomas & Betts**  
www.tnb.com

DESCRIPTION: **Color-Keyed** INSULATED CONNECTORS,  
WIRE SIZES #8-250 MCM - COLOR CODE

SHEET NO:

2 OF 3

REV. NO:

-

DRAWING NO:

**WSD-000451**

Cat No.	Bolt	A	B	C	D	E	G	TBM6S or 25000 Tool	Hydraulic 13642M
542041	#10	2.20	1.18	.42	.08	.34	.625	11821-CK	21707M-CK
542051	1/4	2.32	1.28	.44	.08	.42	.625	11822-CK	21708M-CK
542061	1/4	2.40	1.28	.52	.10	.51	.625	11823-CK	21709M-CK
542081	1/4	2.69	1.28	.68	.11	.58	.625	11824-CK	21710M-CK
542091	3/8	3.36	1.93	.75	.13	.62	1.00	11825-CK	21711M-CK
542101	3/8	3.43	1.93	.83	.13	.67	1.00	11826-CK	21712M-CK
542111	3/8	3.46	1.81	.94	.14	.76	1.00	11827-CK	21713M-CK
542121	3/8	3.75	1.93	1.03	.14	.78	1.00	11828-CK	21714M-CK
542131	1/2	3.87	1.93	1.13	.14	.86	1.00	11829-CK	21715M-CK

SAME AS SHEET ONE EXCEPT TWO HOLES

**Thomas & Betts**  
www.tnb.com

DESCRIPTION: **Color-Keyed** INSULATED CONNECTORS,  
WIRE SIZES #8-250 MCM - COLOR CODED

SHEET NO:

3 OF 3

REV. NO:

DRAWING NO:

**WSD-000451**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [ABB manufacturer:](#)*

Other Similar products are found below :

[TY27MX](#) [TV10-516R](#) [RF727](#) [2CMA100178R1000](#) [ACS150-01E-09A8-2](#) [KS70-1104](#) [A75-30-11-230V-50HZ](#) [10-100](#) [5SDD](#) [92Z0401](#)  
[ESV14-BS](#) [EZS-21-250](#) [F204AC-40/0.1](#) [F362-25/0.03](#) [A40-30-10-84](#) [AF26-30-00-14](#) [AF30-30-00-13](#) [AF460-30-11-68](#) [AF50-30-11-70](#)  
[1455](#) [B14-250](#) [EF45-30](#) [ERG297](#) [HSC2-20](#) [1SAM201904R1001](#) [1SAM350000R1003](#) [1SAZ711201R1045](#) [1SAZ721201R1009](#)  
[1SAZ721201R1014](#) [1SAZ721201R1025](#) [1SAZ721201R1045](#) [1SBL367001R1300](#) [1SDA057197R1](#) [1SFA611100R1104](#) [1SFA611101R1002](#)  
[1SFA611130R1103](#) [1SFA611133R1106](#) [1SFA611143R1101](#) [1SFA611202R1108](#) [1SFA611203R1108](#) [1SFA611210R1101](#)  
[1SFA611215R1001](#) [1SFA611216R1108](#) [1SFA611281R1002](#) [1SFA611285R1002](#) [1SFA611702R6006](#) [1SFA616162R1025](#)  
[1SFA896106R1100](#) [1SVR730020R0200](#) [IPC4111](#) [OHB125J12](#)