

## SILVYN® SI

SILVYN® SI - grey soft PVC conduit



Low weight



Flame-retardant

### Benefits

Protection against dust  
Protection against humidity  
Low abrasion protection

### Application range

Easy cable protection  
Additional insulation  
Bundling and guiding of cables and wires

### Product features

Flexible  
Soft

### Product Make-up

Soft-PVC conduit

**SILVYN® SI****Technical Data**

Classification ETIM 5:	ETIM 5.0 Class-ID: EC001177 ETIM 5.0 Class-Description: Protective plastic hose
Classification ETIM 6:	ETIM 6.0 Class-ID: EC001177 ETIM 6.0 Class-Description: Protective plastic hose
Note:	Flame-retardant and self-extinguishing Dielectric strength: 25 kV/mm Tear-resistance: 23 N/mm <sup>2</sup> Shore A hardness: 75 °C to 90 °C
Colour delivered:	Silver grey (RAL 7001)
Material:	Soft PVC
Temperature range:	-5°C to +80°C

**Note**

Photographs and graphics are not to scale and do not represent detailed images of the respective products.  
Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	ID x OD mm	Suitable for SILVYN® SSV-M/SSVZ-M	Suitable for SILVYN® SSV/SSVZ
SILVYN® SI			
61713210	7.0 x 9.0	12/1 / -	-
61713240	9.0 x 12.0	12/2 / -	-
61713270	11.0 x 14.0	16/1 / -	-
61713300	13.0 x 16.0	16/2 / -	-
61713330	14.0 x 18.0	20/1	-
61713360	18.0 x 22.0	20/3	13,5/1
61713390	23.0 x 28.0	25	21
61713420	32.0 x 38.0	32 / 32/2	29/2

Last Update (09.04.2018)

©2018 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for* [Non-Heat Shrink Tubing and Sleeves](#) *category:*

*Click to view products by* [Lapp Kabel](#) *manufacturer:*

Other Similar products are found below :

[CTA-0053](#) [8429-9](#) [8445-7.5](#) [8450](#) [120-116-1-1-09BE](#) [120-116-1-1-09BF](#) [120-116-1-1-09BP](#) [120-116-1-1-12BE](#) [120-116-1-1-12BP](#) [120-123-06](#)  
[120-123-10](#) [120-125-12BL](#) [120-125-12R](#) [120-125-20R](#) [120-126-09](#) [120-126-09BL](#) [120-126-12](#) [120-126-12BL](#) [120-126-52](#) [120-126-52BL](#) [120-](#)  
[104-12](#) [120-105-1-1-06BE](#) [120-105-1-1-06CE](#) [120-116-1-1-06BP](#) [120-116-1-1-10BP](#) [120-116-1-1-12BF](#) [120-123-12](#) [120-125-09](#) [120-125-12](#) [120-](#)  
[125-12Y](#) [120-125-52BL](#) [120-S002-12](#) [HC1B-7008-0375-0](#) [120-S001-09](#) [120-S002-09](#) [121-101-1-1-56BFC](#) [121-101-1-1-64BFC](#) [RAY-90-3.0\(100\)](#)  
[20675-2](#) [8S42-100FR-CS8184](#) [SAS-115-1-1048-1X](#) [SAS-160-1-1048-1X](#) [25T-GB](#) [RAY-103-10.0\(100\)](#) [RAY-103-4.0\(100\)](#) [4627-S](#) [3-1991136-0](#)  
[561-SL1000NYGY](#) [561-SL1000PP](#) [561-SL250FRPP](#)