

ULINKpro 5Volt Adapter

The 5Volt (5V) Adapter enables ULINKpro to connect to 5V-only target devices.



ULINKpro 5V Adapter.

Features

- Expands the I/O Voltage range to 1.5V - 5.5V to accommodate 5V-only devices
- Supports JTAG and SW clock speeds up to 50MHz
- Provides full speed data trace capture (SWV)
- Supports instruction trace capture up to 400 Mbps using 4-pin ETM
- Target [Connectors](#)
 - 10-pin Cortex debug (0.05 inch connector)
 - 20-pin Cortex debug + ETM Trace (0.05 inch connector)

The 5V Adapter replaces ULINKpro's standard 20-pin ribbon cable, and connects to either the 10-pin (Cortex Debug) or 20-pin (Cortex Debug + ETM) connectors on Keil evaluation boards.

Note

- The 5V Adapter is not included as standard with ULINKpro. It must be purchased separately.
- The 5V Adapter is only required when working with 5V only devices.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Keil manufacturer](#):

Other Similar products are found below :

[RL-ARM](#) [MDK-ARM](#) [CA51](#) [MCBSTM32F200U](#) [MCB1760](#) [MCB11U10UME](#) [MCB1760U](#) [PB-HEAVY-D15/30-BL](#) [PB-HEAVY-D15/30-YL](#) [PB-HEAVY-D15/50-YL](#) [PB-HOME-1/15](#) [MDK-ARM-B](#) [PB-HEAVY-D15/40-BK](#) [PB-HEAVY-D15/40-BL](#) [PB-HEAVY-D15/40-YL](#) [PB-HEAVY-D15/50-BK](#) [PB-HEAVY-D25/30-BK](#) [PB-HEAVY-D25/40-BL](#) [PB-HEAVY-D25/50-BL](#) [MCBSTM32](#) [MCB2929UME](#) [MCB2470](#) [PB-HEAVY-D15/50-BL](#) [PB-HEAVY-D25/40-BK](#) [PB-HEAVY-D25/40-YL](#) [PB-HEAVY-D15/30-BK](#) [PB-HEAVY-D25/50-YL](#) [PB-HOME-1/20](#) [PB-HEAVY-D25/25-BK](#) [PB-HOME-1/10](#) [ULINKPRO D](#) [ULINKPLUS](#) [ULINKPRO](#) [MDK-PLUS-T-LC](#) [MDKPR-KD-40000](#)