



Product Description:

Application	For communication and signal control systems.
Reference Standard	BT Standards and Customer Requirements
Multi-construction	1

Cable Construction:

Conductor	Bare Copper
Construction	0.61
Standard Dia.(mm)	0.61
Insulation Layer	Gas Injected Foam PE
Min. Thickness	1.095
Insulation Dia.(+/-0.3mm)	2.8
Bond AL-Foil Shield	Al/PET/Adhesive
Construction (μ)	9/12/25
Coverage(%)	≧115%
Braiding (mm)	Tinned Copper
Construction	T0.12 × 16 × 7
Braid Coverage(%)	>93%
Jacket	LSZH
Min. Thickness(mm)	≧0.55
Dia.(±0.1mm)	4.5
Insulation Colour	Natural
Outer Jacket Colour	Light White
Packaging	500M/Wooden Drum


Electrical Characteristics:

Max.Conductor DC Resistance at 20°C (Ω/Km)	<6.1
Min.Insulation DC Resistance at 20°C (MΩ*KM)	20,000
Rated Temperature(°C)	-20 to +70
Rated Voltage(V)	30
Velocity ratio (%)	82
Impedance(Ω)	75 ±3

Attenuation at 20°C (- dB/100m) (+/-8%)

1MHz	1.2
4MHz	2.5
17MHz	4.95
69MHz	9.15
78MHz	9.65

Design:



Part Number Table

Description	Part Number
Cable, Coaxial, 500m, White, LSZH	PP000637

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[0301CV100W](#) [04JSBLACK](#) [06JSBLACK](#) [08450046010](#) [08450056010](#) [08450066010](#)
[08450166010](#) [08450236010](#) [08450256010](#) [08JSBLACK](#) [10026B](#) [10026BK](#) [10026G](#)
[10026R](#) [10026TB](#) [10026TBK](#) [10026TG](#) [10026TR](#) [10026TW](#) [10026W](#) [10030B](#)
[10030BK](#) [10030G](#) [10030O](#) [10030R](#)