Cable Multicore



pro-**Power**

RoHS Compliant

Product Description:

Part Number	PP000632	PP000633	PP000634	PP000635	PP000636	
Application	For Inte	For Internal or external wiring - Hi Impact Resistant cable.				
Multi-construction	2 Cores	3 Cores	3 Cores	5 Cores	5 Cores	
Construction	Bare Copper					
	2 Cores	3 Cores	3 Cores	5 Cores	5 Cores	
Construction	1.38	1.38	1.78	1.38	1.78	
Stranded Dia.(+/-0.08mm)	1.38	1.38	1.78	1.38	1.78	
Insulation		FR-PVC				
Thickness	0.6	0.6	0.75	0.6	0.75	
Insulation Dia.(+/-0.1mm)	2.63	2.63	3.32	2.63	3.32	
Insulation Colour	Blue & Brown	Green / Yellow, Brown, Blue	Brown, Blue, Green / Yellow	Brown, Blue, Black, Grey, Green / Yellow	Blue, Brown, Grey, Black, Green / Yellow	
Filling		Chalk				
Inner Jacket		PVC				
Thickness (mm)	1	1	1	1	1.1	
Dia.(+/-0.15mm)	6.95	7.35	8.9	8.8	10.7	
Outer Jacket		PVC				
Thickness (mm)	0.8	0.8	1	0.8	1.1	
Dia.(+/-0.15mm)	8.65	9.05	11.1	10.5	12.9	
Marking	2 × 1.5mm ² PVC/PVC to BS 6500 [Meter Mark]	3 × 1.5mm ² PVC/PVC to BS 6500 [Meter Mark]	3 × 2.5mm ² PVC/PVC to BS 6500 [Meter Mark]	5 × 1.5mm ² PVC/PVC to BS 6500 [Meter Mark]	5 × 2.5mm ² PVC/PVC to BS 6500 [Meter Mark]	
Packaging		100m/Reel				

Electrical Characteristics:

Max.Conductor DC Resistance at 20°C (Ω/Km)	<12.5	<12.5	<7.5	<12.5	<7.5
Rated Temperature (°C)	-20 to +80				
Rated Voltage (V)	300/500				
Min. Insulation DC Resistance at 20° C (M Ω × KM)	>500				


www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



Cable Multicore

pro-**Power**

Design:



Part Number Table

Description	Part Number	
Multicore, 2 Core, 1.5mm ² , 100m, 500V	PP000632	
Multicore, 3 Core, 1.5mm ² , 100m, 500V	PP000633	
Multicore, 3 Core, 2.5mm ² , 100m, 500V	PP000634	
Multicore, 5 Core, 1.5mm ² , 100m, 500V	PP000635	
Multicore, 5 Core, 2.5mm ² , 100m, 500V	PP000636	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



X-ON Electronics

Authorized Distributor

Click to view similar products for Pro Power manufacturer.

Other Similar products are found below :

 0301CV100W
 04JSBLACK
 06JSBLACK
 08450046010
 08450056010
 08450066010

 08450166010
 08450236010
 08450256010
 08JSBLACK
 10026B
 10026BK
 10026G

 10026R
 10026TB
 10026TBK
 10026TG
 10026TR
 10026TW
 10030B

 10030BK
 10030G
 10030R
 10030R
 10030B
 10030B