

H1Z2Z2-K

Cross-linked solar cables - type H1Z2Z2-K, certified according to EN 50618

H1Z2Z2-K - cross-linked solar cable according to EN 50618 for durable, weather-resistant use in photovoltaik systems

Info

CPR: Article number choice under www.lappkabel.com/cpr

H1Z2Z2-K (type according to EN 50618)

Substitutes previous ÖLFLEX® SOLAR XLR-R



UV-resistant



Temperature-resistant



Halogen-free



Solar Energy



Suitable for outdoor use



Cold-resistant

Benefits

Reduction of flame propagation and of toxic combustion gases in the event of fire

Robust against mechanical impacts

For outdoor applications

H1Z2Z2-K

Application range

For use in photovoltaic-systems with rated voltage 1500 V DC

For the cabling between the solar modules and as extension cable between the module strings and the DC/AC inverter

Flexible or building-integrated PV systems

Product features

Flame retardant acc. to IEC 60332-1-2

Weather/UV-resistant acc. to EN 50618, appendix E

Ozone-resistant according to EN 50396

Good notch and abrasion resistance

Halogen-free according to IEC 60754-1

(amount of halogen acid gas)

Corrosiveness of combustion gases according to IEC 60754-2 (degree of acidity)

Norm references / Approvals

H1Z2Z2-K (type according to EN 50618)

Items with other cross-sections on request

Product Make-up

Fine-wire, tinned-copper conductor

Coreinsulation made of cross-linked copolymer

Colour of core insulation: white

Outer sheath made of cross-linked copolymer

Outer sheath colour: black, red or blue

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class-Description: Flexible cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC001578 ETIM 6.0 Class-Description: Flexible cable
Conductor stranding:	Fine wire according to VDE 0295, class 5/IEC 60228 class 5
Minimum bending radius:	Fixed installation: 4 x outer diameter
Nominal voltage:	AC U ₀ /U : 1,0/1,0 kV DC U ₀ /U : 1,5/1,5 kV Max. permissible operating voltage: DC 1,8 kV
Test voltage:	AC 6500 V
Current rating:	Im compliance with EN 50618, Table A.3
Temperature range:	-40°C to +120°C max. conductor temperature based on EN 60216-1 Ambient temperature range according to EN 50618: -40°C to +90°C

H1Z2Z2-K

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: Coil 100 m; Drum (500; 1000) m

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Conductor cross-section (mm ²)	Outer diameter [mm]	Copper index (kg/km)
1023552	4	5.8	38.4
1023553	6	6.3	57.6
1023554	10	7.4	96
1023555	16	8.1	153.6
1023590	25	10.3	240
1023591	35	11.8	336
Core insulation: white / Outer sheath: red			
1023572	4	5.8	38.4
1023573	6	6.3	57.6
1023574	10	7.4	96
1023575	16	8.1	153.6
Core insulation: white / Outer sheath: blue			
1023582	4	5.8	38.4
1023583	6	6.3	57.6
1023584	10	7.4	96
1023585	16	8.1	153.6

Last Update (03.08.2018)
 ©2018 Lapp Group - Technical changes reserved
 Product Management www.lappkabel.de
 You can find the current technical data in the corresponding data sheet.
 PN 0456 / 02_03_16

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Specialised Cables category](#):

Click to view products by [Lapp Kabel manufacturer](#):

Other Similar products are found below :

[GP-IE515546DS-002](#) [96CB-L2020PIB2](#) [1200740161](#) [R7ACAB003S](#) [R88ACAKA0015SRE](#) [R88ACAWL005SDE](#) [R88ACRGB010C](#)
[R88ACRGD0R3C](#) [R88ACRGD0R3CBS](#) [R88ACRKA020CRE](#) [1300660201](#) [1971465-2](#) [22733-8](#) [2R7004A20F060](#) [SSL009PC2DC012N](#)
[FC2A-KC6C](#) [FZVS415M](#) [CCSFCBF2](#) [R7ACAB005S](#) [R88ACAGD003SRE](#) [R88ACAGE005BRE](#) [R88ACAKE003SRE](#) [R88ACAKE005SRE](#)
[R88ACAKE010SRE](#) [R88ACRKM010SRE](#) [R88AFIK222RE](#) [XS2WM12PUR4SA10M](#) [XS2WM12PVC4SA10M](#) [05AU05](#) [UCABLE](#)
[10114734-2010LF](#) [R88ACRKC015NRE](#) [XW2Z010H3](#) [XW2Z010H1](#) [5-1589827-8](#) [861084-1](#) [XW2Z200JB24](#) [CR4000A76M020](#)
[1300140039](#) [CR4000A76M005](#) [CR4006A76M005](#) [10077488-N0550FDLF](#) [XW2ZRY150C](#) [I4JPBJLUXX100](#) [I4JPBJLUXX50](#) [CM06W](#)
[CM08](#) [POE004](#) [0243 009 05](#) [0243 009 20](#)