


Features

- * The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- * For surface mounted applications
- * Metal silicon junction, majority carrier conduction
- * Low power loss, high efficiency
- * Built-in strain relief, ideal for automated placement
- * High forward surge current capability
- * High temperature soldering guaranteed:
260°C /10 seconds at terminals



Package Outline Dimensions in inches (millimeters)

SMA:



Mechanical Data

- * Case: JEDEC DO-214AC molded plastic body
- * Terminals: leads solderable per MIL-STD-750, Method 2026
- * Polarity: Color band denotes cathode end
- * Mounting Position: Any

Maximum Ratings and Electrical Characteristics

Rating at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Type Number	Symbols	SS 12	SS 13	SS 14	SS 15	SS 16	SS 18	SS 110	SS 115	SS 120	Unit	
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	20	30	40	50	60	80	100	150	200	V	
Maximum RMS Voltage	V_{RMS}	14	21	28	35	42	56	70	105	140	V	
Maximum D.C Blocking Voltage	V_{DC}	20	30	40	50	60	80	100	150	200	V	
Maximum Average Forward Rectified Current	$I_{F(AV)}$	1.0									A	
Peak Forward Surge Current, 8.3ms single half sine-wave	I_{FSM}	30									A	
Maximum Instantaneous Forward Voltage at 1.0A(Note1)	V_F	0.50			0.75		0.80		0.95		V	
Maximum Reverse Current @ $T_J=25^\circ C$	I_R	0.2					0.1					mA
@ Rated VR @ $T_J=100^\circ C$		6			5		-					
@ $T_J=125^\circ C$		-					2					
Voltage Rate of Change (Rated VR)	dV/dt	10000									V/ μs	
Typical Thermal Resistance	$R_{\theta JL}$ $R_{\theta JA}$	28 88										$^\circ C/W$
Operating Junction Temperature Range	T_J	-55 to +125				-55 to +150						$^\circ C$
Storage Temperature Range	T_{STG}	-55 to +150									$^\circ C$	

Note: 1、 Pulse test: PW=300 μs , 1% duty cycle

Ratings and Characteristic Curves

FIG.1 FORWARD CURRENT DERATING CURVE




FIG. 2 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 TYPICAL FORWARD CHARACTERISTICS




FIG. 4 TYPICAL REVERSE CHARACTERISTICS




FIG. 5 TYPICAL JUNCTION CAPACITANCE





FIG. 6 TYPICAL TRANSIENT THERMAL IMPEDANCE





SS12 THRU SS120

1.0 Amp. Surface Mount Schottky Barrier Rectifiers

Ordering Information

Part No.	Package	Packing
SS12~SS120	SMA	5K/Reel
SS12~SS120	SMA	6K/Reel
SS12~SS120	SMA	7.5K/Reel

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Schottky Diodes & Rectifiers](#) category:

Click to view products by [JGD SEMICONDUCTORS](#) manufacturer:

Other Similar products are found below :

[CUS06\(Te85L,Q,M\)](#) [MA4E2508M-1112](#) [D1FH3-5063](#) [MBR0530L-TP](#) [MBR10100CT-BP](#) [MBR30H100MFST1G](#) [MMBD301M3T5G](#)
[PMAD1103-LF](#) [PMAD1108-LF](#) [RB160M-50TR](#) [RB520S-30](#) [RB551V-30](#) [D83C](#) [DD350N18K](#) [DZ435N40K](#) [DZ600N16K](#)
[BAS16E6433HTMA1](#) [BAS 3010S-02LRH E6327](#) [BAT 15-099R E6327](#) [BAT 54-02LRH E6327](#) [NRVBAF360T3G](#) [NRVTS10100MFST1G](#)
[NRVTS12100EMFST1G](#) [NSR05F40QNXT5G](#) [NSVR05F40NXT5G](#) [JANS1N6640](#) [SB07-03C-TB-H](#) [SB1003M3-TL-W](#) [SBAT54CWT1G](#)
[SK32A-LTP](#) [SK33A-TP](#) [SK34A-TP](#) [SK34B-TP](#) [SMD1200PL-TP](#) [ACDBN160-HF](#) [SS3003CH-TL-E](#) [STPS3045CPIRG](#) [STPS30S45CW](#)
[PDS3100Q-7](#) [GA01SHT18](#) [CRS10I30A\(Te85L,QM\)](#) [CRS10I30B\(Te85L,QM\)](#) [MBR1240MFST1G](#) [MBR20100CT-BP](#) [MBRB30H30CT-1G](#)
[BAS28E6433HTMA1](#) [BAS 70-02L E6327](#) [BYS11-90-E3TR3](#) [JANTX1N5712-1](#) [VS-STPS40L45CW-N3](#)