

TWN3 MIFARE

13.56MHz Contactless Reader/Writer





The TWN3 MIFARE transponder reader is designed for easy integration into various applications.

The device supports either USB or RS232 communication just in dependence on the connection cable and is available as ready-to-connect desktop reader in a slim line black or white housing or as a OEM board (PCB) without housing for direct integration into embedded applications.

Readers can be programmed with a script language for autonomous execution of even complex commands like login procedures, increment/decrement functions and many more.

Technical Data	
Housing	Material ABS UL94-V0, colour black or white
Frequency	13.56 MHz
Dimensions	Desktop Reader: 88mm x 56mm x 18mm / 3.5inch x 2.2inch x 0.7inch OEM Board: 76mm x 49mm x 14mm / 3.0inch x 1.9inch x 0.6inch
Power Supply	5V ± 10% via communication cable (USB); serial version requires external power supply
Supply Current	55mA typ. (USB, normal operation); 120mA peak
Temperature Range	Storage: -45°C up to +85°C (-49°F up to 185°F) Operating: -25°C up to +80°C (-13°F up to 176°F)
Antenna	Aircoil
R/W Distance	up to 100 mm / 4 inch (depending on transponder)
Host Interfaces	USB, RS232.
OS Support	Windows XP, Vista, 7(32/64 bit), 8, 8.1 and Linux
Communication Parameters	USB: Full speed (12 MBit) RS232: Baudrate: 9600 Parity: none, even, odd
Modes of Operation	USB keyboard emulation USB virtual COM port (bi-directional communication) Direct access to built-in RFID module (transparent mode)
Special Features	Powerful scripting language
Supported Transponders	<ul style="list-style-type: none"> ▪ ISO14443A ▪ MIFARE: Classic 1k & 4k , Classic 1k & 4k EV¹), DESFire EV¹), Mini, Plus S²), X² , Pro X¹), SmartMX¹), PayPass¹), Ultralight, Ultralight EV¹), Ultralight C³), NTAG2xx⁴) ▪ LEGIC Advant (ISO14443A)¹) ▪ SLE44R35¹) ▪ SLE66Rxx (my-d move)¹)
Certifications	CE, Australia, EAC, FCC, IC, SRRC, RoHS-II compliant
Weight	Approximately 15g (without housing)
Order Code	OEM board Desktop reader: T3DO-M USB black: T3DT-MB2BEL USB white: T3DT-MB2WEL Serial black: T3DT-MR2BEL Serial white: T3DT-MR2WEL

¹) UID only, ²) Support of security level 1 ³) Without crypto ⁴) r/w , enhanced security features planned

Accessories					
Order Code	Snap-in holder HKSI-B - black, HKSI-W - white		Bracket Holder HKBR-B - black, HKBR-W - white		CAB-B2 - USB cable 200cm / 78.74inch CAB-B4 - USB cable 45cm / 17.72inch CAB-B7 - USB cable 120cm / 47.24inch CAB-M1 - USB cable mini 12cm / 4.72inch CAB-R2 - RS232 cable 200cm / 78.74inch
Order Code	PWA-EU - Power Supply (EU) PWA-AUS - Power Supply (AU)		ART14713 Power Supply (US) ART14715 Power Supply (UK)		

Drawing/Pin Out
Refer to document DS_TWN3 Pinout & Cables

Elatec reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. Elatec declines all responsibility for the use of product with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification. Disclaimer: All names are registered trademarks. © 2015 Elatec GmbH – DocRev5 – 08/2015

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Modules](#) category:

Click to view products by [Elatec](#) manufacturer:

Other Similar products are found below :

[HMC-C009](#) [nRF24L01P-MODULE-PCB](#) [HMC-C001](#) [HMC-C021](#) [HMC-C024](#) [XB9XT-DPRS-721](#) [XBP24BZ7PIT-004J](#) [XBP9B-DMUTB022](#) [nRF24L01P-MODULE-SMA](#) [CMD-KEY2-418-CRE](#) [XM-C92-2P-UA](#) [XB9XT-DPUS-721](#) [V640-A90](#) [HMC-C583](#) [MAAM-008818-TR3000](#) [MTSMC-H5-U](#) [SIMSA868-PRO](#) [SIMSA915C-PRO](#) [SIMSA868C-PRO](#) [SIMSA433C-PRO](#) [SIMSA915-PRO](#) [XBP9B-DMUT-042](#) [HMC-C582](#) [HMC-C022](#) [XBP9B-DPST-041](#) [XBP9B-DMWT-042](#) [SM-MN-00-HF-RC](#) [HMC-C031](#) [MT-02](#) [M1002GB](#) [702-W](#) [SIMSA868C-N-PRO](#) [SIMSA433C-N-PRO](#) [SIMSA915C-N-PRO](#) [PEPPER WIRELESS C1 USB](#) [S2-1050J-Z0K4J](#) [S2-10732-Z1T61](#) [S2-10716-Z1W4E](#) [S2-107ET-Z1W6D](#) [S2-10686-Z1L1D](#) [S2-10688-Z1L1T](#) [S2-106BA-Z1P20](#) [UC15EA-MINIPCIE](#) [SU60-2230C-PU](#) [RC-TFSK3-868](#) [NANO RFID POE](#) [650201424G](#) [H330 A30-00](#) [CMD-HHCP-433-MD](#) [RC-CC1101-SPI-868](#)