

Braided shielded cables sect. 0,75 mm²



FirestoP®



Applications:
Braided shielded cables for data transmission and electronics.

Characteristics:
Conductors: stranded in O.F.C. red copper
Cond. Insulation: Flame Retardant PVC CEI 20-22/II°
Core colours: Brown, Blue, Black, Yellow/green, Red, White, Yellow, Grey, Bright-orange, Green, Violet, Pink
Total Shield: Braided covering 85% O.F.C. red copper
External Sheath: Flame Retardant PVC CEI 20-22/II°
Sheath colour: Black

Max rated Voltage AC: 49 V.
Operative Temperature °C.: -15° / +70°



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C 1075	1	1 x 0,75 (18 AWG)	24x0,20	2,3		4,0	100	B	2,6
C 2075	2	2 x 0,75 (18 AWG)	24x0,20	2,3		6,4	100	B	5,8
C 3075	3	3 x 0,75 (18 AWG)	24x0,20	2,3		6,8	100	B	7,8
C 4075	4	4 x 0,75 (18 AWG)	24x0,20	2,3		7,4	100	B	11,0
C 5075	5	5 x 0,75 (18 AWG)	24x0,20	2,3		7,8	100	B	9,0
C 6075	6	6 x 0,75 (18 AWG)	24x0,20	2,3		8,6	100	B	12,0
C 8075	8	8 x 0,75 (18 AWG)	24x0,20	2,3		10,6	100	B	14,5
C10075	10	10 x 0,75 (18 AWG)	24x0,20	2,3		11,2	100	B	15,0
C12075	12	12 x 0,75 (18 AWG)	24x0,20	2,3		11,6	100	B	25,0

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
30		260
30	170	300
30	150	270
30	140	260
30	140	260
30	130	250
30	110	220
30	100	210
30	100	200

Braided shielded cables sect. 1,00 mm²



FirestoP®



Applications:
Braided shielded cables for data transmission and electronics.

Characteristics:
Conductors: stranded in O.F.C. red copper
Cond. Insulation: Flame Retardant PVC CEI 20-22/II°
Core colours: Brown, Blue, Black, Yellow/green, Red, White, Yellow, Grey
Total Shield: Braided covering 85% O.F.C. red copper
External Sheath: Flame Retardant PVC CEI 20-22/II°
Sheath colour: Black

Max rated Voltage AC: 49 V.
Operative Temperature °C.: -15° / +70°



C 1100	1	1 x 1,00 (17 AWG)	32x0,20	2,5		4,4	100	B	3,0
C 2100	2	2 x 1,00 (17 AWG)	32x0,20	2,5		7,2	100	B	8,0
C 3100	3	3 x 1,00 (17 AWG)	32x0,20	2,5		7,8	100	B	9,0
C 4100	4	4 x 1,00 (17 AWG)	32x0,20	2,5		8,6	100	B	10,0
C 6100	6	6 x 1,00 (17 AWG)	32x0,20	2,5		10,8	100	B	16,0
C 8100	8	8 x 1,00 (17 AWG)	32x0,20	2,5		11,2	100	B	19,0

21		280
21	170	300
21	150	270
21	130	240
21	130	230
21	120	220

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Conductor Cables](#) category:

Click to view products by [Tasker](#) manufacturer:

Other Similar products are found below :

[M27500-20SP2S23](#) [M3905-BK005](#) [6502FE 8771000](#) [CV6807-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [720451-000](#) [752687-000](#) [83709-002-1000](#) [8469 060100](#) [877541-000](#) [88444-002-1000](#) [9444 060U1000](#) [9497 0001000](#) [9684-060-1000](#) [1302110032](#) [EPD6062-12-9CS1693](#) [EPD-RWC-10972](#) [EPD-RWC-12305](#) [C35473-000](#) [2020D1301-9](#) [219538-6](#) [2412F-010-1000](#) [9534 060U500](#) [29531-010-2000](#) [22759/41-22-9CS2620](#) [259633-000](#) [29529C-010-2000](#) [29532-010-1500](#) [302595-000](#) [CTC-0018-22-9/5-9CS2340](#) [3600B/50 100SF](#) [3644B/16-100SF](#) [CXA-0078-20-3-9CS2405](#) [CXA-0092-14-6/9CS2973](#) [MC6A-16/0.2T2-YWGN](#) [44A0211-20-9CS3030](#) [44A0311-12-9-F871](#) [44A1221-14-9/9-9CS3030](#) [44A1221-16-9/9-9CS3030](#) [44A1321-14-9/9-9CS3030](#) [44A9685-0-F957CS2855](#) [506087-000](#) [5102UE 008500](#) [5201UE 0081000](#) [534553-000](#)