

We measure it.



Ambient CO-/CO₂ measuring instrument

testo 315-3 – Parallel measurement of CO and CO₂ in ambient air according to European standard EN 50543

Parallel and direct CO-/CO₂ measurement

TÜV-tested according to EN 50543

Convenient, easy handling

Measurement values transferrable to the testo 330 (V2010)

Data printout on site



°C

%RH

ppm
CO₂ppm
CO

Precision – from the sensor to the housing

With a highly accurate electrochemical sensor for CO measurement and a shock-resistant infrared CO₂ sensor, the measuring instrument testo 315-3 is state-of-the-art technology. It is excellently equipped to resist external influences by its robust design and the optionally available TopSafe. And that's not all. During the measurement, optical and audible signals let you know immediately whether the variably adjustable limit values have been exceeded.

Thanks to the wireless data transfer via IrDA or Bluetooth, you can transfer your measurement data directly to the flue gas analyzer testo 330, or print them out. Your customers receive a special service: the results are presented directly on site. The Auto-off function and a Lithium polymer rechargeable battery ensure that the instrument, thanks to its long running time, can be used for long periods without using unnecessary power.

www.testolimited.com

testo 315-3

We measure it. 

Technical data

testo 315-3 without Bluetooth

testo 315-3 ambient CO/CO₂ measuring instrument without Bluetooth incl. USB mains unit and cable

Part no. 0632 3153



testo 315-3 Bluetooth

testo 315-3 CO/CO₂ measuring instrument with Bluetooth incl. USB mains unit and cable

Part no. 0632 3154

General technical data

Storage temperature	-20 to +60 °C / -4 to +140 °F	
Operating temperature	0 to +40 °C / +32 to +104 °F	
Oper. humidity	0 to 95 %RH	
Protection class	IP40 acc. to EN 60529	
Power supply	Lithium polymer battery pack	
Battery life	10 h measurement time (at +20 °C/+68 °F) / Mains operation possible	
Battery charging	In instrument via charger	
Interface	IrDA interface / optional: Bluetooth	
Permit	Acc. to EN 50543	
EC guideline	2004/108/EC	
Dimensions	190 x 65 x 40 mm	
Weight	200 g	
Warranty	Instrument:	24 months
	Rech. battery:	12 months
	CO sensor:	12 months
	CO ₂ sensor:	12 months
	Warranty conditions see internet page: www.testo.com/warranty	

Sensor type	Measuring range	Accuracy ±1 digit	Resolution
CO sensor	0 to 100 ppm	±3 ppm (0 to 20 ppm) ±5 ppm (>20 ppm)	0.5 ppm
CO ₂ sensor	0 to 10.000 ppm	±300 ppm (0 to 4.000 ppm) ±8% of mv (4.000 to 6.000 ppm) ±500 ppm (6.000 to 10.000 ppm)	10 ppm
Temperature/humidity module	+5 to +95 %RH -10 to +60 °C	±2.5 %RH (5 to 95 %RH) ±0.5 °C (±1 Digit)	0.1 %RH 0.1 °C

Accessories

Accessories	Part no.
Accessories for measuring instrument	
Temperature/humidity module Ø 25 mm, plug-in	0636 9725
USB mains unit incl. cable	0554 1105
Transport and Protection	
Topsafe testo 315-3	0516 0223
Case for secure storage of measuring instrument	0516 0191
Printer and Accessories	
Testo fast printer IRDA with wireless infrared interface; 1 roll thermal paper; 4 AA batteries	0554 0549
BLUETOOTH printer set with wireless BLUETOOTH interface; incl. 1 roll thermal paper, rechargeable battery and mains unit	0554 0553
Spare thermal paper for printer, permanent ink	0554 0568
Additional accessories	
Control and adjustment set for humidity sensors (11.3 %RH and 75.3 %RH)	0554 0660



Topsafe testo 315-3




Temperature/humidity module Ø 25 mm, plug-in



Case for secure storage of measuring instrument (without content)





Testo fast printer IRDA with wireless infrared interface



testo 315-3



0981 2621 20/cw/A/01.2014



Testo Limited
Newman Lane
ALTON, HAMPSHIRE
GU34 2UR
Phone: 01420 544 433
Fax: 01420 544 434
Email: info@testo.co.uk

www.testolimited.com



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Testo manufacturer:](#)

Other Similar products are found below :

[206 PH1](#) [TESTO 316-1 0632 0316](#) [TESTO 470 0563 0470](#) [TESTO 770-1 0590 7701](#) [TESTO 905-T1 0560 9055](#) [0572 0500](#) [0590 0016](#) [0602 4592](#) [0590 0008](#) [0590 0018](#) [0602 0645](#) [0635 1025](#) [0628 0020](#) [TESTO 435-2 0563 4352](#) [TESTO 605I 0560 1605](#) [TESTO 755-2 0590 7552](#) [TESTO 770-2 0590 7702](#) [TESTO 869 + TESTO 745](#) [TESTO 869 + TESTO 750-3 465 410-2 460 0572 6172](#) [0590 0001](#) [0614 2272](#) [TESTO 417 0560 4170](#) [0609 7072](#) [TESTO 174-H SET](#) [TESTO 176-T4](#) [TESTO 176-P1](#) [TESTO 830-T2](#) [TESTO 103](#) [TESTO 905-T1](#) [TESTO 108-2](#) [TESTO 905I](#) [TESTO 108 0563 4403](#) [0590 7703](#) [TESTO 435-3 0560 4353](#) [TESTO 735-1 0560 7351](#) [TESTO 760-3 0590 7603](#) [TESTO 770-3 0590 7703](#) [0590 0013](#) [0602 4892](#) [TESTO 635-2 0563 6352](#) [TESTO 750-3 0590 7503](#) [TESTO 760-1 0590 7601](#) [816-1](#) [TESTO 174-T SET](#) [TESTO 605-H1](#)