

## Braided shielded cables sect. 1,50 mm<sup>2</sup>



**Firestop®**



**Applications:**  
Braided shielded cables for data transmission and electronics.

**Characteristics:**  
 Conductors: stranded in O.F.C. red copper  
 Cond. Insulation: Flame Retardant PVC CEI 20-22/II°  
 Core colours: Brown, Blue, Black, Yellow/green  
 Total Shield: Braided covering 85% O.F.C. red copper  
 External Sheath: Flame Retardant PVC CEI 20-22/II°  
 Sheath colour: Black



Max rated Voltage AC: 49 V.  
Operative Temperature °C.: -15° / +70°

tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C 1150	1	1 x 1,50 (16 AWG)	30x0,25	2,9		4,8	100	B	3,8
C 2150	2	2 x 1,50 (16 AWG)	30x0,25	2,9		7,8	100	B	10,0
C 3150	3	3 x 1,50 (16 AWG)	30x0,25	2,9		8,4	100	B	11,0
C 4150	4	4 x 1,50 (16 AWG)	30x0,25	2,9		10,0	100	B	14,0

## Spiral shielded cables 500 series



**Applications:**  
Flexible spiral shielded cables for data transmission and electronics. Suitable to connect also RJ 45 connectors in electronic applications.

**Characteristics:**  
 Conductors: stranded in O.F.C. red copper  
 Cond. Insulation: PVC  
 Core colours: DIN 47100 standards  
 Total Shield: Spiral covering 100% O.F.C. red copper  
 External Sheath: PVC  
 Sheath colour: Grey - RAL 7032



Max rated Voltage AC: 49 V.  
Operative Temperature °C.: -15° / +70°

tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C 504	4	4 x 0,12 (26 AWG)	7x0,15	0,9		3,8	100	B	2,4
C 506	6	6 x 0,12 (26 AWG)	7x0,15	0,9		4,6	100	B	3,5
C 508	8	8 x 0,12 (26 AWG)	7x0,15	0,9		5,0	100	B	4,0

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
140	100	200
140	90	180
140	80	170

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Multi-Conductor Cables](#) category:*

*Click to view products by [Tasker](#) manufacturer:*

Other Similar products are found below :

[M27500-20SP2S23](#) [M3905-BK005](#) [6502FE 8771000](#) [CV6807-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [720451-000](#) [752687-000](#) [83709-002-1000](#) [8469 060100](#) [877541-000](#) [88444-002-1000](#) [9444 060U1000](#) [9497 0001000](#) [9684-060-1000](#) [1302110032](#) [EPD6062-12-9CS1693](#) [EPD-RWC-10972](#) [EPD-RWC-12305](#) [C35473-000](#) [2020D1301-9](#) [219538-6](#) [2412F-010-1000](#) [9534 060U500](#) [29531-010-2000](#) [22759/41-22-9CS2620](#) [259633-000](#) [29529C-010-2000](#) [29532-010-1500](#) [302595-000](#) [CTC-0018-22-9/5-9CS2340](#) [3600B/50 100SF](#) [3644B/16-100SF](#) [CXA-0078-20-3-9CS2405](#) [CXA-0092-14-6/9CS2973](#) [MC6A-16/0.2T2-YWGN](#) [44A0211-20-9CS3030](#) [44A0311-12-9-F871](#) [44A1221-14-9/9-9CS3030](#) [44A1221-16-9/9-9CS3030](#) [44A1321-14-9/9-9CS3030](#) [44A9685-0-F957CS2855](#) [506087-000](#) [5102UE 008500](#) [5201UE 0081000](#) [534553-000](#)