



Heat Shrinkable Tubing 3:1 - Self extinguishing

TCN20 overexpanded

Mechanical, electrical and corrosion protection applications for parts with high diameter variances. This fast shrinking tubing makes it suitable for high volume production.

Features and Benefits

- Thin walled overexpanded polyolefin tubing
- Inch size tubing with 3:1 shrink ratio
- Very fast shrinking and low shrink temperature
- Highly flame-retardant, UL224 VW-1



Heat shrink tubing TCN20 overexpanded.

MATERIAL	Polyolefin, cross-linked (PO-X)
Shrink Ratio	3:1
Operating Temperature	-55 °C to +125 °C
Minimum Shrink Temperature	+100 °C
Longitudinal change after shrinkage	+/-5 %
Dielectric Strength	20kV/mm according to ASTM D2671
Flammability	Self extinguishing
Specifications	CSA, UL224 125 °C 600V VW-1

RoHS



Heat Shrinkable Tubing 3:1

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Article-No.
TCN20-2.4/0.8	2.4	0.8	0.40	300 m	Black (BK)	300-73130
TCN20-3.2/1.2	3.2	1.2	0.50	300 m	Black (BK)	300-73140
TCN20-4.8/1.6	4.8	1.6	0.50	300 m	Black (BK)	300-73150
TCN20-6.6/2.4	6.6	2.4	0.55	300 m	Black (BK)	300-73160
TCN20-9.5/3.2	9.5	3.2	0.65	100 m	Black (BK)	300-73170
TCN20-12.7/4.8	12.7	4.8	0.75	100 m	Black (BK)	300-73180
TCN20-19.0/6.4	19.0	6.4	0.75	60 m	Black (BK)	300-73190
TCN20-25.4/9.5	25.4	9.5	0.79	60 m	Black (BK)	300-73200
TCN20-38.0/12.7	38.0	12.7	0.95	30 m	Black (BK)	300-73210

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:

Click to view products by [Hellermann](#) manufacturer:

Other Similar products are found below :

[770-006S102](#) [5685710001](#) [CR6145-000](#) [CR8248-000](#) [CR9960-000](#) [603312-4](#) [607381P039](#) [617867N001](#) [6500750004](#) [D-306-38](#) [770-003S106W2](#)
[770-007A303](#) [770-010Y106W1](#) [770-010Y706W1](#) [7771210001](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [MFT-MT2000-NO.14-0-SP](#) [MFT-MT2000-](#)
[NO.65-X-SP](#) [MHHT-4-15K2-G-104](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#) [MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-](#)
[3/32-6-SP](#) [MIL-LT-3/4-6-SP](#) [MIL-LT-3/8-0-SP](#) [8159270001](#) [839602-000](#) [8423-6](#) [FP301-116-6"-Black](#) [FP301-1/2-48"-Black](#) [FP301-12-48"-Black-](#)
[Hdr](#) [FP301-1/4-48"-Black](#) [FP301-1/4-48"-White-Hdr](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-](#)
[Hdr](#) [FP301-316-6"-Clear](#) [FP301-332-6"-Black](#) [FP301-3/8-6"-Clear](#) [912229N002](#) [120-126-16BL](#) [121-001-09](#) [121-018-32](#) [121-018-40](#) [121-123-1-1-](#)
[32BTC](#) [121-123-1-1-40BTC](#)