



### Heat Shrinkable Tubing 3:1 flexible and coloured

#### TF31

If higher fire protection is a requirement heat shrinkable tubing TF31 is a good choice. It is used for protection insulation and identification wires, cables and light duty harnesses.

#### Features and Benefits

- Thin walled, very flexible polyolefin tubing
- Few sizes cover a wide range of diameters allowing reduced inventory
- Fast shrinking and low shrink temperature
- Flame-retardant, UL224 VW1 listed




**Detailed Information about Heatguns please refer to page 529.**



**Cut lengths available on request. Please contact us!**




One Step to the Web!



Heat Shrinkable Tubing 3:1

**RoHS** ✓



TF31 with 3:1 shrink ratio allowing for a wider range of application.

<b>MATERIAL</b>	Polyolefin, cross-linked (PO-X)
<b>Shrink Ratio</b>	3:1
<b>Operating Temperature</b>	-55 °C to +135 °C
<b>Minimum Shrink Temperature</b>	+90 °C
<b>Longitudinal change after shrinkage</b>	+5 %/-15 %
<b>Dielectric Strength</b>	37 kV/mm
<b>Flammability</b>	ASTM D876
<b>Specifications</b>	CSA, UL224 125 °C 600V VW-1

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Article-No.
TF31-1.5/0.5	1.5	0.5	0.50	30 m	Black (BK)	333-30150
	1.5	0.5	0.50	30 m	Blue (BU)	333-30156
	1.5	0.5	0.50	30 m	Green (GN)	333-30155
	1.5	0.5	0.50	30 m	Green-Yellow (GNYE)	333-30157
	1.5	0.5	0.50	30 m	Red (RD)	333-30152
	1.5	0.5	0.50	30 m	White (WH)	333-30159
	1.5	0.5	0.50	30 m	Yellow (YE)	333-30154
	1.5	0.5	0.50	300 m	Black (BK)	333-20150
TF31-3/1	3.0	1.0	0.60	30 m	Black (BK)	333-30300
	3.0	1.0	0.60	30 m	Blue (BU)	333-30306
	3.0	1.0	0.60	30 m	Green (GN)	333-30305
	3.0	1.0	0.60	30 m	Green-Yellow (GNYE)	333-30307
	3.0	1.0	0.60	30 m	Red (RD)	333-30302
	3.0	1.0	0.60	30 m	White (WH)	333-30309
	3.0	1.0	0.60	30 m	Yellow (YE)	333-30304
	3.0	1.0	0.60	150 m	Black (BK)	333-40300

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.



### Heat Shrinkable Tubing 3:1 flexible and coloured

TF31




Heat Shrinkable Tubing 3:1

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Article-No.
TF31-6/2	6.0	2.0	0.70	30 m	Black (BK)	333-30600
	6.0	2.0	0.70	30 m	Blue (BU)	333-30606
	6.0	2.0	0.70	30 m	Green (GN)	333-30605
	6.0	2.0	0.70	30 m	Green-Yellow (GNYE)	333-30607
	6.0	2.0	0.70	30 m	Red (RD)	333-30602
	6.0	2.0	0.70	30 m	White (WH)	333-30609
	6.0	2.0	0.70	30 m	Yellow (YE)	333-30604
	6.0	2.0	0.70	150 m	Black (BK)	333-40600
TF31-9/3	9.0	3.0	0.80	30 m	Black (BK)	333-30900
	9.0	3.0	0.80	30 m	Blue (BU)	333-30906
	9.0	3.0	0.80	30 m	Green (GN)	333-30905
	9.0	3.0	0.80	30 m	Green-Yellow (GNYE)	333-30907
	9.0	3.0	0.80	30 m	Red (RD)	333-30902
	9.0	3.0	0.80	30 m	White (WH)	333-30909
	9.0	3.0	0.80	30 m	Yellow (YE)	333-30904
	9.0	3.0	0.80	150 m	Black (BK)	333-20900
TF31-12/4	12.0	4.0	0.85	30 m	Black (BK)	333-31200
	12.0	4.0	0.85	30 m	Blue (BU)	333-31206
	12.0	4.0	0.85	30 m	Green (GN)	333-31205
	12.0	4.0	0.85	30 m	Green-Yellow (GNYE)	333-31207
	12.0	4.0	0.85	30 m	Red (RD)	333-31202
	12.0	4.0	0.85	30 m	White (WH)	333-31209
	12.0	4.0	0.85	30 m	Yellow (YE)	333-31204
	12.0	4.0	0.85	100 m	Black (BK)	333-21200
TF31-18/6	18.0	6.0	1.00	30 m	Black (BK)	333-31800
	18.0	6.0	1.00	30 m	Blue (BU)	333-31806
	18.0	6.0	1.00	30 m	Green (GN)	333-31805
	18.0	6.0	1.00	30 m	Green-Yellow (GNYE)	333-31807
	18.0	6.0	1.00	30 m	Red (RD)	333-31802
	18.0	6.0	1.00	30 m	White (WH)	333-31809
	18.0	6.0	1.00	30 m	Yellow (YE)	333-31804
	18.0	6.0	1.00	60 m	Black (BK)	333-41800

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.



## Heat Shrinkable Tubing 3:1 flexible and coloured

TF31



Heat Shrinkable Tubing 3:1



Detailed Information about Heatguns please refer to page 529.

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Article-No.
TF31-24/8	24.0	8.0	1.20	30 m	Black (BK)	333-32400
	24.0	8.0	1.20	30 m	Blue (BU)	333-32406
	24.0	8.0	1.20	30 m	Green (GN)	333-32405
	24.0	8.0	1.20	30 m	Green-Yellow (GNYE)	333-32407
	24.0	8.0	1.20	30 m	Red (RD)	333-32402
	24.0	8.0	1.20	30 m	White (WH)	333-32409
	24.0	8.0	1.20	30 m	Yellow (YE)	333-32404
	24.0	8.0	1.20	60 m	Black (BK)	333-42400
TF31-40/13	40.0	13.0	1.25	30 m	Black (BK)	333-34000
	40.0	13.0	1.25	30 m	Blue (BU)	333-34006
	40.0	13.0	1.25	30 m	Green (GN)	333-34005
	40.0	13.0	1.25	30 m	Green-Yellow (GNYE)	333-34007
	40.0	13.0	1.25	30 m	Red (RD)	333-34002
	40.0	13.0	1.25	30 m	White (WH)	333-34009
	40.0	13.0	1.25	30 m	Yellow (YE)	333-34004
	40.0	13.0	1.25	60 m	Black (BK)	333-24000

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[770-006S102](#) [5685710001](#) [CR6145-000](#) [CR9960-000](#) [603312-4](#) [607381P039](#) [617867N001](#) [6500750004](#) [D-306-38](#) [770-003S106W2](#) [770-007A303](#)  
[770-010Y106W1](#) [770-010Y706W1](#) [7771210001](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [MFT-MT2000-NO.14-0-SP](#) [MFT-MT2000-NO.65-X-SP](#)  
[MHHT-4-15K2-G-104](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#) [MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-3/32-6-SP](#)  
[MIL-LT-3/4-6-SP](#) [MIL-LT-3/8-0-SP](#) [8159270001](#) [839602-000](#) [8423-6](#) [FP301-116-6"-Black](#) [FP301-1/2-48"-Black](#) [FP301-12-48"-Black-Hdr](#) [FP301-1/4-48"-Black](#) [FP301-1/4-48"-White-Hdr](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-Hdr](#) [FP301-316-6"-Clear](#) [FP301-332-6"-Black](#) [FP301-3/8-6"-Clear](#) [912229N002](#) [120-126-16BL](#) [121-001-09](#) [121-018-32](#) [121-018-40](#) [121-123-1-1-32BTC](#) [121-123-1-1-40BTC](#) [121-127-09BK](#)