



Special Product Data	Conditions	Min	Typ	Max	Unit
Sealing compound		Voltatex CE 12 FW-UL			
Housing material		Crastin,SK 645FR, rated 94V-0, 140 °C, E.I. Dupont			
Case color		black			

Mag. values DIN IEC 60404-8-	Conditions	Min	Typ	Max	Unit
Remanence Br		1.120	1.240		mT
Revers. temp. coeff. of Br			-0,02		%/K
Coercivity HcB		47	51,3		kA/m
Coercivity HcJ		48	51,7		kA/m
Density			7,4		g/cu cm
Max. operating temperature				80	°C
Magnetic moment	measured with MS150	19,8	22,2		E-6 Vs*cm
Magnet Material		AlNiCo			
Direction of Magnetization		axial			

General data	Conditions	Min	Typ	Max	Unit
Remarks		All details according to manufacturers information			

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Standexmeder](#) manufacturer:*

Other Similar products are found below :

[MK21P-KIT](#) [LS04-2A66-PP-500W](#) [HE12-1A83](#) [HM24-1A69-300](#) [DIP24-1C90-51L](#) [MK18-B-500W](#) [SHV12-1A85-78L4K](#) [HE06-1B83-150](#)  
[MK24-B-3-OE](#) [MK21M-1A66B-500W](#) [SIL05-1A72-71QHR](#) [H24-1B83](#) [HE05-1A83-150](#) [BE12-2A85-BV420](#) [LI05-1A85](#) [KSK-1A80-1020](#)  
[BE24-1A66-M](#) [KT12-1A-BV88589](#) [HM24-1A69-20-6](#) [HM12-1A83-06-UL](#) [MK04-1A66C-500W](#) [DIP05-1A72-11L](#) [KT12-1A-40L-THT](#)  
[NDFEB 8X15MM](#) [MK04-1A66B-500W](#) [MK06-4-C](#) [NDFEB 10X5X1.9MM](#) [H12-1B83](#) [MK06-4-B](#) [LS01-1A66-PP-500W](#) [ALNICO500;](#)  
[5X20MM](#) [MS05-1A87-75D](#) [HM24-1B69-06](#) [SIL05-1A31-71L](#) [DIP12-2A72-21L](#) [MK06-8-H](#) [MS05-1A87-75DHR](#) [DIP24-1C90-51D](#)  
[GR560-1520](#) [M11/M8](#) [LS02-1A66-PA-500W](#) [FPS-B](#) [HE24-1A83](#) [SHV12-1A85-78L3K](#) [KSK-1C90F-2025](#) [HE24-1A69-03](#) [LI24-1A85](#)  
[M13](#) [NDFEB 6X10MM](#) [LS02-1A66-PP-500W](#)