

A	V	Hz	2P+E	EARTH HR. POS	3P+E	EARTH HR. POS	3P+N+E	EARTH HR. POS
CURRENT	VOLTAGE	FREQUENCY						

## Connectors

**CEE** NORM

16	110	50 - 60	31886	4				
	240	50 - 60	31880	6				
	415	50 - 60			31881	6	312001	6
32	110	50 - 60	310085	4				
	240	50 - 60	31882	6				
	415	50 - 60			31883	6	312002	6



### QUICK CONNECT® Connector with Cable Sleeve

- Screwless terminals
- IP54 Splashproof

16	110	50 - 60	3125	4	31681	4	31962	4
	240	50 - 60	3126	6	3129	9	31662	9
	415	50 - 60	31665	9	3130	6	3136	6
32	110	50 - 60	3137	4	31973	4	31979	4
	240	50 - 60	3138	6	3141	9	31664	9
	415	50 - 60	31666	9	3142	6	3148	6



### QUICK CONNECT® Connector with Multi-Grip Cable Gland

- Screwless terminals
- IP54 Splashproof

63	110	50 - 60						
	240	50 - 60						
	415	50 - 60			310490	6	310494	6

63A with screwless terminals and pilot contact

**Note:** This pilot contact should **NOT** be counted as a main 'pin'



### QUICK CONNECT® Connector with Multi-Grip Cable Gland


- Screwless terminals
- IP54 Splashproof

**QUICK CONNECT®**



# Dimensions

**CEE** NORM




Amperes	16			32		
Poles	3	4	5	3	4	5
Ø a	53	58	64	66	66	74
b	142	147	156.5	181	181	181
Ø c	5	5	7	8	8	8.5
Ø d	14.5	15.5	17.5	23.5	23.5	26
e	72	78	85	90	90	99
Conductor mm <sup>2</sup> min	1	1	1	2.5	2.5	2.5
Conductor mm <sup>2</sup> max	2.5	2.5	2.5	6	6	6

## QUICK CONNECT<sup>®</sup> Connector

- Moulded cable sleeve
- 4-point (quarter turn) locking system
- Screwless terminals

 Splashproof




Amperes	16			32		
Poles	3	4	5	3	4	5
Ø a	53	60	66	74.5	74.5	74.5
b	104.5	116.5	117.5	137.5	137.5	138.5
c	145	157	158	190	190	191
d	97.5	104.5	105.5	127.5	127.5	128.5
Ø e	18	18	18	23	23	23
f	69	79	86	92	92	97
Conductor mm <sup>2</sup> min	1	1	1	2.5	2.5	2.5
Conductor mm <sup>2</sup> max	2.5	2.5	2.5	6	6	6

## QUICK CONNECT<sup>®</sup> Connector with Multi-Grip Cable Gland

- Screwless terminals
- 4-point (quarter turn) locking system
- Multi-Grip cable gland system with moulded-in gasket

 Splashproof



Amperes	63	
Poles	4	5
Ø a	95	95
b	251	251
c	109	109
Ø d	36	36
Conductor mm <sup>2</sup> min	6	6
Conductor mm <sup>2</sup> max	16	16

## QUICK CONNECT<sup>®</sup> Connector with Multi-Grip Cable Gland

- Multi-Grip cable gland system with moulded-in gasket
- Max cable diameter 36mm
- Screwless terminals
- Nickel plated contacts

 Splashproof

**QUICK  CONNECT<sup>®</sup>**

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Ceenorm](#) manufacturer:*

Other Similar products are found below :

[2138](#) [11962](#) [11302](#) [21013-TLS](#) [31012-TLS](#) [112001](#) [3126](#) [3138](#) [204-TLS](#) [203-TLS](#) [31001-TLS](#) [21001-TLS](#)