



Polyester self-closing sleeving

Helagain Twist-In

Helagain Twist-In is used to bundle and protect pre-terminated cables in machine-building and automation, electrical installations and automobile and truck manufacturing.

Helagain Twist-In is also available in practical 2 m and 5 m lengths for use in the home or office.

Features and Benefits

- Self-closing sleeve made of polyester
- Very good protection against abrasion
- Ideal for retro-fitting
- Quick and easy installation and removal
- Allows to bundle for inspection, maintenance and assembly
- Small range of sizes covers a wide range of applications



Helagain Twist-In gives easy access to cables and wires for inspection, maintenance and assembly.



Application video: Twist-In

MATERIAL	Polyester (PET)
Operating Temperature	-70 °C to +125 °C
Melting Point	+255 °C
Flammability	Self extinguishing, FMVSS 302
Specifications	UL-Recognised



The sleeve can best be cut with the hot cutting tool HSG0. See page 533.



TYPE	Bundle Ø min.	Bundle Ø max.	Colour	Reel Length	Article-No.
Twist-In 05	4.0	5.0	Black (BK)	150 m	170-01000
Twist-In 08	5.0	8.0	Black (BK)	100 m	170-01001
Twist-In 13	10.0	13.0	Black (BK)	50 m	170-01002
Twist-In 19	16.0	19.0	Black (BK)	25 m	170-01004
Twist-In 25	19.0	25.0	Black (BK)	25 m	170-01005
Twist-In 29	25.0	29.0	Black (BK)	15 m	170-01006
Twist-In 32	29.0	32.0	Black (BK)	15 m	170-01007
Twist-In 38	32.0	38.0	Black (BK)	15 m	170-01008
Twist-In 50	38.0	50.0	Black (BK)	15 m	170-01010

All dimensions in mm. Subject to technical changes. Minimum Order Quantity (MOQ) may differ from package content.

TYPE	Bundle Ø min.	Bundle Ø max.	Colour	Reel Length	Article-No.
Twist-In 05	4.0	5.0	Black (BK)	5 m	170-01011
Twist-In 08	5.0	8.0	Black (BK)	5 m	170-01012
Twist-In 13	10.0	13.0	Black (BK)	5 m	170-01013
Twist-In 19	16.0	19.0	Black (BK)	2 m	170-01014
Twist-In 25	19.0	25.0	Black (BK)	2 m	170-01015
Twist-In 29	25.0	29.0	Black (BK)	2 m	170-01016
Twist-In 32	29.0	32.0	Black (BK)	2 m	170-01017
Twist-In 38	32.0	38.0	Black (BK)	2 m	170-01018

All dimensions in mm. Subject to technical changes. Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Non-Heat Shrink Tubing and Sleeves](#) category:

Click to view products by [Hellermann](#) manufacturer:

Other Similar products are found below :

[CTA-0053](#) [8429-9](#) [8445-7.5](#) [8450](#) [120-116-1-1-09BE](#) [120-116-1-1-09BF](#) [120-116-1-1-09BP](#) [120-116-1-1-12BE](#) [120-116-1-1-12BP](#) [120-123-06](#) [120-123-10](#) [120-125-12BL](#) [120-125-12R](#) [120-125-20R](#) [120-126-09](#) [120-126-09BL](#) [120-126-12](#) [120-126-12BL](#) [120-126-52](#) [120-126-52BL](#) [120-104-12](#) [120-105-1-1-06BE](#) [120-105-1-1-06CE](#) [120-116-1-1-06BP](#) [120-116-1-1-10BP](#) [120-116-1-1-12BF](#) [120-123-12](#) [120-125-09](#) [120-125-12](#) [120-125-12Y](#) [120-125-52BL](#) [120-S002-12](#) [HC1B-7008-0375-0](#) [120-S001-09](#) [120-S002-09](#) [121-101-1-1-56BFC](#) [121-101-1-1-64BFC](#) [RAY-90-3.0\(100\)](#) [20675-2](#) [8S42-100FR-CS8184](#) [SAS-115-1-1048-1X](#) [SAS-160-1-1048-1X](#) [25T-GB](#) [RAY-103-10.0\(100\)](#) [RAY-103-4.0\(100\)](#) [4627-S](#) [3-1991136-0](#) [561-SL1000NYGY](#) [561-SL1000PP](#) [561-SL250FRPP](#)