



CONSTRUCTION:
[(1/0.50)*4P]BC

CONSTRUCTION DESCRIPTION :

1. CONDUCTOR: 1/0.50 ± 0.005BC
ID: 0.94 ± 0.02mm
MATERIAL: HDPE (210)
2. STANDING DIRECTION: RIGHT
3. FILLER: 500D NYLON PLASTIC
4. OD: 5.2 ± 0.15mm
MATERIAL: 45P PVC
COLOR: GREY

5. MAKING:

NETWORK SYSTEMS CABLE UTP ANSI TIA/EIA-568A 24AWG
(4PR) OR ISO/IEC11801 VERIFIED CAT 5e (001-305M)

6. PACKING: 305M/R

CORE COLOR :

- blue/white&blue
- brown/white&brown
- orang/white&orang
- green/white&green

REMAKE:

1. THE ID AND OD OF THE WIRE MUST BE EXACT, CAN NOT REDUCE THE CENTRE.
 2. THICKNESS OF COAT BY EQUALITY: 0.5mm, THE LEAST THICKNESS: 0.45mm
 3. THICKNESS OF CORE BY EQUALITY: 0.2mm, THE LEAST THICKNESS: 0.18mm
 4. Impedance: 100 Ω ± 15%
- Rating temperature: -20°C to 60°C
Standards: ISO/IEC11801, ANSI TIA/EIA-568A

DRING NO.		PRODUCT NO.		TITLE:					
SAM-AC-0032				CAT5E UTP 0.50BC					
APPROVED BY	CHECKED BY	DRAWN BY	CUSTOMER	PAGE	UNIT	SCALE		REV	
				1 of 1	mm				
VCOM International Ltd.								RESCRIPITION	DATE
									2010-9-30

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ethernet Cables / Networking Cables](#) category:

Click to view products by [VCOM](#) manufacturer:

Other Similar products are found below :

[0152660053](#) [603020002](#) [73-7797-25](#) [73-8890-10](#) [73-8890-14](#) [73-8891-14](#) [73-8891-25](#) [73-8892-50](#) [73-8894-10](#) [73-8894-3](#) [73-8895-14](#) [73-8896-7](#) [MCJB2-10P6Q7-120](#) [84909-0204](#) [9QA0-111-12-3.00](#) [1200650742](#) [1200700174](#) [1200860368](#) [1200650013](#) [1201080008](#) [1-21919-1](#) [1300500373](#) [1300101844](#) [1300101845](#) [130050-0004](#) [1300500014](#) [1410147](#) [E16A06002M030](#) [E200102-009-S1](#) [MT14-187L](#) [17-103530](#) [NK5EPC18RDY](#) [NK5EPC18VLY](#) [NK5EPC18YLY](#) [NK5EPC1GRY](#) [NK5EPC30BLY](#) [NK5EPC30VLY](#) [NK5EPC30YLY](#) [NK5EPC4Y](#) [NK5EPC6YLY](#) [NK5EPC8BLY](#) [NK5EPC9YLY](#) [NK6PC30BUY](#) [NK6PC30GRY](#) [NK6PC30RDY](#) [NK6PC30Y](#) [NK6PC30YLY](#) [1969343-6](#) [C501100010](#) [C501106002](#)