



UBT

■ Dimensions

V(Code)		10 (1A)			16 (1C)			25 (1E)			35 (1V)			50 (1H)		
Cap. (μF)	Item Code	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )
4.7	4R7															
10	100													8 × 11.5	1.15	85
22	220													8 × 11.5	0.75	180
33	330													8 × 11.5	0.50	250
47	470													8 × 11.5	0.45	300
100	101				8 × 11.5	0.32	340	8 × 11.5	0.13	500	10 × 12.5	0.15	620	8 × 11.5	0.35	440
220	221	8 × 11.5	0.26	340	10 × 12.5	0.15	620	10 × 12.5	0.10	680	10 × 16	0.094	790	10 × 20	0.18	555
330	331	10 × 12.5	0.15	620	10 × 12.5	0.10	680	10 × 16	0.075	945	10 × 20	0.075	950	12.5 × 20	0.098	930
470	471	10 × 12.5	0.10	680	10 × 16	0.075	945	10 × 20	0.057	1100	12.5 × 20	0.058	1330	12.5 × 25	0.070	1330
1000	102	10 × 20	0.057	1100	12.5 × 20	0.042	1490	12.5 × 25	0.033	1750	16 × 25	0.031	2010	16 × 31.5	0.031	2430
2200	222	12.5 × 25	0.033	1750	16 × 25	0.024	2300	16 × 31.5	0.020	2710	18 × 35.5	0.025	2790			
3300	332	16 × 25	0.024	2300	16 × 31.5	0.020	2710	18 × 31.5	0.017	3310						
4700	472	16 × 31.5	0.020	2710	18 × 31.5	0.018	3270									

V(Code)		63 (1J)			80 (1K)			100 (2A)		
Cap. (μF)	Item Code	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )
10	100							8 × 11.5	1.50	150
22	220	8 × 11.5	2.00	130	8 × 11.5	1.50	150	10 × 12.5	0.80	480
33	330	8 × 11.5	1.50	150	10 × 12.5	0.80	480	10 × 12.5	0.80	480
47	470	10 × 12.5	0.59	530	10 × 12.5	0.80	480	10 × 16	0.55	630
100	101	10 × 16	0.41	690	10 × 20	0.39	790	12.5 × 20	0.25	990
220	221	12.5 × 20	0.16	1050	12.5 × 25	0.18	1240	16 × 25	0.11	1500
330	331	12.5 × 25	0.12	1290	12.5 × 31.5	0.16	1390	16 × 31.5	0.079	1790
470	471	12.5 × 31.5	0.097	1460	16 × 25	0.11	1500			

Rated ripple current (mA<sub>rms</sub>) at 125°C 100kHz  
Impedance (Ω) MAX. at 20°C 100kHz

● Frequency coefficient of rated ripple current

V	CV	Frequency			
		120Hz	300Hz	1kHz	10kHz or more
10 to 100	1000 > CV	0.50	0.64	0.83	1.00
	1000 ≤ CV	0.67	0.79	0.91	1.00

V(Code)		160 (2C)		200 (2D)		250 (2E)		350 (2V)		400 (2G)		450 (2W)	
Cap. (μF)	Item Code	Case size φD × L (mm)	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Rated ripple (mA <sub>rms</sub> )
4.7	4R7							10 × 20	53	10 × 20	53	10 × 25	58
10	100			10 × 20	78	10 × 20	78	10 × 25	85	10 × 25	86	12.5 × 20	86
22	220	10 × 20	115	10 × 25	126	12.5 × 20	128	12.5 × 25	139	12.5 × 31.5	142	16 × 25	154
33	330	10 × 25	154	12.5 × 20	157	12.5 × 25	171	16 × 25	189	16 × 25	189	16 × 31.5	203
47	470	12.5 × 20	187	12.5 × 25	204	16 × 25	225	16 × 31.5	243	16 × 31.5	243		
68	680	12.5 × 25	245	16 × 20	250	16 × 31.5	292						
100	101	16 × 25	329	16 × 25	329								
150	151	16 × 31.5	434										

Rated ripple current (mA<sub>rms</sub>) at 125°C 120Hz

● Frequency coefficient of rated ripple current

V	Cap. (μF)	Frequency					
		50Hz	120Hz	300Hz	1kHz	10kHz	100kHz or more
160 to 450	4.7 to 33	0.75	1.00	1.25	1.50	1.75	1.80
	47 to 150	0.80	1.00	1.15	1.30	1.40	1.50

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Aluminium Organic Polymer Capacitors](#) category:*

*Click to view products by [Nichicon](#) manufacturer:*

Other Similar products are found below :

[MPP684J4240815LC](#) [B32529C0222J000](#) [PCZ1V181MCL1GS](#) [PCZ1V221MCL1GS](#) [PCZ1E331MCL1GS](#) [PCZ1E271MCL1GS](#)  
[PCZ1E151MCL6GS](#) [ECASD40E337M009KA0](#) [HVK-63V100MF61E-R2](#) [UBT1V102MHD8](#) [UBT2A221MHD8](#) [UBT2C330MPD8](#)  
[35PZE270M10X9](#) [35PZF270M10X9](#) [ULR128M0GF08](#) [ULR187M1CF1ARRX0CR](#) [ULR277M0JE08RRX0CR](#) [ULR337M0JE08RRX0CR](#)  
[ULR477M0JF08](#) [ULR567M0EE08RRX0CR](#) [ULR567M0JF08](#) [ULR827M0JF1A](#) [UPE0E561MNN6308](#) [ULR337M1CF08](#)  
[ULR108M0JF1ARRX0CR](#) [ULR108M0JF08RRX0CR](#) [UPE0E471MNN6308](#) [ULR477M0ED09RRX0CR](#) [ULR128M0JF1ARRX0CR](#)  
[UBT1J470MPD8](#) [63PZE56M10X9](#) [50PZF100M10X9](#) [63PZF56M10X9](#) [A750KK477M1AAAE016](#) [A755MS477M1CAAE013](#)  
[EEFCD0J470R](#) [50SEK33M](#) [ULR277M1CF1A](#) [ULR158M0EF1ARRX1CR](#) [ULR477M1CG1B](#) [EEUEB1H471](#) [A755MS158M0JAAE013](#)  
[A759MS686M1JAAE047](#) [25PZE330M10X9](#) [A755KS227M1EAAE025](#) [A759BQ106M1VAAE090](#) [A759KS106M2CAAE110](#)  
[SMPC\\_224K0630DB2315](#) [EEF-HX1E150R](#) [KJ2G820MNN1830](#)